

AD-A270 018



The Department of Defense

DOD DEPARTMENTS/AGENCIES:




Department of the Army



Department of the Navy



Department of the Air Force





Advanced Research Projects Agency



Defense Nuclear Agency



Strategic Defense initiative Organization

DEFENSE SMALL BUSINESS INNOVATION RESEARCH PROGRAM (SBIR)

This document has been approved for public release and sale; as distribution is uniformed.

93-22838

FY 1992 SBIR SOLICITATION PHASE I AWARD ABSTRACTS ARMY PROJECTS

VOLUME I

DTIC QUALITY INSPECIED &

Accesion For	
NTIS COASI	7
DTID OF D Under the lead	_
Jan School Community	
By A25250	· 1
Dut ibidon!	
Dut ibulion! Ave soldly sk	. '65
Dut ibidon!	. '65

TABLE OF CONTENTS

reface	j
troduction	¥
RMY Projects	Į
ross Reference	
by Firm Name 8	5
by Army Topic Number	3

This report presents the technical abstracts of the Phase I proposals that resulted in contract awards from the Fiscal Year 1992 Solicitations of the Department of Defense (DoD) Small Business Innovation Research (SBIR) Program. The Army, Navy, Air Force, Defense Advanced Research Projects Agency (DARPA)¹, Defense Nuclear Agency (DNA), and Strategic Defense Initiative Organization (SDIO) are the DoD components of the SBIR Program. Two solicitations inviting small business firms to submit proposals under this program were published in FY92. Navy, Air Force, DARPA¹, DNA, and SDIO participated in Program Solicitation 92.1 (Closing Date: 10 January 1992), and Army, Navy, and DARPA¹ participated in Program Solicitation 92.2 (Closing Date: 1 July 1992). The selection of proposals for funding was made from proposals received by the Military Services and Agencies.

FY 1992 SBIR PROGRAM

	Number of Topics		Proposals Received		Phase 1 Awards	
	<u>92.1</u>	92.2	<u>92.1</u>	92.2	92.1	92.2
Army	0	177	0	1841	0	260
Navy	106	82	1495	832	127	92
Air Force	181		2128		229	
DARPA ¹	129	97	1301	911	105	77
DNA	25		172	*-	22	
SDIO	16		734		209	
Total	457	356	5,830	3,584	692	429
Grand Total	813		9,414		1,121	

Of the 1,121 Phase I awards, 158 awards went to minority-owned businesses and 95 awards were to woman-owned businesses. Overall, 12 percent of the FY92 SBIR proposals were selected for funding.

In order to make information available on the technical content of the Phase I projects supported by the DoD SBIR Program, four volumes containing the abstracts and contracts for the awarded projects are published. The small business information with accompanying abstract are arranged in alphabetical order by firm name. Cross reference indices appear at the back of the volume for quick reference.

- Volume I contains Army Projects
- Volume II contains Navy Projects
- Volume III contains Air Force Projects
- Volume IV contains DARPA, DNA and SDIO Projects

Venture capital and large industrial firms that may have an interest in the research described in the abstracts in this publication are encouraged to contact the firm whose name and address is shown.

¹ As of March 15, 1993, DARPA changed its name to Advanced Research Projects Agency (ARPA). However, DARPA is used in this publication because the FY92 topics were issued and awards were made under the DARPA name.

INTRODUCTION

In 1982, Congress enacted and the President signed the "Small Business Innovation Development Act of 1982" (Public Law 97-219), which created the Small Business Innovation Research (SBIR) Program to give small, high-technology firms a greater share of the federally-funded research and development contract awards.

Under the SBIR Program, each federal agency with an extramural budget for research or research and development in excess of \$100 million per fiscal year must establish an SBIR Program. The program is funded by setting aside 1.25 percent of the participating agency's extramural R&R&D contracting dollars. The agencies participating in the Department of Defense SBIR Program are the Army, Navy, Air Force, Defense Advanced Research Projects Agency (DARPA). Defense Nuclear Agency (DNA), and Strategic Defense Initiative Organization (SDIO).

The objectives of the DoD SBIR Program include stimulating technological innovation in the private sector, strengthening the role of small business in meeting DoD research and development needs, encouraging participation by minority and disadvantaged persons in technological innovation, and increasing the commercial application of DoD supported research or research and development.

The SBIR Program consists of three distinct phases. Under Phase I, DoD components make awards to small businesses, typically of up to one man-year of effort over a period of six months, subject to negotiation. Phase I is to determine, insofar as possible, the scientific or technical merit and feasibility of ideas or concepts submitted in response to SBIR topics. Proposals selected for contract award are those which contain an approach or idea that holds promise to provide an answer to the specific problem addressed in the topic. Successful completion of Phase I is a pre-requisite for further DoD support in Phase II.

Phase II awards will be made only to firms on the basis of results from the Phase I effort, and the scientific and technical merit of the Phase II proposal. Proposals which identify a follow-on Phase III funding commitment from non-Federal sources will be given special consideration. Phase II awards will typically cover two to five man-years of effort over a period of 24 months, also subject to negotiation. The number of Phase II awards will depend upon the success rate of the Phase I effort and availability of funds. Phase II is the principal research or research and development effort, and requires a comprehensive proposal outlining the intended effort in detail.

In Phase III, an innovation is brought to the marketplace by private sector investment and support. No SBIR funds may be used in Phase III. Also, under Phase III, DoD may award follow-on contracts with non-SBIR funds for products and processes meeting DoD mission needs.

Proposals received in response to a DoD solicitation are evaluated on a competitive basis in the organization which generated the topic, by scientists and engineers knowledgeable in that area. Selections for Phase I are made in accordance with the following criteria:

- The scientific/technical quality of the research proposal and its relevance to the topic description, with special emphasis on its innovation and originality.
- Qualifications of the principal investigator, other key staff, and consultants, if any, and the adequacy of available or obtainable instrumentation and facilities.
- Anticipated benefits of the research to the total DoD research and development effort.
- Adequacy of the Phase I proposed effort to show progress toward demonstrating the feasibility of the concept.

The "Small Business Innovation Act of 1986" (P.L.97-443) extended the "Sunset Clause" to 1993 and increased the taxation of the extramural research and development budget to 1.25 percent. The latest SBIR re-authorization law (P.L. 102-564), signed October 28, 1992, extends the program through 2000, doubles the taxation to 2.5 percent by 1997, and increases the average Phase I and Phase II award agreements.

4D VIDEO 3136 PAULINE DRIVE

SEBASTOPOL, CA 95472 Phone: (707) 829-8883

Topic#: 92-018

Office: AVSCOM Contract #:

Pl: James S. Walton, Ph.D.

ID#: 92AVS-098

ID#: 92AVS-143

ID#: 92SS -006

Title: An Investigation of the Feasibility of Using Video-Based Motion Measurement for Recovering Helicopter Blade Kinematics Abstract: Traditionally, kinematic measurements have been made using electro-mechanical transducers which produce a signal which is proportional to the parameter being measured. This approach is unlikely to be replaced by optical tracking techniques, but there are many instances where it is impractical (or even impossible) to attach a mechanical device to the subject. The blades of a helicopter rotor are an excellent case-in-point. While a better understanding of blade kinematics is fundamental to the design of the aircraft, it is difficult to recover three-dimensional kinematics by traditional means under operational conditions. 4D Video believes that an image-based motion measurement system can be used to quantify the rigid-body dynamics of helicopter rotor blades under operational conditions. We propose to investigate the most appropriate means for achieving this objective. Our purpose is to develop a specification which will form the foundation of an SBIR Phase II proposal to develop new hardware and software to perform the required tasks. For the purpose of the present proposal, our effort will focus on two issues: sample-rate, and the development of a customized (circular) tracking algorithm which will take maximum advantage of the predominant motions of the rotor blades. However, other issues have been identified and will be addressed.

ABTECH CORP. 700 HARRIS STREET CHARLOTTESVILLE, VA 22903

Phone: (804) 977-0686

Topic#: 92-022

Office: AVSCOM Contract #:

Topic#: 92-034

Office: CECOM

PI: Gerard J. Montgomery

Title: Expert Polynomial Network Turbine Engine Di gnostician

Abstract: The objective of this effort is to demonstrate a prototype advanced diagnostic system for the T800 turboshaft engine using a hybrid polynomial network and production-rule expert system. The resulting system will demonstrate the feasibility of developing a revolutionary diagnostic capability which can model the engine at a system level, detect failures before they become significant isolate faults, estimate the loss of efficiency of various engine components, and predict future faults. AbTech has developed an innovative network approach, called polynomial networks, based on over a decade of research in neural networks and advanced statistics. Polynomial networks are simply networks of very powerful high-order polynomial equations. It discusses how networks can be applied to substantially increase the control and diagnostic capabilities of systems in a practical and very cost-effective manner. It then details a specific project to integrate and apply the existing AIM software and a production-rule system to T800 engine diagnostics.

ADROIT SYSTEMS, INC. 209 MADISON STREET ALEXANDRIA, VA 22314

Phone: (703) 684-2900

Contract #: PI: Richard D. Jurgens Title: Autonomous, Hand-Held Satellite Location and Pointing System (SLAPS)

Abstract: Adroit Systems, Inc. proposes to develop a hand-held, autonomous Satellite Location and Point System (SLAPS). The system will store communication satellites' ephemeris data to calculate and display visibility windows. SLAPS also will use this data to calculate the azimuth and elevation angle to the communication satellite of interest. The system will use interferometry of Global Positioning System (GPS) satellite signals to determine its pointing angle. The user will be guided to the proper pointing angle by a visual display and audio cueing. Using GPS to determine the pointing angle to the satellite confers additional benefits on the user. The user will have his position and time in a universal reference frame used by the rest of the military. A pointing system based on GPS does not have to be calibrated, and is made of rugged, solid state electronics with no moving parts or optics. It will work in all latitudes because it is not susceptible to magnetic field deviations. In Phase I, Adroit proposes to develop the system and component functional specifications. These specifications will be used to determine the feasibility of the concept. A design methodology will then be developed in anticipation of prototyping SLAPS in Phase II.

ADVANCED COMPUTER SUPPORT COMPANY 3000 SOUTH ROBERTSON BOULEVARD, SUITE 400

LOS ANGELES, CA 90034

Phone: (310) 815-4858

Title: Data Distribution Technology

Topic#: 92-038 Office: CECOM

Contract #:

PI: Dr. Anat Gafni

Abstract: This proposal describes a system architecture that we propose to implement as a programmer's toolkit for the triggered distribution of information within a distributed object-oriented database. The system architecture permits sudden appearance and disappearance of data objects, understands that the communication infrastructure can be temporarily partitioned, and guarantees that rule firings cannot cause unstable, non-terminating sequences of updates. The architecture permits a spectrum of data consistency algorithms and database transaction models. The data object structure allows procedures within the object to be preceded by a pre-condition that can check permissions, legitimate input values and data integrity prior to execution. Post-conditions implement consistency checking, replication of objects and processes, and triggers that further activate other procedures or other objects. Triggers enable versioning of objects. The toolkit consists of routines to communicate updates and register rules and triggers between databases. The architecture supports the efficiency discovery of objects that merit attention. It permits dynamic changes in the rule set, yet provides an efficient indexing mechanism to avoid evaluating triggers needlessly.

ADVANCED MATERIALS CORP.

100 N. BELLEFIELD AVENUE, SUITE 861 PITTSBURGH, PA 15213

Phone: (412) 268-3469

Title: Non-Cooperative Combat Identification using Multispectral Imaging

Topic#: 92-035 Office: CECOM

Contract #:
PI: L.J. Denes

Abstract: We propose development of a 'smart' optical preprocessor that installs as an integral part of the light gathering optics of first- or second-generation forward looking infrared imaging systems (FLIRs). This optical preprocessor is based on an advanced-art imaging acousto-optic tunable filter (aka, A-O filter). These newly-configured A-O filters are programmable to seek out specific spectral features of any potential target, at video rates, with throughputs approaching 100%, and with diffraction-limited clarity. One device can be made to operate from the UV to the mid IR. This versatility far surpasses any other spectral imaging approach. Every object has (or can be given in painting) a unique IR optical signature. In our concept, emblems or flags' are painted on friendly targets giving unique IR signatures but still camouflaged in the visible spectrum. These paints are modified formulations of camouflage coatings. Two example approaches are deuterated-modified and IR laser dye-modified polyurethane camouflage paints. Deuterated-modification shifts the IR absorption bands around 3.4 um while IR laser dyes will provide intense absorption lines in the near IR 90.7-1.1 um). Non-friendly targets, of course, can also be directly acquired and identified using the same optical preprocessor hardware. Once their IR spectral signatures are known, camouflaged targets used by foes can be isolated from background clutter. In other missions, objects such as vegetation types (i.e. coca plants) or vapor cloud hazards (e.g., chemical, biological or carcinogenic) can also be identified through their optical signature.

ADVANCED MECHANICAL TECHNOLOGY, INC.

151 CALIFORNIA STREET NEWTON, MA 02158

Phone: (617) 964-2042

Title: Diesel-Fired Self-Pumping Water Heater R&D

Topic#: 92-070 Office: NATICK

Contract #:

PI: Andrew D. Vasilakis

Abstract: A self-pumping water heater is proposed wherein a small portion of the water to be pumped is evaporated in a boiler and used to pressurize and heat the main stream of water. Unlike early slow direct-acting steam pumps, the proposed approach operates at moderate frequencies and is extremely compact. In Phase I, an analytical model describing the dynamics of the process would be formulated, and a proof-of-principle self-pumping water heater would be fabricated and tested.

ADVANCED SCIENTIFIC CONCEPTS, INC. 2020 ALAMEDA PADRE SERRA, SUITE 123 SANTA BARBARA, CA 93103

Phone: (805) 966-3331

Title: Assessment and Training of Metacognitive Skills

Topic#: 92-154 Office: ARI

Contract #:

PI: James Geiwitz, Ph.D.

ID#: 92NAT-086

ID#: 92C3 -032

ID#: 92NV -072

Abstract: Metacognitive skills that involve the monitoring and control of cognitive skills like problem solving develop in expert executives and appear to lead to great improvement in the problem solving process. We propose to study the topic of metacognition to construct a conceptual model that has three characteristics: 1) it will show the interrelationship of metacognitive skills and cognitive task performance so that 2) it will suggest the most valid assessment technique for the measurement of metacognitive skills and 3) it will show the development of metacognitive skills. From the third characteristic, we will design a training program to accelerate the acquisition of metacognitive skills in officers in the US Armed Forces. From the second characteristic, we will construct proficiency tests of metacognitive skills for measuring the level of these skills in commanders at various levels of professional development; the tests can also be used to evaluate the effectiveness of the training.

ADVANCED SYSTEM TECHNOLOGIES, INC.

12200 E. BRIARWOOD AVENUE, SUITE 260 ENGLEWOOD, CO 80112

Phone: (303) 790-4242

Topic#: 92-032

Office: CECOM Contract #:

PI: Dr. Robert T. Goettge

Title: Automated Design Tool Set for Reliability and Performance Evaluation of Fault-Tolerant Avionics Systems

ID#: 92AV -031

ID#: 92MIC-018

ID#: 92NV -037

Abstract: Reliability and performance are critical characteristics of the Army's avionics systems. These systems must meet stringent requirements in the areas of: (1) dispatchability, or operational readiness to support missions; (2) dependability, or the ability to perform critical functions correctly during the duration of the mission; and (3) responsiveness, or the ability to deliver computing services at rates sufficient to meet time-critical processing deadlines. Automated tools are needed to evaluate the implications of complex design alternatives in these areas of system effectiveness. Phase I research will determine the feasibility of an automated tool set for integrated evaluation of fault-tolerant avionics system reliability and performance. The tool set will consist of separate design capture, design translation, and design evaluation capabilities. Quantitative measures of effectiveness that will be produced by the tool set include system maintainability and availability, probability of avionics system failure during missions of given duration, and critical function response times and resource utilizations. Capabilities provided by existing automated tools, including the START tool for integrated reliability and performance analysis, as well as other reliability prediction tools such as HARP, SHARPE, and ARAM, will provide a starting point for the tool set specification to be developed in Phase I.

ADVANCED TECHNOLOGY AND RESEARCH CO

14900 SWEITZER LANE, SUITE 104

LAUREL, MD 20707

Phone: (301) 498-8200

Topic#: 92-060

Office: MICOM Contract #:

PI: Randy R. Kindsfather

Title: Day/Night Low Light Level (LLL) TV Sensors

Abstract: A low-cost, miniaturized Low Light Level (LLL) CCD TV camera system capable of more than 400 TV lines per picture height at an illumination level ranging from moonless starlight (10 E-4 foot candles) is proposed. The electro-optical portion of the system will incorporate an input lens with an electrically controllable iris, a GEN III image intensifier, a coupling lens and a 2/3-inch CCD. With careful design and component selection, a signal-to-noise ration of 9 or better can be achieved at low light level conditions while maintaining daylight operability. Digital techniques will be employed both to optimize image exposure and to reduce noise. Iris diameter, intensifier gain and shutter duration will be set through multi-zone metering and fuzzy logic control. Fixed pattern noise will be filtered by temporal averaging and edge-preserving spatial smoothing techniques. Multi-zone metering and all noise filtering algorithms will be implemented in hardware for video rate output. Performance of the final electro-optical design will be verified through a detailed math model, and that of exposure control and noise filtering will be verified through extensive computer simulation.

ADVANCED TECHNOLOGY MATERIALS, INC.

7 COMMERCE DRIVE DANBURY, CT 06810

Phone: (203) 794-1100

Title: Thermally Isolated PbTiO3 Uncooled Focal Plane Array Detector

Office: CECOM Contract #: Pl: David Kurtz

Topic#: 92-044

Abstract: Infrared sensors and sensor arrays are widely used in military and commercial applications such as night vision, medical diagnosis and weather mapping. Expensive quantum effect sensors, such as HgCdTe systems, must be cooled to liquid

nitrogen temperatures and are difficult to produce with uniform properties. A significant opportunity exists to dramatically improve detector fabrication and performance by employing thin film pyroelectric materials for the detector element. While encouraging pyroelectric properties have been reported in several ferroelectric materials, PbTiO3 is advantageous because of its high pyroelectric coefficient (40-90 nC/cm2.K at 297K), high Curie temperature (490 degrees C), mechanical and chemical resistance. PbTiO3 can be deposited in thin film form. However, unless thermal mass is minimized, pyroelectric sensitivity is severely reduced. ATM proposes to develop a thermally isolated micro air-bridge device using a novel MOCVD technique for PbTiO3 growth that will not only produce high pyroelectric sensitivity material, but also lead itself to c-axis oriented, high density array fabrication on a manufacturing scale with significantly reduced Pb toxicity hazards. The Phase II program will address fabrication and integration of high density detector arrays on silicon substrates containing CMOS circuitry.

ADVANCED TECHNOLOGY MATERIALS, INC.

7 COMMERCE DRIVE DANBURY, CT 06810 Phone: (203) 794-1100

Title: Improved Tungsten Penetrators

Topic#: 92-131

Office: MTL Contract #:

PI: Delwyn Cummings

Abstract: Kinetic energy penetrators are currently relied upon as a way to defeat enemy armor. Historically these penetrators have been composed of uranium or tungsten based alloys due to their high densities. In addition to density, the deformation behavior of the alloy determines it's performance. A penetrator whose tip mushrooms or fractures on impact is less effective than a penetrator that retains it's shape or has a tip that self sharpens. Although the densities of uranium and tungsten are similar, uranium alloys have generally exhibited deformation on impact that has resulted in better penetrator performance. The drawback with uranium alloys, however, is toxicity and cost. In this Phase I SBIR program, tungsten alloys will be processed in a variety of novel ways to improve their performance as penetrators. ATM proposes to produce large (>10 mm diameter) [100] oriented crystals of pure tungsten and W-Ni-Fe alloy rods with elongated and preferred orientation of the grains. The effect of rhenium additions will also be examined. X-ray diffraction, high rate compression testing, and optical microscopy will be used to assess the results.

AERONIX, INC. 1775 W. HIBISCUS BLVD. SUITE 3

MELBOURNE, FL 32901 Phone: (407) 984-1671

Topic#: 92-172 Office: SDC

ID#: 92SDC-026

ID#: 92MIC-021

ID#: 92MTL-169

Contract #:

Title: A Multi-Processor Embedded Data Processor for Multi-Object Detection & Tracking

Abstract: The Aeronix Phase I task will demonstrate the application of an innovative parallel processing computer architecture and parallel processing programming environment to a class of problems associated with the real time detection, recognition, acquisition and tracking of multiple objects in a high rate image sensor environment. The Phase I task will examine the problems associated with the multiplicity of objects in a large image data space and present a comprehensive process for the collection filtering, transformation and analysis of these objects across multiple processing elements. The Phase I task will map the Kinetic Energy Anti-Satellite program requirements on the Aeronix proprietary Embedded Data Processor (EDP) Architecture. The EDP is a space based Multi Instruction Multi Data Stream (MIND) parallel processing architecture for embedded data processing applications. The EDP offers significant increases in performance (up to 1000's of HIPS) over conventional architectures while improving overall system reliability and providing inherently high levels of fault tolerance.

AEROPRO SYSTEMS 6371 FIREFLY DRIVE SAN JOSE, CA 95120

Phone: (408) 997-1397

Topic#: 92-051

Office: MICOM Contract #:

PI: Gerald J. Wotel

Title: Tactical Missile Air Turbo Rocket Propulsion System Critical Components Definition Study

Abstract: The air turbo rocket (ATR) offers significant potential in terms of cost/performance ratio for tactical missiles. The high specific impulse of the ATR significantly increases range over solid rockets, while maintaining critical missile weight and launch system geometry constraints. The higher thrust levels of the ATR improve acceleration capability and rapid thrust control over a similar size turbojet. The program has two major tasks. Task 1 will develop an ATR cycle computer code, and be

executable on an IBM PC or compatible microcomputer. The cycle code will then be utilized to develop an ATR conceptual design. Rocket propellents will be evaluated and used in a mission analysis. The cycle code will be integrated into a two-dimensional trajectory simulation code. A parametric mission analysis will be conducted, varying ATR propulsion design parameters, and propulsion system size. Cycle parameters critical to achieving the mission goals will be identified. A design will be selected and mission performance variations determined for alternative propellants. An optimum design will then be selected and recommended. Task 2 encompasses the detailed design of the flightweight ATR propulsion system. A heavyweight test component will be designed and fabricated.

AKM ASSOC., INC.

635 MARINER'S ISLAND BLVD., SUITE 205

SAN MATEO, CA 94404

Phone: (415) 571-7910

Topic#: 92-090 Office: TACOM

Contract #:

PI: Dr. Asok K. Mukhopadhyay

ID#: 92TAC-149

ID#: 92AVS-074

ID#: 92TRA-019

Title: INTEGRATED TWO-MAN CREW STATION (ITCS) AI APPLICATION STUDY

Abstract: Tank Automotive Command (TACOM) of the U.S. Army has embarked on a major program called VETRONICS (Vehicle Electronics). VETRONICS envisions the application of state-of- the-art electronics systems in the form of an architecture that will integrate all the vehicle electronics and electrical systems including those directly related to combat. communications/command/control/intelligence(C3 I) and survivability functions. This system will enable future vehicles to utilize all the available information that results from the application of electronics technology on tomorrow's battlefield. An integral part of the VETRONICS program is the Integrated Two-Man crew station (ITCS). Normally a combat vehicle (i.e., battle tank) carries four crew members commander, driver, gunner and loader. When the crew size is reduced to two, viz, to the commander and the gunner, many tasks will be forced to be autonomous or semiautonomous not to overload the two-man crew. ITCS will go a long way to prove the fieldability of a two-man crew in a combat vehicle. The proposed Phase I effort will consist of an indepth study of Artificial Intelligence (AI) techniques and their possible applications that would be necessary to develop the ITCS. Tradeoff studies of existing hardware and software will be conducted. The effort will also consist of identification of other features to enhance future combat vehicles using AI. The Phase II effort will consist of determining the two most critical AI functions for development of the ITCS and developing the needed hardware and software for those functions for integration into the ITCS.

AMERICAN GNC CORP. 9131 MASON AVENUE CHATSWORTH, CA 91311

Phone: (818) 407-0092

Title: Rotorcraft-Specific Reconfigurable Flight Control System

Topic#: 92-013 Office: AVSCOM

Contract #:

PI: Ching-Fang Lin

Abstract: Advanced rotorcraft systems are highly complicated and have become prime targets for enemy anti-air weapons. Thus, battle-induced damage can be anticipated. To increase the availability, combat survivability, maintainability, and life-cycle cost effectiveness of advanced rotorcraft, reconfigurable flight controls are needed. In this project, a rotorcraft-specific reconfigurable flight control system is developed. This system addresses unique characteristic of the rotorcraft system which is not surface-rich in comparison to its fixed-wing counterpart. The fuzzy logics are used to furnish inflight fault detection. onboard expert diagnosis evaluation, and real-time fault accommodation functions. A two layer arrangement of fuzzy logics are also used for mode blending to enhance pilot handling qualities. Simulations are used to verify and quantify the performance of the fuzzy reconfigurable flight control system. In Phase II, the design, both software and hardware, will be implemented and tested in a hardware-in-the-loop environment.

AMERICAN POWER JET COMPANY

705 GRAND AVE

RIDGEFIELD, NJ 07657

Phone: (201) 945-8203

Topic#: 92-177

Office: TRADOC

Contract #: DABT60-93-C-0006

PI: George Cherowitz

Title: Concept-Based Requirements Decision Support System (CBRDSS)

Abstract: The application of modern Computer Assisted Engineering (CASE) tools is proposed to address the development of the decision support system architecture concept. This technique has been applied to similarly complex and interrelated

large-scale enterprises, in which inputs from a very large diversity of data sources must be appropriately integrated and modeled. APJ has demonstrated the viability of structured system analysis using CASE in the process of organizing the contents of MIL-STD-1358-1A and AR 700-127, as well as the Navy Logistics System. Our approach to program integration and prioritizet on has been successfully applied to a series of Army and Navy programs. This technique provides a structure for orga et ang decision support and effective application of Artificial Intelligence(AI). The result is an architecture for rational Army program integration and prioritization of the Battlefield Laboratory/ Louisiana Maneuver process.

AMERICAN RESEARCH CORP. OF VIRGINIA

PO BOX 3406

RADFORD, VA 24143

Phone: (703) 731-0655

Topic#: 92-099

Office: ARO Contract #:

PI: Dr. Adel K. Sarrafzadeh

ID#: 92ARO408

ID#: 92MIC-132

ID#: 92AVS-005

Title: Digital Speckle Imaging for In Situ Monitoring and Characterization of Laser-processed Refractory Coatings Abstract: The use of high-temperature laser densification/annealing techniques for enhancing materials surface characteristics has opened new opportunities in material/laser-process diagnostic instrumentation. Important issues in fabrication of reproducible refractory ceramic coating film lies in understanding of the interrelationship between processing parameters and surface properties. To respond to this need, the proposed project involves the development of diagnostic instrumentation based on laser speckle imaging for in situ process monitoring and quantitative characterization of high-temperature structural ceramic coating properties. The program is innovative in correlating process parameters relating to coating-sensitive properties at temperatures exceeding 1500 degrees C. Variations in surface-reflected optical images in terms of speckle spatial frequencies and correlation intensities, due to different glass phase transformations, will identify characteristic signatures associated with film formation. Phase I Technical Objectives include the analysis of randomly scattered laser speckle characteristics for optically rough surface coatings, evaluation of laser speckle imaging techniques for measurement of micro-surface properties, assessment of empirical correlation on experimental parameters and optimization of a proof-of-concept instrumentation for in situ monitoring of laser-processed refractory ceramic coating films.

ANALATOM, INC. 1183 BORDEAUX DRIVE #1 SUNNYVALE, CA 94089

Phone: (408) 734-9392

Topic#: 92-064

Office: MICOM Contract #:

PI: J. Altman, Ph.D.

Title: Organically Modified Silicates as a Solid Host for Organic Laser Dyes

Abstract: The proposed Phase I work will constitute a study of prospective organic dye host materials, fabrication techniques, AR/HR/PR (Anti-Reflection/High Reflection/Partial Reflection) optical coatings (specific to the selected host material), and factors which are relevant to optical pumping with flashlamps or equivalent sources. Special emphasis will be placed upon organically modified silicates (ORMOSIL's). Because of our current expertise in the field we believe Analatom occupies a leadership position in the development of ORMOSIL's for solid state dye lasers, we are especially well qualified to pursue this line of research/development at the present time. The principal investigator for this project has been intimately involved in solid state dye laser development for the past two years. Our goal for the proposed work will be to extend the present dye lifetimes in a solid state ORMOSIL, or other as yet unidentified host, by an order of magnitude or more over current lifetimes while maximizing optical conversion efficiency. We have evidence to indicate that the stated goals are very realistic ones and should be readily achieved during the course of the contract.

ANALYTIC DESIGNS, INC. 245 EAST GAY STREET COLUMBUS, OH 43215

Phone: (614) 224-9078

Title: LO Rotor Blade De-Ice Systems Evaluation

Topic#: 92-006 Office: AVSCOM

Contract #:

PI: Dr. Harry Shamansky

Abstract: This proposal investigates candidate main rotor blade de-icing systems which offer signature reduction capabilities. In comparison to traditional mechanical boot style de-icing systems, electrical de icing systems are considered. One such candidate is a novel electrical thin film resistive de-icing system, which shows potential to lower the RCS levels associated with main rotor blade systems. This de-icing approach is a modified form of resistive heating. The resistive element is comprised

of a thin sheet of resistive material in the areas of ice accretion on the rotor blade surfaces. In contrast to traditional resistive heating where highly conductive wires are used, a film of resistive material can be used to achieve the desired low observable (LO) specifications. This approach would be applicable as both an ice prevention technique and a descing technique. Basic evaluation of this approach will be performed through numerical and experimental investigation. Comparisons will be made to the traditional mechanical and electrical de-icing systems with various signature reduction techniques to assess the viability of the thin film resistive de-icing system.

ANALYTIC DESIGNS, INC. 245 EAST GAY STREET COLUMBUS, OH 43215

Phone: (614) 224-9078

Title: Bi-Static Chaff Signature Modeling

Topic#: 92-139

Topic#: 92-007

Office: AVSCOM

ID#: 92VAL-005

ID#: 92AVS-013

ID#: 92TAC-053

Office: VAL Contract #:

Pl: Dr. Nan Wang

Abstract: The scattering behavior for a collection of thousands of linear dipoles at resonance has long been a subject of study for passive electronic countermeasures (ECM) against pertinent threat radar systems. Previously, the echo area of the radar cross section (RCS) of a chaff cloud has been calculated by multiplying the number of dipoles by the so-called "tumble average RCS" of a single dipole. Estimates based on this simple model have been poor. In this study a rigorous mathematical model based on the sinusoidal reaction formulation will be solved by the method of moments of the Galerkin type. Using a snap-shot model of various chaff geometries, possibly from a fractal based generator, both the mono-static and bi-static scattering signatures will be statistically characterized. Furthermore, the effects of aspect angle on chaff signatures will be quantified, and the correlation between the chaff signatures obtained at different look angles will be established.

ANALYTICAL DESIGNS, INC. 194 N. SUNNYVALE AVE. SUNNYVALE, CA 94086

Contract #: Phone: (408) 732-2927 PI: Brian Howley Title: Control System for Model Scale Semi-Autonomous Rotorcraft Research Vehicle

Abstract: The purpose of this study is to explore and develop the best candidate attitude control system to maximize the FFRRV flight envelope and handling qualities for various rotorcraft configurations. The intent is to provide a controls design methodology which allows hardware and software reconfigurations and leverages the ease and simplicity of down loading design parameters to a well defined and robust adaptive control system. An automated controls design will be computer implemented and used to determine the appropriate gains and filters given the FFRRV configuration. This will then be down loaded as machine code using a commercially available auto-code generator to a flight processor commanding a defined architecture of multiple control loops i.e. torque, rate, attitude and velocity loops. Off the shelf commercial grade hardware for inertial instruments, transmitters/receivers, and electric servos/controller will be compiled and evaluated for modularity and maintainability. Both modern and classical controls techniques will be explored.

ANALYTICAL SERVICES & MATERIALS, INC.

107 RESEARCH DRIVE HAMPTON, VA 23666

Phone: (804) 865-7093 Title: Refined Reduced Order Models for Estimation of Terrain Induced Loads in Flexible Vehicles

Topic#: 92-082

Office: TACOM Contract #:

PI: Charles L. Blackburn

Abstract: The new aerospace materials are finding applications in the design of military armor vehicles. However, the effect on ride quality, fire control, and internal structural loads due to the increased flexibility of these new vehicles must be ascertained by dynamic analysis. The size of models required to simulate these flexible body effect can be prohibitive from both cost and time perspective. Therefore, this proposal is directed to the development of a technique for obtaining a refined reduced order model that can accurately predict the response of a vehicle over a frequency range of concern and lends itself to

application during the design and structural optimization phase.

ANALYTICAL SPECTRAL DEVICES, INC. 4760 WALNUT STREET, SUITE 105 BOULDER, CO 80301

Phone: (303) 444-6522

Title: Submersible Ice Spectroradiometer

Topic#: 92-145

ID#. 92CRR-007

ID#: 92ARD-059

ID#: 92NAT-055

Office: CRREL

Contract #: DACA33-93-C-0007 PI: Alexander F.H. Goetz

Abstract: Measuring light transmission through sea ice in arctic regions is important to the understanding of the biological potential, the regional heat and mass balance, and for the investigation of possible through-ice communications. Past measurements have been made with a submersible scanning spectroradiometer. In this study a design will be developed for a two-spectrometer instrument to measure simultaneously the surface irradiance with a standard cosine receptor and the under-ice irradiance by means of submersible cosine receptor-fiberoptic bundle coupled to the surface spectroradiometer. Three types of underwater cosine receptors will be tested. A modification to an existing PSII spectroradiometer will be made to accommodate a CCD area array detector, and temperature sensitivity to -30 degrees C will be measured. Scattered light measurements will be carried out on an existing LabSpec to test the holographic grating order separation filter combination for light leakage. An absorption filter will be specified to reduce the peak sensitivity region of the array to increase the dynamic range at short and long wavelength. An investigation will be made to define the best method to maintain a one hour battery charge life in temperatures reaching -30 degrees C. The Phase I study will last for six months.

ANAMET LABORATORIES, INC 3400 INVESTMENT BLVD. HAYWARD, CA 94545

Phone: (510) 887-8811

Topic#: 92-001 Office: ARDEC

ARDEC

Contract #:
PI: Rocky Richard Arnold, PH.

Title: Frangible Ammunition Containers

Abstract: The objective of this Phase i work is to develop and demonstrate that a frangible munitions container, one capable of passing an Insensitive Munitions (IM) cook-off test, can be presumed with a low-cost modification to the container can. The critical problem associated with existing containers is the rapid development of combustion gases and high pressures which cause the container to literally explode creating fragments which, in turn, promulgate the fire and create ancillary explosions. The design goal is thus to provide a modification to the can that will allow venting of the combustion gases without the creation of fragment. The innovative solution provided herein relies upon the use of fracture mechanics theory and analysis to define the geometry of a crack starter machined into the surface of the can. ' is informative to note that within the time period that the pressure in the container rises to critical levels (approximately 10 milliseconds), a properly configured crack starter can cause the generation of over 31 feet of crack surface. This significant level of crack formation allows for more than sufficient venting to prevent explosion and fragment formation. The key element of the innovative approach relies upon the use of stateOor-the-art fracture mechanics technology and stress analyses to define the precise dimensions of the crack starter. Also, since the number of potential crack starter geometries is virtually unlimited, it is necessary in this research, to define the configuration most efficient and reliable. It is noted that this approach, once demonstrated, provides an extremely low-cost and reliable solution to the problem of venting. Phase I work will develop and demonstrate the feasibility of the innovative approach providing the Army with a highly effective system with concomitant low risk.

APPLIED POLYMER SYSTEMS, INC. 4302 E. 10TH AVE., #404 TAMPA, FL 33605

Phone: (813) 247-3065

Title: Development of Flexible EMI Shielded Materials

Topic#: 92-068

Office: NATICK Contract #:

Pl: William W. Bristowe, Ph.D.

Abstract: A novel plasma spray process allows for a highly metallic filled thermoplastic to be deposited on assorted cloth substrates, to create a flexible EMI construction material. Filler causing the EMI property to occur is dry-mixed into the thermoplastic, and the coating composition is created in situ on the cloth surface. Highly filled coatings are achievable, which previously have been denied due to rheological restrictions of using a high solids blend. Metallic fillers are proposed as the EMI shielding agent. Flexible, weather resistant the moplastics are used as the bonding matrix for these active fillers. Excellent adhesion to the substrate is attained during the plasma process due to chemical grafting, which is caused by the plasma exposure. Cloth can be from any origin, although a synthetic ther composition such as nylon, polyester, Nomex, or fluorinated polymer, would be preferred.

APPLIED RESEARCH ASSOC.

330 WEST 42 STREET NEW YORK, NY 10036

Phone: (617) 862-7020

Title: Impulse Radar Electronic Support Measures (ESM) Techniques

Topic#: 92-033 Office: CECOM

Contract #:

PI: William J. Crosby

ID#: 92EW -043

ID#: 92SDC-009

ID#: 92MIC-099

Abstract: An innovative ESM impulse detection and processing concept is described, incorporating three individual, but complementary, wideband processors used in selected combinations to provide a versatile and cost effective design which can be scaled to the anticipated battlefield or civilian environment. A program is proposed to determine performance and implementation of the individual processors and the combinations in which they are best employed as a function of various impulse environments.

APPLIED TECHNOLOGY ASSOC., INC.

1900 RANDOLPH ROAD SE ALBUQUERQUE, NM 87106

Phone: (505) 247-8371

Title: HIGH ENERGY LASER WAVEFRONT ANALYSIS

Topic#: 92-170 Office: SDC Contract #:

PI: Robert Pierson

Abstract: There is a need for a reliable High Energy Laser Wavefront Analyzer (HELWA) to be used for beam quality testing at the Army's High Energy Laser Systems Test Facility (HELSTF). Accurate HEL wavefront measurements are critical to HEL device performance evaluation. Current devices are inflexible and difficult to maintain due to size, complexity, and a dependence of high precision moving parts. This effort will investigate the feasibility of constructing a reliable integrated wavefront sensor suitable to the HEL community and adaptable to other applications. A low maintenance high reliability wavefront analyzer is attainable by integrating innovations from two areas. The first area involves the coupling of commercially available microlenslet technology with modern infrared detector arrays; the resulting compact Hartmann wavefront sensor is a sturdy and adaptable phase and intensity sampling device capable of high spatial and temporal resolution. The second area of innovation encompasses ATA's advanced wavefront reconstruction and wavefront sensor simulation algorithms. By combining these processing, visualization, and diagnostic tools with the appropriate lenslet arrays, optics, and IR cameras, ATA will seek to design a system customized to the Army HEL operation, but flexible enough to adapt to other government and commercial applications.

ATLANTIC AEROSPACE ELECTRONICS CORP. **470 TROTTEN POND ROAD**

WALTHAM, MA 02154 Phone: (617) 890-4200

Title: Fractal Analysis of Multi-Band IR Imagery for Target Acquisition

Topic#: 92-059 Office: MICOM Contract #:

PI. Tame Peli

Abstract: It is proposed to develop and demonstrate a new signal processing approach for acquiring low contrast military targets in multi-band IR imagery. This new computationally efficient processing methodology has been shown to provide significant better detection/discrimination results in single-band long wave FLIR imagery as well as in the acoustic, SAR and visible optics domains. Atlantic Aerospace has emerged as the technical leader in developing and applying this technology to defense-related problem areas. We believe that the same generic approach appropriately modified to reflect the structural and textural characteristics of high value targets and typical backgrounds in multi-hand IR imagery, will provide significant new capability and substantial performance gains for automatic target acquisition. In this Phase I program we will utilize our previously developed morphology-based detection algorithm, that applies both size and amplitude constraint, at the pixel level, to identify potential areas of interest in multi-band IR imagery. For each of the detected areas we will perform fractal analysis independently in the available spectral bands. Our analysis methods will include the evaluation of fractal and high order signatures. The potential capability of the developed measures to automatically cue an operator or a fully automated process to areas of high value targets will be demonstrated. Although the primary interest of this Phase I program is on developing fractal-based measures for the discrimination of man-made objects from natural backgrounds, we will also analyze large patches of natural background and characterize their fractal properties in each spectral band. The emphasis will be on parameterization most appropriate for scene generation.

ATLANTIC AEROSPACE ELECTRONICS CORP.

6404 IVY LANE, SUITE 300 GREENBELT, MD 20770

Phone: (301) 982-5273
Title: High Performance Electrically Scanned Antenna

Topic#: 92-119

ID#: 92HDL-004

ID#: 92EW -048

ID#: 92MIC-102

ID#: 92TEC-054

Office: HDL Contract #:

PI: Victor C. Sanchez

Abstract: The objective of the proposed Phase I effort is to perform a preliminary design of an electronically scanned antenna capable of supporting a multimode radar testbed operating in MTI, ultra-high range resolution and SAR modes. The proposed paseline antenna concept consists of four major components: a two-dimensional antenna array of polarization-diverse radiating elements, a dual purpose elevation feed, an active Rotman lens azimuth feed and an azimuth beam steering network. Use of the active Rotman lens ("Wide Instantaneous Bandwidth Active Scanned Array", proposal dated 5 Feb 92, submitted by Atlantic Aerospace Electronics Corp. to Harry Diamond Laboratory BAA ACT Committee) and a p-i-n diode switch beam steering network ("Low Cost Conformal Electronically Scanned Array", final report dated 20 Sept 91, prepared by Atlantic Aerospace Electronics Corp. for Harry Diamond Laboratory under contract number DAALO2-91-C-0055) has been evaluated for radar antenna applications in the referenced earlier work and will not be considered in further detail in this proposal. The polarization-diverse elements will consist of dual-input elements with an integrated MMIC switch module to select vertical, horizontal, right-hand and left-hand circular polarizations. The elements will reside in a two-dimensional array such that each vertical, or elevation, column has a dual-mode selectable feed and all columns are fed in azimuth by the output ports of the Rotman lens. The selectable elevation feed will be designed to switch between two pattern modes: fixed cosecant-squared and monopulse. The azimuth feed distribution will be such as to achieve peak sidelobe levels of 25db below the main beam. System performance will be quantified by predictions of antenna patterns at different frequencies (5% about 16Ghz), azimuth scan angles (within + or - 45 deg.), elevation beam modes and polarization selections.

AURORA ASSOC.

3350 SCOTT BOULEVARD, BUILDING 30

SANTA CLARA, CA 95054 Phone: (408) 748-0867

Title: Non-Cooperative Combat Identification

Topic#: 92-035

Office: CECOM Contract #:

PI: Dr. I.C. Chang

Abstract: There exists a need for an effective Identification of Friend or Foe (IFF) as part of the target acquisition function in air and ground systems. The most important constraints applied to the real time IFF system include low probability of intercept, fail-safe, safe-guarded, and almost non-cooperative. The concepts of a number of proposed new IFF techniques are described. These techniques are based on the three types of sensors: FLIR, radar, and ladar. Among the three, the approaches which appear the most practical and require simple implementation are ladar-based. Several novel processing devices that are key to the IFF sensors are discussed.

AURORA ASSOC.
3350 SCOTT BOULEVARD, BUILDING 30

SANTA CLARA, CA 95054

Phone: (408) 748-0867

Topic#: 92-057 Office: MICOM

Contract #: PI: Dr. I.C. Chang

Title: Optical Microwave Based Technology for IFF of Unmanned Aerial Vehicles (UAV)

Abstract: The program objective is to develop and demonstrate a low cost, low probability of intercept (LPI) sensor technology for IFF of Unmanned Aerial Vehicles (UAV). Conventional approach using active microwave radars suffer from low angular resolution, high clutter, problem of electronic jamming and emitter observability which can be used by the enemy for homing or identification purpose. A laser radar (Ladar) approach is described. The technology needed for implementing the proposed ladar IFF system include fast beam steering device, widefield narrowband filter and coherent detection techniques. New concepts of optical preprocessing devices are proposed that will significantly enhance the performance of the IFF ladar system.

AUTOMATIX, INC. 755 MIDDLESEX TURNPIKE BILLERICA, MA 01821

Phone: (508) 667-7900

Topic#: 92-092 Office: TECOM

Contract #:

PI: Mr. Michael Wilt

Title: Automated Smoke and Obscurant Cloud Recognition Using Machine Vision

Abstract: The objective of this program is to develop advanced image processing/analysis technology for the automatic determination of smoke and obscurant cloud spatial extent and the extraction of relevant features from video images produced by multiple visible and infrared sensors viewing a cloud from different angles. The 2D information is used to quantity the dimensions, volume, centroid, and location of the cloud. Phase I tasks will mainly include: a review of previous work particularly within DoD and in related applications such as meteorology; an analysis of application requirements; an investigation and limited prototyping of required image processing/analysis approaches. This will include proposing and evaluating image segmentation schemes that can reliably identify image regions corresponding to cloud cover, approaches for region or boundary representation and description, and extraction of geometric/topological features or other 2D measures such as cloud density. The Phase I prototyping will be performed on state-of-the-art image processing/analysis workstations implemented on standard computer platforms. Videotaped images will be used for testing the prototypes and evaluating the applicability and feasibility of the proposed schemes. On the basis of the Phase I results, needs for future R&D will be identified and the Phase II effort will be planned.

AUTOMATIX, INC.
755 MIDDLESEX TURNPIKE
BILLERICA, MA 01821
Phone: (508) 667-7900

Topic#: 92-133
Office: MTL
Contract #:
PI: Mr. Joel Katz

Title: Vision Aided Monitoring and Control System for Ceramic and Powder Metallurgy Manufacturing

Abstract: The objective of this program is to develop non-contact vision sensing and processing schemes that can be used for ceramic and powder metallurgy process monitoring and control. Proposed applications include monitoring of overall shrinkage or differential shrinkage rates during drying of slurries, monitoring dimensional changes, shrinkage and control to final dimensions during sintering, and detecting defects and inhomogeneities before sintering. Phase I tasks will mainly include: a review of previous work particularly in ceramic and powder metallurgy process monitoring and control; an analysis of application requirements including options for interfacing with an intelligent design and processing system; an investigation and limited prototyping of required vision sensing and processing approaches. This will include both prototyping of inspection and precision gauging approaches for dimensional checking and an exploratory analysis of methods for producing optimal images under ceramic processing conditions and techniques for the measurement of local in-plane surface strains. The Phase I prototyping will be performed on state-of-the-art vision systems implemented on standard computer platforms. Limited demonstrations will be performed with simulated sintering operations in room temperature. On the basis of the Phase I results, need for future R&D will be identified and the Phase II effort will be planned.

BELTRAN, INC. 1133 EAST 35 STREET BROOKLYN, NY 11210

BROOKLYN, NY 11210 Contract #:
Phone: (718) 338-3311 PI: Thomas C. Kosvic
Title: "Tripning" of Supercooled Water Drops for Helicopter Descripe

Title: "Tripping" of Supercooled Water Drops for Helicopter Deicing

Abstract: Ice accretions on helicopter rotor blades occur as a result of the impact of supercooled water particles on the surface. Supercooled water particles are in an unstable state. Means are sought to "trip" these particles into ice crystals or amorphous snow so that the particles will not adhere to the surface. Density waves (sound) and electromagnetic waves (including lasers) are to be investigated for suitability as "trip" mechanisms reduce the icing potential. Experiments will be conducted in a microcalorimeter using super cooled water in capillary tubes. The kinetics of freezing will be studied for the various "trip" mechanisms.

BEND RESEARCH, INC. 64550 RESEARCH RD. BEND, OR 97701 Phone: (503) 382-4100

Topic#: 92-067
Office: NATICK
Contract #:
PI: James R. Lowell

Topic#: 92-006

Office: AVSCOM

ID#: 92NAT-028

ID#: 92AVS-009

ID#: 92MTL-179

Title: Activated-Carbon Fibers With High Surface Areas

Abstract: This proposal is directed to the preparation of high-surface-area (HSA) activated-carbon fibers that are suitable for

the Army's lightweight chemical-protective combat uniforms. The overall goal of the proposed program is to develop a domestic source of activated-carbon fibers having surface areas greater than 1500 m2/g. Our approach begins with a novel method of preparing polymeric precursor fibers, which is based on existing technology now being commercialized for other applications by Bend Research. The precursor fibers will then be heat-treated, carbonized, and activated using existing, proven techniques. we believe this process offers a high probability for success. Successful completion of the Phase I program and a subsequent Phase II should lead to domestic production of activated-carbon fibers that are technically superior to those currently available overseas and that are less expensive to produce. During a Phase II program we would collaborate with a textile manufacturer and/or carbon-fiber manufacturer to facilitate the early commercial-scale production of the improved fibers.

BENTHOS, INC. 49 EDGERTON DR. N. FALMOUTH, MA 02556

Phone: (999) 999-9999

Contract #: PI: John Sewell Title: High Power Density Piezoelectric Actuator for Helicopter Gearbox Noise Cancellation

Abstract: A requirement exists to cancel structure-borne noise from helicopter gear boxes by attacking the source of the noise with a high power density single axis actuator. A major requirement is to provide a high force capability in the high power density package and have it be applicable to a bandwidth of 1000 to 4000 Hz. Among the candidates are ceramic, ceramic composite, magnetostrictive and electrological fluid technology. While existing systems can produce high forces, the weight and size of these systems is far too great to be useful. Benthos, a leader in the development and manufacture of piezoelectric driven devices, in corporation with other engineering specialists in high power density actuators, proposes to develop two high force actuators using piezoelectric and magnetostrictive actuators. Each of these will be tailored to optimize their force/weight properties, and will be tested side by side to determine the optimum configuration for the application. The objective of the study is to develop a working prototype of two tested, highly reliable actuator materials in a configuration which will be as close to a working model as feasible in this first phase. From the results of the subsequent analysis, a design will be submitted for a refined version of the actuator to be built and tested in anticipation of the FSD phase of the project.

BERKELEY RESEARCH ASSOC., INC.

P.O.BOX 241

BERKELEY, CA 94701 Phone: (703) 750-3434

Title: Improved Vertical Field Simulation Fidelity for the "Aurora" Gamma Ray Simulator

Topic#: 92-127 Office: HDL

Contract #: PI: Jeffry Golden

Topic#: 92-023

Office: AVSCOM

ID#: 92AVS-154

ID#: 92HDL-081

ID#: 92BRD-013

Abstract: Scale model testing is proposed for the development of a transmission line for applying a vertical electric field that is synchronized to the AURORA radiation pulse to improve the SREMP simulation fidelity in the AURORA test cell. The scale model tests will permit more rapid and affordable design changes than a full scale model so that the effects of time varying air conductivity and coupling to the conducting walls of the test cell can be better studied. Novel construction techniques are also proposed which may lead to lower cost than conventional approaches for the implementation of the transmission line scheme of U.S. patent 4,393,509 by G. Merkel and W.D. Scharf (July 12, 1983). In addition, the exploratory development of a single point initiated, field distortion, oil dielectric switch is proposed as a means to reduce the asynchronism of the four AURORA diode pulses which also affects the simulation fidelity. The Phase I effort includes the preliminary design and cost determination of the full scale system to be constructed in Phase II.

BIO-IMAGING RESEARCH, INC. 425 BARCLAY BLVD. LINCOLNSHIRE, IL 60069

Phone: (708) 634-6425

Title: Underground Mine Detection Using X-Ray Backscatter Imaging

Topic#: 92-025 Office: BRDEC Contract #:

PI: Francois Zayek

Abstract: We propose to design and develop a new x-ray detector system for use in underground mine imaging applications. The detector system will be designed to operate with a pencil-beam scaming x-ray source, and will detect the Compton interacted radiation that is scattered back toward the X-ray source. It will image horizontal views of thin layers of the underground structure. The detector we propose to use is cadmium zinc telluride (CdZnO2Te), which is a solid state detector. It is insensitive

a crystal to achieve fast and broadband spectral tuning. AOTFs are totally solid state devices with no moving parts, compact (1 cm cubed), light weight, and low power for battery operation. Because of that, the diameter of the submersible portion of the spectroradiometer is only about 5 cm. Since the AOTF can do self-calibration, no periodic maintenance is needed. In addition, the AOTF can be programmed to simultaneously pass multiple wavelengths, implement powerful matched filtering algorithms and the light throughput is independent of the resolution, which can greatly increase the sensitivity. As a side benefit, this spectroradiometer can also measure the polarization ratio of the light at different wavelength simultaneously. The fast tuning speed (10 ohms), high resolution (1-2 nm), high sensitivity, small size and inherent ruggedness of AOTFs make them ideal for los level light measurement under thick sea ice cover.

BUSEK CO., INC. 19 KEARNEY RD NEEDHAM, MA 02194 Phone: (617) 449-3929

Title: Synthesis of Fullerenes

Abstract: Busek Co. herein proposes a new fullerene synthesis process which was experimentally demonstrated and involves plasma breakdown of suitable hydrocarbons. The byproduct of the synthesis is hydrogen that can be sold or used on site for fuel cell based electricity production. Thus, two revenue bearing streams, fullerenes and H2 (or electrical power without CO2 emissions) are the product of the proposed process. Approximate cost analysis of the proposed and competing processes were performed and indicated that the plasma based fullerene synthesis could conceivably bring down their production cost to zero because all costs could be covered by the sale of H2 or electricity. In Phase I we propose to begin experimental fullerene yield optimization program (using existing equipment) via parametric variations of three process variables. Alternative fullerene purification process that involves supercritical fluids will also be investigated. The experimental program will be guided by concurrent analysis and the system cost analysis will be refined. Busek Co. will be assisted by SRI International. They currently produce fullerenes and already work with us on our AFOSR and SDI programs to develop a fullerene fueled space propulsion system. In Phase II the system will be scaled up and a prototypical system will be constructed and demonstrated.

CAPE COD RESEARCH, INC. 19 RESEARCH ROAD EAST FALMOUTH, MA 02536

Phone: (508) 540-4400

Title: Environmentally Compliant Coatings for Waterproof Fabrics and Clothing

Abstract: Fabrics for rain gear and outdoor equipment have been traditionally rendered waterproof by coating with solvent-borne rubber solutions, solvent-borne polyurethanes and vinyl plastisols. Regulatory pressure for environmental and worker safety compliance has become a potent driving force in eliminating volatile organic solvents from commercial coating products. A variety of low solvent coating technologies are on the horizon to replace the traditional solvent-based coating methods. The proposed research explores the feasibility of applying current compliant coating methods to the problem of fabric waterproofing. The experimental thrust of the program explores the feasibility of using a combination of water-reducible formulation and UV curing to obtain an effective and environmentally benign waterproofing system for U.S. Army wet weather clothing.

CENTER FOR REMOTE SENSING P. O. BOX 9244 MCLEAN, VA 22102

Phone: (703) 848-0800

Title: Ionospheric Propagation Predictions Using Satellite Beacon

Topic#: 92-031 Office: CECOM Contract #: PI: Suman Ganguly

Topic#: 92-100

PI: V. J. Hruby

Topic#: 92-075

Contract #:

Office: NATICK

PI: Francis L. Keohan

Office: ARO

Contract #:

ID#: 92ARO-015

ID#: 92NAT-139

ID#: 92C3 -028

Abstract: This receiver sets forth a plan to utilize commercial GPS receivers for real time ionospheric prediction at a remote location. The project will demonstrate the feasibility of using TEC measurements and evaluate the accuracy and applicability of these measurements for improvements in HF propagation. For this we assess the predictability of the slab thickness parameter T towards solar and geophysical parameters. Numerical models of thermosphere-ionosphere and the protonosphere will be used

to obtain a self consistent physical description of the electron density distribution, slab thickness and their constituent parameters. Results of these simulations will not only allow a coherent assessment of the predictability of T and its constituent parameters

but also will allow "parameterization" of the complex situation. These parameters will then be used to drive a simple self consistent 2-D ionospheric model for real time update.

CERACON, INC. 1101 N. MARKET BLVD. #9 SACRAMENTO, CA 95834

Phone: (916) 928-1933

PI: Ramas V. Raman

Title: Advanced Refractory Metal Coatings Via an Innovative Powder Metallurgy Approach

Abstract: Armament Research Development and Engineering Contaging interested in powel approach

Abstract: Armament Research Development and Engineering Center is interested in novel approaches to increase wear and erosion life of gun barrels. Prior work under the Advanced Materials for Gun Systems (AMGS) Program has identified that refractory metal alloys (tantalum-based) possess a balance of properties suited for this type of severe application. However, a processing methodology capable of bonding refractory alloys to a steel surface while retaining bond strength and microstructural control is desirable but not available. A Phase I program is proposes in which thermostructural modeling will be used to identify promising refractory alloys in collaboration with GE Armament Systems. Ceracon will apply an innovative cold isostatic processing approach to obtain a thin coating of refractory metal on the inner surface of steel. These materials will be fully densified and bonded using Ceracon's high pressure rapid consolidation process. Characterization and properties as well as wear erosion data, will be measured to enable down-selection of one coating material system for Phase II evaluation.

CERCOM, INC. 1960 WATSON WAY VISTA, CA 92083 Phone: (619) 727-6200

Topic#: 92-021
Office: AVSCOM
Contract #:
PI: Andre Ezis

Topic#: 92-012

Office: AVSCOM

Topic#: 92-003

Office: ARDEC

Contract #:

ID#: 92ARD-027

ID#: 92AVS-115

ID#: 92AVS-064

Title: Selectively Reinforced Ceramic Matrix Composites for Bearing Races

Abstract: All-ceramic bearings offer high temperature capability, longer fatigue lifetimes, and lower weight compared to conventional steel bearings. However, the low fracture toughness of the ceramic material (typically silicon nitride) restricts the allowable hoop stress, and therefore severely limits their use for potential applications. Reinforcement of the ceramic matrix is a viable means to increase fracture toughness, although reinforcement of the bearing surface may induce fatigue crack initiation, result in differential wear rates and reduce attainment of fine surface finish. Consequently, a ceramic matrix composite (CMC) design with a monolithic bearing surface case and a higher toughness core region fabricated into a bearing race geometry is desirable. In this Phase I effort, techniques to fabricate silicon nitride with selective reinforcement (graded CMC) are conceptualized, demonstrated and evaluated by fabricating materials in selected geometries and thereafter characterized with respect to physical and mechanical properties. Fabrication techniques to be considered for producing selectively graded reinforced ceramic bearing races include: 1) centrifugal spinning of matrix based slurries containing particulate reinforcement(s), 2) selected high pressure molten metal infiltration to produce graded-tough cermets and 3) incorporation of refractory fibers for selected reinforcement.

CFD RESEARCH CORP. 3325-D TRIANA BLVD. HUNTSVILLE, AL 35805 Phone: (205) 536-6576

805 Contract #:
PI: Matthew E. Thomas

Title: Novel Inlet Protection System for Auxiliary Power Units Abstract: The proposed Inlet Protection System (IPS) concept inc

Abstract: The proposed Inlet Protection System (IPS) concept includes advanced T800 features and potential implementation of Electrostatic Particle Separation (EPS) technology. It is retrofitable into existing installations as well as integratable into future APU/SPU engines. CFDRC proposes an experimental/analytical team for CFDRC, Garrett Auxiliary Power Division (GAPD), and the University of Cincinnati (UC). The Phase I program includes: 1. application if GAPD IPS design procedures to assist in focusing CFDRC's proposed base line concept test program at UC; 2. IPS analytical wall contour optimization with and without implementation of EPS technology using advanced CFD analysis; 3. preliminary assessment and specification of scavenge requirements; and 4. documentation of CFD technology utilized to refine the IPS concept proposed here. Application of CFD technology during Phase I is expected to assist in early minimization of first stage compressor rotor excitation sources due to IPS inlet flow distortion. Phase II will consist of IPS prototype detailed design, fabrication, and sand removal efficiency

testing. GAPD will assist CFDRC in assessment and implementation of all U.S. Army airworthiness requirements.

CFD RESEARCH CORP. 3325-D TRIANA BLVD. HUNTSVILLE, AL 35805

Phone: (205) 536-6576 Title: Tacital Missile Air Turbo Rocket Propulsion System Topic#: 92-051 Office: MICOM Contract #:

ID#: 92MIC-076

Pl: Matthew E. Thomas

Abstract: An innovative approach is proposed for the development of a low cost Air Turbo Rocket (ATR) propulsion system by using Off-the-Shelf (OTS) component technology. The proposed ATR propulsion system will be capable of delivering up to 500 lbf boost thrust and 265 lbf of fully throttlable sustained thrust with a 10-1 turndown ratio. All propulsion module integration requirements will be focused toward a 5.85 inch diameter tactical missile airframe that can operate at a sea level sustained flight Mach Number of 1.5. Major activities during Phase I include: 1) optimization of critical ATR cycle parameters; 2) detailed vehicle mission analysis; 3) delivery and test support of OTS turbomachinery components; 4) analysis and conceptual design of ATR combustor technology; and 5) generation of an ATR module detailed design layout. During Phase II a flight weight ATR propulsion module will be developed by CFDRC and assembled in the MICOM propulsion laboratory. Phase III could consist of actual integration of ATR propulsion technology into a prototype test missile.

CHAMBELL ENGINEERING, INC. 3415 STANWOOD BOULEVARD HUNTSVILLE, AL 35811

Phone: (205) 852-8720

Topic#: 92-053 Office: MICOM ID#: 92MIC-061

ID#: 92MED-073

ID#: 92TAC-037

Contract #: PI: Don W. Jones

Title: Solid Rocket Booster Starter System for Tactical Missile Turbojet Engines

Abstract: The turbojet engine starter system utilizes the pressure of the solid propellant boost motor to pressurize a fluid contained in a bladder tank. The increase in fluid pressure ruptures a diaphragm containment seal allowing the fluid to flow through a boost motor/heat exchanger where the high pressure fluid is heated to high temperature. The heated fluid is used to spin-up rotors and to ignite the burner of the turbojet engine. The thermal energy input to the heat exchanger is from the products of combustion of the solid booster motor.

CHARLES RIVER ANALYTICS, INC. 55 WHEELER STREET CAMBRIDGE, MA 02138

Phone: (617) 491-3474

Title: Active Noise Cancellation Stethoscope

Topic#: 92-160

Office: MEDICAL

Contract #:

PI: Dr. Greg L. Zacharias

Abstract: The Phase I study will conduct a proof-of-concept demonstration of an active noise cancellation (ANC) stethoscope for auscultation of patient breath sounds during aeromedical evacuation. We believe that the most effective solution can be built around the use of ANC technology. By using a separate measurement of the acoustic noise environment surrounding the medic and patient, an ANC device can track the complex and time varying changes in the noise, and compensate for them in real-time. This provides the medic with a significantly enhanced signal-to-noise (S/N0 ratio, which, in turn, improves his ability to hear critical sounds and make the correct physical assessment of the patient. An initial demonstration will evaluate the performance of commercially-available ANC hardware, to identify basic performance levels and to identify critical design requirements to be met by the prototype system. A design effort will then focus on the development and evaluation of a state-of-the-art ANC stethoscope, with the ANC compensation specifically designed for in-rotorcraft auscultation. Engineering evaluation and psychoacoustic testing will be used to evaluate the Phase I prototype and define the development, validation, and documentation requirements of the Phase II effort.

CMTG RESEARCH, INC. 14 CASE ST.

NORTH CANTON, CT 06059

Phone: (203) 693-0639

Topic#: 92-080 Office: TACOM Contract #:

PI: Gary M. Colello

Title: Non-Hydraulic Suspension Actuators

Abstract: EASE (Electrically Adaptive Suspension Element) is comprised of three major sub-systems, these being the electromagnetic Coaxial linear (EMCL) actuator, the Adaptive Feedback Network, and the Thermal Management System. The EMCL actuator is designed for use as the active suspension element of a combat vehicle. The EMCL actuator is particularly suited to this adaptive architecture because the actuator is completely linear over its long travel, and has excellent frequency response, force and travel characteristics. The EMCL actuator is a hybrid brush-fed synchronous DC linear motor consisting of a helical conductor making up the bore of the cylinder and the mechanical support of the cylinder provided by an iron/fiberglass composite shell. The actuator will mount to a support frame in a manner similar to a conventional hydraulic actuator or snubber. The piston of the actuator consists of permanent magnet/back iron modules that provide thrust for actuation. The movement of the EMCL piston causes the actuator to distend or compress depending upon vehicle requirements. A set of bore guides is used to stabilize the piston in the bore while the bore guides also serve as an electrical conduit providing power to the piston and bore conductor. The basic design of the EMCL actuator is very similar to the electromagnetic actuator used for a torpedo countermeasures launcher that was designed, fabricated and successfully tested under a DARPA funded launcher effort. The proposed SBIR Phase I work includes design, fabrication and testing for a complete EASE system which includes a computer controlled adaptive feedback network, electromagnetic coaxial linear actuator, power supply and power conditioning.

COLEMAN ENGINE CORP. 108 LA VILLA DRIVE LYNDEN, WA 98264 Phone: (206) 354-7513

Title: Single Rotor Turbine Expander

Topic#: 92-014

ID#: 92AVS-082

Office: AVSCOM Contract #:

PI: Richard R. Coleman

Abstract: Two torms of turbine expander are proposed. One, the single-rotor, partial admission, multistage, reentry type reaction turbine, is suitable for use at any realizable pressure ratio and should be especially effective in low mass flow engines because rotor blade Reynolds number can be maximized for a given flow area. The other, a modified form of the radial flow turbine, is adaptable to and abets structural compactness in both conventional gas turbine engines and systems based upon high pressure ratio wave engines. Both expanders inherently increase the maximum allowable material-limited gas inlet temperature because of the temperature averaging effect of the gas streams. The unsteady gas dynamics involved in the reentry type reaction turbine requires the modification and upgrading of existing computer simulation programs in order to address some of the unique characteristics of this machine and provide data for the design of a laboratory test rig. However, current capabilities in numerical techniques and modern computers permit effective solution of these problems. The performance and basic structural analysis of the radial flow turbine variant can be carried out with existing programs. These two expanders can drastically broaden the range of gas turbine propulsion applications.

CCLONIAL CIRCUITS, INC. 1026 WARRENTON RD FALMOUTH, VA 22406

Phone: (703) 752-5511

Topic#: 92-124 Office: HDL ID#: 92HDL-060

Contract #:
PI: Bruce McCormick

Title: SERA Tester Application for Process Control

Abstract: This effort would develop the laboratory set-up of the solderability tester into a real time statistical process control tool in the manufacture of printed wiring boards. By correlation of SERA test data to copper contamination levels in the solder plating bath; and the application of statistical process control techniques, real time feedback to the plating process would be established.

COMPUTING SERVICES SUPPORT SOLUTIONS 6709 LA TIJERA BLVD., #451

LOS ANGELES, CA 90045

Phone: (213) 298-5309

Title: Noise Reduction Techniques

PI: Dr. Ananthram Swami

Contract #:

Abstract: Signal Processing based on higher-order cumulants is a powerful tool to detect and estimate non-Gaussian signals in the presence of colored Gaussian noise of unknown power spectral density. Since signals used in communication systems are

symmetrically distributed, the third-order cumulants (or bispectra) are theoretically zero, and hence, we are forced to use fourth-order cumulants (or trispectra). The blind equalization problem, in the presence of colored Gaussian noise, will be studied in this proposal. Existing algorithms, as well as proposed theoretical and practical extensions will be investigated. Both transversal as well as lattice structures, and algorithms based on conventional cumulants, as well as the trispectrum will be investigated. A candidate architecture amenable to implementation on existing signal processing hardware will be developed. Promising algorithms will be selected based on their theoretical performance analysis, the computational complexity, and their suitability to hardware implementation. Algorithms will be validated via simulations, and possibly against data to be obtained from the DoD.

CONTAMINATION STUDIES LABORATORY

201 EASR DEFENBAUGH ST.

KOKOMO, IN 46902

Phone: (317) 452-6651

Title: Solder-Plating Process Control

Topic#: 92-124

Office: HDL Contract #:

PI: Terry L. Munson

ID#: 92HDL-058

ID#: 92AVS-024

ID#: 92AVS-089

Abstract: At CSL, Inc. the Sequential Electrolytic Reduction Analysis equipment will be optimized for both board and component manufacturing processes. Six manufacturers will be supplying product during this project. Our approach to optimization will be through applying SERA technologies to all board and component processes that directly relate to the solderability issues. CSL, Inc. will use a four phase approach with the objectives being correlation, redesign, multiple board analysis, and evaluation of component plating processes. By optimizing the technology through these four phases, we will be able to maximize the system areas of application as a process control tool. Using industry partners and an analytical laboratory approach, we can then maximize the exposure to the industry through a multidimensional test matrix. Understanding the type and level of oxides present throughout the metalization processes will lead to improved product quality. To give today's manufacturers cost affective process control tools that will improve product reliability can only save our industry uncountable millions od dollars and allow these manufacturers to better compete in the world market. CSL, Inc.'s use of both military approved and automotive electronic manufacturers will allow a more expedient commercialization of this technology.

CONTINUUM DYNAMICS, INC.

P.O. BOX 3073

PRINCETON, NJ 08543

Phone: (609) 734-9282

Topic#: 92-008 Office: AVSCOM

Contract #:

PI: Dr. Todd R. Quackenbush

Title: Design and Control Strategies using Smart Structures Technology for Rotorcraft Maneuverability Enhancement

Abstract: Military rotorcraft will need a high degree of maneuvering capability to survive in the future battlefield operations. Conventional design methods and blade control technology offer only limited means for improving current maneuver performance levels. As a consequence, alternate technologies involving active control and "smart" materials are attractive since they offer the possibility of enhancing load factor, turning rate, and climb rate without penalties in vehicle utility. This proposal outlines an effort to evaluate the feasibility of new design and control strategies for rotor blades to improve maneuvering performance. These strategies will be based on the use of active control of twist and camber based on the application of Shape Memory Alloy (SMA) technology. This effort will combine advanced performance prediction and design optimization methods with recent work in rotor state estimation and control techniques to evaluate the improvements in rotor maneuverability available using actuators based on SMA technology.

CORDEC CORP.

8270-B CINDER BED ROAD, P.O. BOX 188

LORTON, VA 22079

Phone: (703) 550-8044

Topic#: 92-017

Office: AVSCOM

Contract #:

PI: Dr. R. J. Weimer

Title: Fabrication of High Temperature Metal Matrix Composite Tubes by Vapor Deposition Methods

Abstract: Advanced turbine engines and flight vehicles will depend upon new, high-temperature metal matrix composites (MMC's) to meet performance goals. Engineering characterization of such materials is difficult and costly, which accounts for the meager property database available to designers. Thin-walled tubes would be especially useful for developing constitutive relations and failure criteria under multiaxial (T-C/Torsion) combined loads (thermal and mechanical, static and dynamic). This

project will develop a process for manufacturing and consolidating MMC precursor wire into high quality tubular specimens by hot isostatic pressing. The MMC wire will be fabricated by a physical vapor deposition process which applies diffusion barriers (if needed) and matrix metal onto a continuous ceramic monofilament. The wire is a microcomposite of the final structure, carrying precisely the amount of matrix needed to achieve the desired final volume fractions. Phase I will establish the feasibility of this approach to making high temperature MMC thin-walled tubes. Phase II would demonstrate reproducible pilot scale production of high-quality tubes and, in the process, establish protocols for fabricating more complex engineering structures from these new materials.

Abstract: The U.S. Army requires safe, high rate, high energy density rechargeable bipolar Li batteries to power a wide range of manportable electronic equipment. Although remarkable strides in solid polymer electrolyte (SPE) technology for

Abstract: A program to investigate symbology and symbology-stabilization concepts for helmet-mounted displays (HMD) has been proposed. The present implementation of HMD symbology as defined in MIL-STD-1295 has been found to cause increased pilot workload and may present hazardously misleading cues in some instances. The Phase I program will identify unresolved

COVALENT ASSOC., INC.

10 STATE STREET WOBURN, MA 01801

Phone: (617) 938-1140

Title: High Rate, Solid Inorganic Polymer Electrolyte-Based Bipolar Lithium Batteries

rechargeable Li batteries have been made, serious problems with safety, rate, and energy density still remain. In this proposal foil/SIPE/LiCo02 will be built and cycled paying particular attention to rate capability, self-discharge at 60C, and cycle life.

CREW SYSTEMS CONSULTANTS

P.O. BOX 963

SAN MARCOS, TX 78667

Phone: (512) 754-7896

Title: Helmet-Mounted Display Flight Symbology and Stabilization Concepts

CYBERNET SYSTEMS CORP.

SUITE B-101, 1919 GREEN RD. ANN ARBOR, MI 48105 Phone: (313) 668-2567

Title: Personal Navigation and Reporting

Abstract: Due to the increasing use of technology to plan and implement modern day combat, it is imperative that troop and vehicles deployment and position be known as precisely as possible. Furthermore, the unit commander must be able to quickly

be done based on Phase I Results. DAINA 4960 FILLMORE STREET, N.E.

COLUMBIA HEIGHTS, MN 55421

Topic#: 92-115 ID#: 92ETD-031

Office: ETDL Contract #:

PI: Dr. Larry A. Dominey

we address three specific areas of SPE technology requiring advances by way of new materials: a chemically and electrochemically stable solid inorganic polymer electrolyte (SIPE); high rate, easily prepared thin film sol-gel LiCo02 cathodes: Li reactivity inhibits which prevent uncontrolled thermal excursions. During Phase I bipolar laboratory cells comprising Li

ID#: 92AVS-083

ID#: 92TOP-009

Topic#: 92-015 Office: AVSCOM

Contract #:

PI: Richard L. Newman

issues and propose candidate solutions for correcting these problems. The Phase II effort will conduct ground simulation and inflight evaluations of these candidate solutions. A strawman HMD design standard will be developed.

> Topic#: 92-147 Office: TOP Contract #: PI: Cyril S. White

Topic#: 92-032 ID#: 92AV -021

Office: CECOM Contract #:

plan, transmit, and display friendly and adversarial troop and vehicle locations to coordinate battlefield operations effectively in the heat of battle. In this effort we propose to develop a Personal Reporting and Navigation System (PNRS) subsystem using Non-Developmental Item navigation aids (GPS, INS, Magneto Compass, etc.), and UHF radio with data interfaces. This system will also provide a unique solution to the problem of ground based friend or foe identification. In Phase I we will demonstrate a conceptual implementation of the system using commercial components. In Phase II complete architecture integration will

Phone: (612) 781-7600 PI: Dr. Paul R. Pukite

Title: Advanced Design Tools for Evaluating Fault-Tolerant Systems

Abstract: As mission critical avionics systems increase in complexity, the evaluation of their performance and reliability will become more difficult. We propose to select and to integrate a group of reliability and performance analysis tools, specifically designed to handle the fault-tolerant operational aspects of the next generation avionics architectures. These tools will support both hardware and software evaluation and will be developed in the Ada programming language. The reliability analysis will use a customized CARMS program (computer-aided rate modelling and simulation), with an interactive graphical and spreadsheet interface. The performance analysis tools will use Petri net analysis and Monte Carlo simulation methods. An embedded Ada expert system will help to guide the proper method selection and to control the evaluation and sensitivity analyses. Personal computers will be used for the initial prototyping and simulation. We expect that the availability of these tools will permit earlier evaluation of the effectiveness of the selected architecture, and thus avoid the need for later changes in the design. Our earlier experience with the PAVE PILLAR avionics architecture, embedded expert system design, and fault-tolerant system analysis and simulation methods will provide a sound foundation for this project.

DANIEL H. WAGNER ASSOC., INC. STATION SQUARE TWO PAOLI, PA 19301

Phone: (215) 644-3400 PI: Dr. Barry Belkin Title: Real-Time Determination for Kwajalein Missile Range (KMR) Tracking Development

Abstract: Current KMR experience is that the complexity and uniqueness of some reentry objects cause atmospheric drag profiles to deviate significantly from model predictions. The possible result is loss of track. As a consequence, there is a need to develop a tracking filter which allows for the accurate real time estimation of drag. The objective of the proposed Phase I effort is to investigate the performance of an empirical method for real time drag estimation based on the use of a modified Euler method to predict object location combined with the use of the Rauch-Tung-Streibel smoother to estimate total body acceleration a. The deceleration due to drag ad can then be estimated from a and the known gravitational acceleration ag. The primary Phase I task proposed include: (1) the design of the tracking algorithm, (2) the adaptation of existing test bed software to support the testing of the tracking algorithm, (3) preliminary algorithm testing, and (4) documentation of the algorithm design and test results.

DASGROUP 3807 ELMHURST ROAD TOLEDO, OH 43613 Phone: (419) 537-2116

Title: Quantum Chemistry Visualization using AVS

Topic#: 92-050 ID#: 92CRD-034 Office: CRDEC

ID#: 92SDC-077

ID#: 92MTL-136

Contract #: PI: Douglas A. Smith

Topic#: 92-176

Office: SDC

Contract #:

Abstract: Molecular modeling is widespread in a variety of federal, industrial and academic laboratories. Graphical interfaces have become the rule, yet quantum chemistry visualization lags far behind other modeling even though quantum calculations account for almost half of the cpu cycles used. In order to address this need, DASGroup will develop a hardware independent graphical user interface based on Application Visualization System (AVS) for the analysis of quantum mechanical calculations of molecular properties. This GUI will be capable of property calculations, visualization, real time manipulation, and animation of results produced by the Gaussian and MOPAC series of programs. DASGroup will compile a computer searchable calculable properties data base for Gaussian and MOPAC, prepare a feasibility study and timetable for converting MOPAC completely into AVS for real time control and visualization of semiempirical calculations, and will demonstrate the visualization and animation of between 1 and 5 calculated molecular properties. DASGroup's ultimate goal is to design and implement MOPAC-AVS, an interactive real time visualization version of MOPAC, and a fully functional molecular modeling graphical user interface for Gaussian, MOPAC, and other quantum codes.

DASGROUP 3807 ELMHURST ROAD TOLEDO, OH 43613 Phone: (419) 537-4028 Topic#: 92-130 Office: MTL

Contract #:

PI: Charles W. Ulmer, II

21

Title: Rational Design of Novel Transparent Ballistic Polymers

Abstract: Molecular modeling for drug design is a reasonably mature science, but the techniques have not yet been applied to most other areas of polymer design. In order to develop transparent polymers with greater protection against ballistic impact, we will develop a modeling protocol for bisphenol-A-polycarbonate (PC), polymethylmethacrylate (PMMA) and Astrel 360 ploysulfone (PES) utilizing semiempirical molecular orbital and molecular mechanics calculations of model systems and molecular dynamics of amorphous polymers. Modeling results of different polymers and of the same polymers under different conditions will be compared with each other and with experimental data to determine what structural elements of PC give it it's unique ballistic properties. Structure property relationship analysis using the newly available software package QSPR-Polymer will allow pre-modeling screening of hundreds of derivatives based on PC. PMMA and PES. Promising QSPR candidates will be cycled through the modeling protocol in order to enhance our understanding and hypotheses, which will ultimately lead to the proposal of new transparent polymers with significantly improved ballistic performance.

ID#: 92ARD-051

DCS CORP. Topic#: 92-004
1330 BRADDOCK PLACE Office: ARDEC

ALEXANDRIA, VA 22314 Contract #:
Phone: (703) 683-8430 PI: James Lincoln

Title: Low Intensity Conflict Aerosol Munitions

Abstract: Aerosol sprays of paint, epoxy, and other substances can be dispensed by mines and other munitions to disable hostile sensors, vehicles, and weapon systems. For example, a paint-filled aerosol mine could be designed to detect an approaching vehicle, pop into the air, and eject and aerosol mist of opaque, brightly colored, solvent resistive, electrically conductive paint at the vehicle. The resulting coating would disable periscopes, vision blocks, windshields, headlamps, lasers, and night vision devices as well as destroy vehicle camouflage. The electrically conductive nature of the paint would serve to ground out communications antennae and disrupt or incapacitate radar/dishes. Tanks and armored vehicles with paint-coated optical surfaces would be hazardous to occupy and their weapon systems would be difficult to employ. Aerosol munitions could be tailored to fit existing mines, mortar rounds, artillery shells, UAV's or missile warheads, thus making them an inexpensive addition to existing inventories. DCS proposes to list and categorize all such aerosol munitions, determine Army requirements, formulate concepts for specific aerosol munitions, and devise optimized functional specifications for at least two types of non-lethal aerosol munitions.

DECISION-SCIENCE APPLICATIONS, INC.

Topic#: 92-139

[L#: 92VAL-004

1110 NORTH GLEBE RD., SUITE 400 Office: VAL ARLINGTON, VA 22201 Contract #:

Phone: (703) 243-2500 PI: Philip G. Tomlinson

Title: Bistatic Chaff and Weather Modeling

Abstract: It is proposed to develop a mathematical model for the bistatic signature of chaff, as well as weather (rain and fog). The model will include the full scattering matrix and temporal and spatial amplitude and phase fluctuation statistics. The model will be parametric in such factors as the electrical length of the chaff dipoles, wind turbulence, and radar resolution volumes. DSA proposes to build upon work in resonance region scattering approximations for dipoles, numerical electromagnetic techniques, atmospheric modeling, and DSA software tools for synthesizing probability density functions.

DEFENSE RESEARCH TECHNOLOGIES, INC. Topic#: 92-128 ID#: 92HDL-084

354 HUNGERFORD DR Office: HDL ROCKVILLE, MD 20850 Contract #:

Phone: (301) 762-3077 PI: Tadeusz M. Drzewiecki

Title: No-Moving-Parts Electrolytic Oxygen Pump for Low Noise Fluidic Applications

Abstract: DRT proposes to develop a novel no-moving-parts pump that delivers flow of oxygen-enriched air, on the order of liters per minute at any desired pressure, without any pulsations or flow noise. A pump operating off a vehicular battery could weigh less than 8 lb. with a size of less than 1 cubic foot. It is based on a demonstrated chemical and biological agent purifying oxygen pumping system, where, in the electrolytic process, a partial pressure of oxygen is developed due to ion flow across a solid electrolyte (yttrium-doped zirconia) in the presence of an electric potential. This pump promises to be the low noise power

supply to use with ultrahigh dynamic range, high sensitivity acousto-fluidic devices and other (e.g., inertial) sensors. It will deliver quiet flow on par with, or better than that of bottled compressed air. Cost could be very low due to its simplicity. DRT will test existing oxygen pump hardware and establish overall performance characteristics and will then develop a preliminary design for implementation in a Phase II effort. Also, DRT proposes to identify and assess other fluid power sources in order to provide the Government with a basis for establishing tradeoffs for manportable verses vehicular verses other applications. A survey of power supplies to include other electrolytic processes, chemical and thermal, would be conducted. Characteristics considered will include pneumatic power required by typical fluidic systems, allowable noise levels, system robustness, source input power requirements (efficiency) and cost.

DELFIN SYSTEMS 1349 MOFFETT PARK DRIVE SUNNYVALE, CA 94089 Phone: (408) 734-2400

Title: Advanced Supervisory Systems

Abstract: Combat vehicle functions and capabilities are becoming increasingly complex. The introduction of computer control architectures in vehicles and vehicle subsystems provide an abundance of information to operating crew members. This increased information load coupled with reduced crew sizes allocated to operate these vehicles creates a major problem. Therefore, the need arises for an intelligent, computer based supervisory system to monitor vehicle operation and advise crew member(s) of key events as they occur. This supervisory system would employ advanced knowledge-based reasoning technologies embedded into the vehicle's status monitoring and control operations to significantly reduce operator workload.

DIRECTED TECHNOLOGIES, INC. 4001 N. FAIRFAX DR. SUITE 775 ARLINGTON, VA 22203

Phone: (703) 243-3383

Title: High Pressure Hydrogen Supply for Increased Fuel Cell Efficiency

Abstract: Fuel cells are being considered by the Army for future individual soldier power supplies. These power units are to be lightweight, compact and suitable for use on the battlefield. A compact, lightweight, safe source of pure hydrogen (and possibly oxygen) is urgently needed. The proposed report will examine a series of high pressure hydrogen and liquid hydrogen storage systems suitable for an individual soldier's power supply. Incorporation of high pressure H2 storage into the power system is felt to simultaneously simplify the system while reducing the size/weight of the fuel cell and boosting system efficiency. An air compression system operated by the expansion of high pressure gases will be conceptually designed to allow "supercharging" of the fuel cell stack. Fuel cell power systems which carry an oxidant supply in addition to a hydrogen supply will also be examined as a possible means of boosting fuel cell efficiency and reducing combined fuel cell/storage system weight and cost.

DOVE ELECTRONICS, INC. 227 LIBERTY PLAZA ROME, NY 13440

Phone: (315) 336-0230

Title: Remote Site Wind Measurement Capability

Office: TECOM Contract #: PI: John F. Dove

Abstract: Dove Electronics, Inc. has designed and fabricated the most advanced active scintillometer for measuring wind speed. wind direction and atmospheric turbulence for the U.S. Army and the National Oceanic and Atmospheric Administration. This device is called HOLODAR and achieves its superior performance through the use of multiplex holographic optical spatial filters. We are now proposing a smart passive scintillometer to meet the TECOM need for a high performance passive scintillometer for measuring wind parameters. This device will achieve high performance through the use of fractal theory, wavelet theory, neural networks, extensive scene and image design and test databases. This effort will also use an enhanced version of the theory of passive wind sensing found in the "Theoretical Analysis and Experimental Evaluation of a Prototype Passive Sensor to Measure Crosswinds", by Clifford, Ochs and Wang dated September 1974. The key to a successful design and fabrication of an outstanding passive scintillometer is the formulation of an effective way to process and exploit the varying uncertainties

Topic#: 92-084 ID#: 92TAC-078 Office: TACOM

ID#: 92ARO-041

ID#: 92TEC-035

Contract #: PI: Ted Batha

Topic#: 92-102

Topic#: 92-091

PI: George N. Baum

Office: ARO

Contract #:

and complexities in the naturally illuminated scenes. The large database of images and naturally illuminated scenes will form the starting point of the required analysis. It is anticipated that a smart sensor will provide best performance in a wide variation of scene dynamics.

DR. WEIGHT AND ASSOC.

7005 E. SPRING ST.

LONG BEACH, CA 90808

Phone: (310) 429-9786

Title: Fuzzification of ASAT's rule based aim-point selection

Topic#: 92-172

ID#: 92SDC-032

Office: SDC

Contract #: DASG60-93-C-0005

PI: Thomas H. Weight

Abstract: The current baseline ASAT aim-point algorithm is based on a hard logic rule-based approach. The main limitation of this approach results from the combination of uncertainties in the ASAT mission. These uncertainties can not be eliminated or even significantly reduced without a tremendous expenditure of resources. ASAT needs an algorithmic approach which is designed to operate in the presence of uncertainty. During the past few years, fuzzy logic has belatedly become important design paradigm in the united States. There are a few tools available for developing fuzzy logic applications. These tools are for the most particular hardware development system. They are also not designed ho support the ASAT application or be integrated with the current ASAT resources. We are proposing to develop a fuzzy logic tool which is primarily designed to support the ASAT project. In addition, this tool will be designed to support a wide variety of image-based fuzzy logic design efforts. It will eventually also offer the relatively new capability of generating rules automatically through the application of neural networks.

DYNA EAST CORP.

3201 ARCH ST. PHILADELPHIA, PA 19104

Phone: (215) 386-4884

Topic#: 92-001

ID#: 92ARD-052

ID#: 92EW -036

Office: ARDEC Contract #:

PI: William J Flis

Title: An Improved Munitions Container for Reduced Hazard Classification

Abstract: We propose to develop an improved multi-purpose munitions container with reduced hazard classification and ability to pass the fast cook-off test. The currently fielded container, when loaded with munitions and exposed to a large fuel fire, acts as a pressure vessel to contain the product gases evolved form the burning munitions inside, until it catastrophically ruptures, with a release of fragments and possible projection of munitions. Using special materials and design features, these containers will be modified to first thermally insulate the contained munitions from the fast cook-off environment; to vent the internal pressure of evolved gases or to fail in a controlled, non-fragmenting manner; and finally, to protect the contained munitions from fragments projected by nearby detonating munitions.

DYNETICS, INC. P.O. DRAWER B HUNTSVILLE, AL 35814

Phone: (205) 922-9230

Topic#: 92-033

Office: CECOM Contract #:

PI: Dr. Chris Anderson

Title: Nonlinear Techniques for Impulse Radar Electronic Support Measures (ESM)

Abstract: Impulse response radars present a major detection problem for current and developmental Electronic Support Measure (ESM) receivers. These signals are characterized by short pulse durations and wide bandwidths, for which current and developmental ESM receivers are not optimized. Detection and characterization of received radar impulses would enable classification of the emitting radar source, including measurement of pulsewidth and pulse repetition frequency. Dynetics proposes a novel nonlinear signal processing approach to solve the impulse and ultra-wide-band radar detection problem. Specific advantages of nonlinear approaches are: 1. Narrowband signals from a dense signal environment are removed prior to pulse detection, 2. Input signal-to-noise ration (SNR) is not degraded, and 3. Pulse detection is performed in the time domain (SNR optimized). To analyze linear and nonlinear detection algorithms, Dynetics has developed an ESM computer simulation. Simulation results are provided to illustrate the benefits of this type of impulse detection. Specific issues to be resolved during Phase I include assessing intercept receiver requirements, specification of nonlinear processing techniques for the detection, characterization, and direction finding of impulse radars, and selection of an optimal approach. In addition, a preliminary design and analysis of the optimal ESM receiver will be performed.

Topic#: 92-062

Topic#: 92-079

Topic#: 92-141

Contract #:

Office: TACOM

ID#: 92MIC-060

ID#: 92TAC-017

ID#: 92CER-046

DYNETICS, INC. P.O. DRAWER B HUNTSVILLE, AL 35814

Office: MICOM Contract #: Phone: (205) 922-9230 PI: B. V. Dasarathy

Title: Advanced Signal Processing Techniques for BAT-Class MMW Seekers

Abstract: Among the most demanding problems for millimeter wave (MMW) radar guided missiles such as that being developed for the Brilliant Antitank (BAT) program is the detection and classification of stationary ground targets in clutter rich environments for autonomous acquisition and terminal homing. This mission must be met with a high probability of successful classification and a minimal false target density (FTD) to best utilize interceptor resources. The threat for these missions consists of the modern tank formation, assembly areas, choke points, and high-value targets. In addition, it is desirable to commit resources against tanks rather than lower-priority vehicles such as trucks. More sophisticated signal processing techniques are required to detect and classify stationary targets with high probability in a clutter-rich environment (including snow) and to perform aimpoint selection and biasing. Nontraditional techniques include the use of wavelet transformations, fractal-based feature extraction, and neural network processing. Specifically, a MMW seeker will be designed and simulated that will include a wavelet transform processor, a detection and segmentation subsystem, a feature extractor that incorporates a fractal dimensionality feature, and a neural network classifier. Collected data (such as collected under the MLRS/TGW program) will be used to test the system.

EAI CORP. 1308 CONTINENTAL DRIVE, SUITE J ABINGDON, MD 21009 Phone: (410) 676-1449

PI: Mr. Matthew Hutton

Title: Computer Simulation Modeling of NBC Sensor Capabilities on Ground Vehicles

Abstract: The technology growth and widespread expansion in the number of nations, particularly among third world countries, possessing or acquiring nuclear, biological, and chemical (NBC) weapons have dramatically altered the NBC threat of U.S. military forces. This worldwide proliferation of an NBC offensive capability indicates that U.S. forces must have an integrated NBC defense which includes NBC sensors on ground vehicles in order to operate and survive on the future multi-threat battlefield. Critical to developing and implementing a strong operationally supportive NBC defense posture is the requirement to integrate NBC effects into wargames and simulations. This project will perform a worldwide market survey and technology review to evaluate existing military, commercial, and developmental NBC sensors for use on U.S. Army ground vehicles. Laboratories, military equipment compendiums, subject matter experts, information analysis centers and other on-line data bases will be utilized. The feasibility of imbedding and/or interfacing NBC models into existing force-on-force models will be assessed. These results will provide the framework for developing a simulation that accurately models NBC insults and their effects against both system/crew and a force within existing COEA force-on-force models.

EASTPORT INTERNATIONAL, INC. 501 PRINCE GEORGE'S BLVD. UPPER MARLBORO, MD 20772

Phone: (301) 249-3300

Title: Removal of Lead Paint from Buildings Prior to Demolition

Office: CERL Contract #: PI: Scott Swetz

Abstract: Eastport International, Inc. (Eastport) and Waste Minimization and Containment Services, Inc. (WMC) propose a demonstration of a remotely operated paint removal system. Our paint removal system, Cryogenesis (trade mark), is based on carbon dioxide (dry ice) pellets propelled by nitrogen. The advantage of this technology is the elimination of additional waste generated during paint removal. This results in less than 0.2% of waste generated by sandblasting techniques. Consequently, the savings over the 1.04 billion square feet of U.S. Army buildings is \$2.6 billion. Additionally, our team is using an of-the-shelf remotely operated vehicle, Eagle, to minimize worker exposure during paint removal. Demolition of antiquated U.S. Army structures littered with lead paint has two fundamental problems: - Minimizing hazardous waste generated; and -Minimizing worker exposure during demolition. Out Eagle/Cryogenesis (trade mark) system solves these problems with existing off-the-shelf systems capitalizing on new technology and traditional strengths of Eastport and WMC.

ELECTRO-OPTEK CORP. 3152 KASHIWA STREET TORRANCE, CA 90505 Phone: (310) 534-3666 Topic#: 92-035 Office: CECOM Contract #:

ID#: 92EW 049

Phone: (310) 534-3666 PI: Eugene L. Dines Title: Dual-Mode Imager for Positive Identification of Friendly Vehicles in Combat

Abstract: We propose to develop a dual-mode sensor for positive all-weather identification of friendly vehicles in combat using 2-dimensional arrays of All-xGaxAs multiple quantum wells (MQWs) for detection long-wavelength infrared (LWIR) radiation and 2-dimensional arrays of 94-GHz millimeter wave (MMW) transceivers. The former will be fabricated by plasma-assisted metalorganic molecular beam epitaxy (PAMOMBE) and the latter by plasma-enhanced chemical vapor deposition (PECVD). In Phase I, we will first develop electron-cyclotron-resonance (ECR) sources for reactive epitaxy on insulating GaAs substrates, followed by the development of MQW IR detectors. We will design the sources and ultra-high-vacuum fixtures for epitaxy and delineate the PAMOMBE processes to grow MQW devices at a high growth rate and with high-quality epitaxy, and thus cost effectively. 94-GHz MMW integrated circuits will be designed and simulated. In Phase II we will fabricate several MQWs one on top of another forming a vertical stack of IR detectors, each responding to a different spectral band. We will then fabricate a prototype 2-dimensional array of these stacks for multispectral IR imaging and integrate it with a two-dimensional 94-GHz MMW array into a high-performance dual-mode sensor providing real-time and positive non-cooperative identification of friendly forces in combat in all weather conditions.

ELECTROKINETICS, INC.

Topic#: 92-151

ID#: 92WES-020

LOUISIANA BUSINESS & TECHNOLOGY, LSU, SOUTH STADIUM

Office: WES

Contract #: DACA39-92-C0140

BATON ROUGE, LA 70803 Phone: (504) 388-3992

PI: Robert Marks

Title: Feasibility of Using Acetic Acid for Improving Electrokinetic Remediation

Abstract: The basic scientific understanding acquired in development of electrokinetic remediation technology displays its potential in insitu removal of heavy metals, radionuclides and some organic chemicals from soils. One specific problem associated with the current processing technique is precipitation of the metal close to the cathode as a metal hydroxide. When this precipitate forms a lowly conductive salt, the electrical potential difference across the cell may increase decreasing the efficiency of removal and increasing the cost of remediation. There is a need to devise enhanced processing techniques to remove and/or avoid the precipitate close to the cathode. This study will investigate the use of acetic acid and/or ammonium acetate buffers to circumvent the encountered problem and enhance removal of metals in electrokinetic remediation. There are two advantages to using acetic acid in depolarizing the cathodic processes; (1) most metal acetates are highly soluble and the hydrogen ion is able to depolarize the cathodic electrolysis reaction thereby reducing the energy necessary in electrolysis and avoiding formation of the hydroxide species; (2) migration of an acetate anion upstream will cause formation of neutral acid and hence maintain a lower conductivity due to the association.

ELECTROMAGNETIC APPLICATIONS, INC. 300 COMMERCIAL STREET, UNIT, 805 BOSTON, MA 02109

Topic#: 92-110 Office: ETDL

Contract #:

ID#: 92ETD-024

Phone: (617) 720-3968
PI: Hoton How Title: Design of Wide-Band Self-Biasing Drop-In Microwave/Millimeter Wave Circulators

Abstract: In this proposal the possibility for wide-band operation of a drop-in circulator has been discussed based on a recent patent disclosure. For this purpose two approaches have been attempted. Since the circulator is biased below resonance, frequency tracking conditions may be obtained via suitable use of the dielectric filling material and the subtension angle of the circulator pots. It is hoped that octave bandwidth operation of the device can be ultimately realized. The second approach is based upon the operational principles relating to a waveguide partial-height ferrite junction circulator. Since the field profile in the drop-in circulator junction is analogous to that associated with the partial-height ferrite in a wideguide junction, we believe that the bandwidth of a drop-in circulator can be extended to at least 30% of its center frequency by using metal transformer with a pinning stub. Finally, we propose that hexagonal ferrites shall be used in the fabrication of millimeter wave devices. This elements the need of external biasing field even at high frequency operation of the circulator.

ENERGY CONVERSION DEVICES, INC.

1675 WEST MAPLE ROAD TROY, MI 48084

Phone: (313) 280-1900

Title: Application of Thin Film Thermoelectrics

Topic#: 92-077

ID#: 92TAC-008 Office: TACOM

ID#: 92TAC-041

ID#: 92BRL-005

Contract #: PI: Krishna Sapru

Abstract: The objective of this program is to develop a thin/thick film materials deposition process technology which will reliably provide high quality materials for constructing Peltier thermo-elements with a high figure of merit over the temperature range of 250-350 Deg K. The study will focus on the materials system consisting of (B1, Sb)2(Te, Se)3 alloys for both p- and n-type thermo-elements. Literature shows that specific compositions in this alloy system have provided high figures of merit (3.2 -3.4 x IO-3/Deg K at 300K) with a maximum Peltier cooling of 77 Deg K. Recently investigators at the University of Virginia reported a high figure of merit of 3.7 x 10-3/K for p- type (Bi, Sb)2(Te, Sb)3 alloy. The process selected for depositing the films in the proposed program will be a unique, high rate Microwave Enhanced CVO process (MECVD) developed at Energy Conversion Devices, Inc. ECD has achieved deposition rates as high as 300 Deg. A/sec for amorphous Si-H alloys using this technique, and this process has been developed for deposition on large area surfaces. Large area thin/thick film thermoelectric modules will be attractive for applications which require heating/cooling ability in a single, light-weight module.

ENGINEERING DEVELOPMENT CORP.

PO BOX 1971. AMES, IA 50010 Phone: (515) 232-5944 Topic#: 92-080 Office: TACOM

Contract #:

PI: Jerald M. Vogel

Title: Development and Demonstration of a Non-hydraulic Actuator for Application in Active and/or Semi-active Suspension

Abstract: A program for the preliminary design, prototype construction, and bench testing of a linear pneumatic suspension strut for application in non-hydraulic combat vehicle suspension systems is presented. The proposed suspension strut system components include an air spring, accumulator, and variable size orifices for the active control of strut dynamic performance. Strut natural frequency, damping ratio, and strut extension are independently adjustable parameters over a specified range of values through controlled sizing of the system airflow orifices and an air source. An optimal control study using a classical Calculus of Variations (Mayer formulation) approach is proposed to determine the feasibility of the strut in an active control system for a quarter vehicle model. System objective functions under consideration include various combinations of vehicle ride quality and controllability. The proposed effort includes a detailed design of the linear suspension strut and bench testing to verify strut natural frequency and damping ratio ranges.

ENIG ASSOC., INC.

SUITE 500, 11120 NEW HAMPSHIRE AVENUE SILVER SPRING, MD 20904

Phone: (301) 593-4471

Title: Design of a MAHEM Shaped Charge Warhead

Topic#: 92-105

Office: BRL Contract #:

PI: Dr. D. John Pastine

Abstract: We describe our novel concept of a magnetohydrodynamic explosive munitions (MAHEM) and apply it to the design of a shaped charge. The MAHEM is an explosive warhead that utilizes magnetohydrodynamic effects to transfer the "global" explosive energy (that is mainly wasted in a conventional warhead) at electromagnetic speeds to a "localized" region where it may act on the metal mass of a shaped charge cone that is to be propelled in a given direction toward a target. Our concept exploits the phenomenon of electromagnetic braking for the purpose of transforming the kinetic energy of detonation products in one part of a system to kinetic energy of metallic ejecta in another part. Hence, the local region can become a region of huge energy accumulation. It should be possible to propel metallic ejecta at velocities much greater than can be done using explosives alone...or to propel a much greater mass...in order to obtain greater kill probabilities. Methods for doing this are outlined, and some examples are provided. The explosive used in the MAHEM can be a truly insensitive explosive, e.g. TABT, resulting in invulnerability to accidental detonation.

ENSCO, INC. 5400 PORT ROYAL RD. SPRINGFIELD, VA 22151

Phone: (703) 321-4540

Title: Nondestructive Testing from Fuzed Data

Topic#: 92-005

Office: ARDEC Contract #:

PI: John Perry

Abstract: Nondestructive inspection using fused data from diverse inspection sensors has the potential for characterizing defects within ordnance items which may not be characterized properly by one sensor only. Data from different NDI methods are often complementary, thereby adding diagnostic information to help lead the inspection to the correct decision about the disposition of a defect. The objectives of the Phase I proposed effort are to design and implement a technique for fusing nondestructive sensor data. We will develop the fusion system for a specific problem that confronts Picatinny Arsenal in the analysis of ordnance items. In addition, we will design the fusion system to be general enough to fuse any type of sensor data. The general objectives of the Phase I project are to lay down a foundation for developing a robust image-encoding scheme that will allow a neural network-based classifier to reliable distinguish between various defect classes. We will also design a decision-level fusion methodology that is able to combine different forms of evidence relating to the nature of particular defects found in ordnance.

EPILOGICS, INC. 160 C ALBRIGHT WAY LOS GATOS, CA 95030

Phone: (408) 379-5200

Topic#: 92-009

Office: AVSCOM

Contract #: PI: Frank A. Fitz

Title: High-Speed Lightweight Over-Running Clutch for Rotorcraft

Abstract: Current helicopters use cam locking (friction type) over-running clutches to achieve a free wheeling behavior which is necessary in their drive trains. These conventional over-running clutches tend to be rather large and heavy when designed to meet functional and flight safety requirements. Epilogics has developed a unique positive locking over-running clutch called Mechanical Diode (MD) which allows strong, light weight and extremely reliable designs with almost complete immunity to torsional vibration. One version of the over-running clutch is presently manufactured by Epilogics for automotive racing applications where strength and durability are critically important. We expect to achieve a design which will be suitable for use between a helicopter engine and drive train. This over-running clutch will provide helicopter driveline manufacturers a lighter, stronger (per unit weight), more reliable and torsionally rigid alternative to the sprag and roller ramp devices presently in use.

ESEA SUITE B-15, 5150 EL CAMINO REAL LOS ALTOS, CA 94022

Phone: (415) 962-1167

Topic#: 92-146

Office: TOP Contract #:

PI: Stanley Dallal

Title: Development of a Hierarchical Dual-Function Terrain Data Set

Abstract: A hierarchical dual-function terrain data set must be designed to ensure rapid access to complex data structures, allow for frequent data modification and be compatible with existing Geographical Information System (GIS) applications. Although widely used, conventional database management systems have shortcomings in their ability to handle geographic information efficiently. An object-oriented database (OODB) design is proposed for the development of a hierarchical dual-function terrain data set. To prove the feasibility of this approach, tasks are outlined that together will develop and test a compilation strategy that will convert an existing data set into an object-based data set. In addition, the concept of providing the OODB the ability to convert itself into a format compatible with existing GIS applications is explored. The enhanced speed and flexibility of an OODB promises to find widespread use in the growing commercial and government GIS market. Data development and maintenance costs will decrease due to the increased portability and natural extensibility of the OODB in accommodating new data types such as multimedia.

ESEA SUITE B-15, 5150 EL CAMINO REAL LOS ALTOS, CA 94022

Topic#: 92-148

Office: TOP Contract #:

ID#: 92TOP-033

ID#: 92ARD-037

ID#: 92AVS-031

ID#: 92TOP-002

Phone: (415) 962-1167

PI: Warren Horowitz

Title: Feature Code Conversion Software

Abstract: Geographic Information Systems (GIS) technology is a rapidly evolving area of technology. To preserve investments made in crating existing databases, a method for automated GIS data conversion is needed. Tools for the conversion of spatial data exists, but the tools for non-spatial data conversion need further development. The overall objective of this project (Phases I and II) is the development of software to analyze, reconcile, and convert non-spatial GIS data from one scheme to another. The proposal is for the Phase I effort. The rule-base of a rule-based expert system will be developed and demonstrated. The effects of conversion between various GIS database structural architectures, and between various logical and physical formats will be analyzed. An appropriate rule set that addresses issues such as the applicability of traditional software techniques, data precision, error correction, and the reporting of data conversion quality will be created. The rule set will be demonstrated through a simplified conversion on paper. The effort will progress in three parts: information gathering, analysis, and a demonstration, which will be incorporated into the final report. Upon completion of the Phase I effort, a conceptual design of the complete system will be available.

FASTMAN, INC. 1414MILLARD STREET BETHLEHEM, PA 18018 Phone: (215) 691-2577 Topic#: 92-062 Office: MICOM Contract #:

PI: Dr. Michael Tucker

Title: Fractal and Wavelet Signal Procesting Techniques for Radar Guided Missiles

Abstract: In this project FASTMAN will determine the feasibility of using fractal and wavelet signal preprocessing in conjunction with neural network pattern classifiers on high-range resolution radar data for detecting cold stationary ground targets in a clutter-rich environment. Previous researchers have demonstrated that measurement of the fractal dimension of high-range resolution (HRR) returns can be used to distinguish stationary targets in clutter rich environments. Other groups of researchers have shown that the Wavelet Transform can be used to accurately and efficiently measure the fractal dimensions of signals by examining the behavior of the transformed signals across scales. We propose to marry these two concepts into a signal preprocessor in which the Wavelet Transform will compute the local fractal dimensions of HRR returns, and those fractal dimensions will form a feature vector which will be used by neural network pattern classifiers to distinguish targets in the backscattered signal. We will also investigate the applicability of two other Wavelet processing techniques for radar signal processing: the use of the Adaptive Wavelet Transform to extract key target features and the use of doppler-tolerant wavelet radar pulses.

FEDERAL FABRICS 21 MARIE DRIVE ANDOVER, MA 01810 Phone: (508) 470-1859 Topic#: 92-073

Office: NATICK
Contract #:
PI: Zvi Horovitz

Title: Fabrication Methods for Pressurized Fabric Arches

Abstract: Seamless curved high pressure beams could be produced by knitting, braiding and weaving. It was determined already that weaving is offering the best potential for resisting snow load due to the higher density and direction of the fiber alignment. Two basic types of curved tubular weaving were considered, a single shuttle flat loom and a multishuttle circular loom. After considerations, the circular loom was selected as the preferred method. The circular loom is of a very high production, and can be designed to accommodate an inner tube integrally during the weaving. The circular loom by definition working out if a creel warp, which makes it easy to weave a curved tube. A circular loom can also control the weft yarn rotation on its own axis precisely to prevent undesirable twisting of the weft if a tape shape yarn is woven.

FERMIONICS CORP. 4555 RUNWAY STREET SIMI VALLEY, CA 93063 Phone: (805) 582-0155 Topic#: 92-043 Office: CECOM Contract #: PI: Muren Chu

ID#: 92NV -030

ID#: 92NAT-127

ID#: 92MIC-035

Title: Infrared Material Growth and Detector Processing Technology for Monolithic Dual-Band Detectors

Abstract: Infrared detectors have wide applications in missile guidance, surveillance and smart ammunition. Within the infrared

spectrum, multi-color detection is highly desirable. Among the two color detectors, the ones with multi-spectral response and sharing the common optical area are of particular interest for military applications. The goal of this program is then to develop a technology to produce two color detectors, arrays and focal plane arrays. The final FPAs to be produced by the technology developed in this program will have a monolithic structure, a common sensing area and will be on silicon wafers. The infrared material will be HgCdTe grown by MOCVD method. In this Phase I program period, HgCdTe multilayers consisting of MWIR and LWIR layers will first be produced. Subsequently, two color detectors will be fabricated in these materials by ion implementation and related processing steps. There are a number of two color detector types. By the end of this Phase I period, we will determine which type will be favored and be used in the Phase II program for producing FPAs. In the second phase of this program, multiplexers for operating two color detector arrays will be designed and fabricated. The HgCdTe two color detector arrays will be integrated to the multiplexers and then the final FPAs will be tested.

FERMIONICS CORP. **4555 RUNWAY STREET** SIMI VALLEY, CA 93063

Phone: (805) 582-0155

Title: Semiconductor Optical Amplifiers for Microwave Applications

Abstract: There are three major issues about the semiconductor amplifiers design to be addressed here: 1. that the design meets the microwave applications' requirements in term of noise, bandwidth and dynamic range, 2, that it is compatible to integration with other opto-electronic components such as detectors, waveguides and lasers, and 3. that they are compatible to integration with current and future MMIC technology. A basic waveguide structure, common to lasers, detector and waveguide, is proposed here for optical amplifiers, integratible with MMICs. By choosing a common structure these components can be readily integrated together without the need for complicated multiple growth procedures and conflicting material and process requirements. The idea centers on the principle that the property of a gain medium can be manipulated by injection of carriers

to vary its gain. Similarly, for an absorbing medium by adjusting its reverse bias voltage its absorption can be varied.

FIBER MATERIALS, INC. 5 MORIN ST. BIDDEFORD, ME 04005

Phone: (207) 282-5911

Title: Development of Activated Carbon Fibers

Topic#: 92-067 Office: NATICK Contract #:

Topic#: 92-118

Office: ETDL

Contract #: PI: Yet-Zen Liu ID#: 92ETD-040

ID#: 92NAT-029

ID#: 92ARD-049

PI: John W. Herrick

Abstract: High surface area, super adsorbent activated carbon fibers are potentially an excellent adsorptive material for chemical protective uniforms. However, these fibers are not currently available from a domestic source. A Phase I program is proposed to demonstrate the feasibility of producing laboratory scale quantities of short highly activated carbon fibers based on a U.S. developed process (U.S. Patent No. 4,082,694). Carbon fibers from four precursor fibers will be obtained; pitch, PAN, phenolic resin and rayon. These fibers will be carbonized with excess potassium hydroxide at temperatures to 800-900 C. washed and dried. The resulting fibers will possess effective BET surface areas of well over 1500M2/gram and provide excellent toxic vapor adsorption when fabricated into a flocked fabric.

FOSTER-MILLER, INC. 350 SECOND AVE WALTHAM, MA 02154 Phone: (617) 890-3200

Title: Advanced Material Gun Barrel

Topic#: 92-003

Office: ARDEC Contract #:

PI: Thomas G. Campbell

Abstract: Improvement to machine gun type automatic weapons is limited by the wear and erosion rates on current gun barrel materials. The technology exists for increasing rates of fire and muzzle velocities with new projectiles. These advanced projectiles develop significantly higher flame temperatures and bore pressures. Gun barrel erosion is accelerated by the combination of the high temperature gas erosion and the friction between the projectile and liner. Significant improvements to accuracy and lethality can be realized with improved gun barrels that withstand these advanced projectiles. The proposed program combines the experience of Saco Defense, Inc. and Foster-Millers's unique gun barrel design concept to produce a structure capable of withstanding the severe erosive environment, providing for greatly enhanced thermal conductivity both

through and along the barrel axis. A ceramic liner will be used at the bore with a reinforcing carbon-carbon (C-C) sleeve. The C-C sleeve will be embedded with radial P100 graphite fibers using Foster-Miller proprietary technology. P100 fibers exhibit among the highest thermal conductivities known and will be used along the barrel axis as well. The unique properties of C-C materials to increase liner compression with temperature, because of the negative CTE, will overcome a common problem encountered with metallic sleeves. The program will entail design, fabrication, and testing of a typical liner/sleeve assembly in Phase I. The thermally induced strains, confirmed in Phase I, will form the basis of a Phase II program which will include rapid fire testing of the gun barrel.

FOSTER-MILLER, INC. 350 SECOND AVE WALTHAM, MA 02154 Phases (617) 800 3700

Phone: (617) 890-3200

Title: Less Than Lethal Ballistically Deployed Sting Nets

Topic#: 92-004

ID#: 92ARD-050

ID#: 92BRD-080

ID#: 92MIC-118

Office: ARDEC
Contract #:

PI: Arnis Mangolds

Abstract: A means of ballistically deploying a less than lethal sting net is proposed. The system developed is capable of capturing fleeing, static or attacking suspects via a LOS ensnarement munitions delivered from a 38mm weapon or a similar platform. The flight and capture principles have been proven in previous test programs and many of the subsystems have undergone initial optimization. A unique fuzing technique permits the munitions to remain in a packaged state to avoid entanglement with intermediate objects. The streamlined profile gives the munitions range capabilities exceeding current less than lethal weapons. It also results in a stable flight pattern resulting in simplified aiming. A conservative design approach has resulted in a system that is less than lethal throughout the complete 0 to 30m range. Enhancements are suggested which can extend its range and extend the demobilization of the target. By integrating an electrical discharge system into nets construction the concept evolves into a deployable electric fence or sting net. The primary challenge is the fuzing system which activates both net deployment and the High Voltage Pulse (HVP) Taser. Development procedures for investigating the munitions fuzing system is proposed.

FOSTER-MILLER, INC. 350 SECOND AVENUE WALTHAM, MA 02154

Phone: (617) 890-3200

Topic#: 92-027

Onice: BRDEC Contract #:

PI: Paul Chambers

Title: Infantry Fighting Position - Overhead Cover and Revetment System

Abstract: The rapidity with which reconnaissance assets can locate and identify defensive perimeters and the speed with which fire can be brought to bear on that target dictate that U.S. Army must be capable of providing its infantry and other ground forces a means of protecting their infantry fighting positions (IFP) from both direct and indirect fire in the shortest possible time after arrival at a defensive location. This protection system consists of two components, an overhead cover (OHC) for ballistic protection and a revetment system to support the walls of the IFP against blast loadings. Foster-Miller proposes to develop and demonstrate an IFP-OHC system which will meet the IFP revetment and ballistic requirements in a standardized but tailorable kit while minimizing installation time and maximizing the protection level provided to the infantry soldier. The system is based on a composite batten and fabric revetment frame and a laminatEd composite sandwich OHC panel fitted with threat specific applique armor. This methodology provides requisite protection from direct (7.62 mm) and indirect fire threats (155 mm), including overpressure from point detonating and airburst artillery, as well as IFP wall collapse caused by delay fuzed artillery rounds.

FOSTER-MILLER, INC. 350 SECOND AVENUE WALTHAM, MA 02154 Phone: (617) 890-3200

Title: Fractal Image Sensor

Topic#: 92-059

Office: MICOM
Contract #:

PI: Dr. Lawrence H. Domash

Abstract: Fractal mathematical concepts are useful for modeling natural image backgrounds (foliage, clouds, sand dunes) and can help discriminate target from background in IR/thermal images on the basis of fractal dimension - particularly useful in a multiband data environment requiring sensor fusion. Similar possibilities exist for data returned from millimeter wave radar

guidance. To date, however, fractal characterization of captured image data has been considered too computationally intensive for real-time response. Foster-Miller has developed a real-time "fractal image sensor" which instantaneously measures fractal dimension by using a parallel optical coprocessor based on photorefractive non-linear optics. By reducing complex image textures to a small fractal feature vector, electronic neural networks can also be applied to the coprocessor output for training on more subtle fractal characteristics. Phase I research will test the applicability of the fractal optical coprocessor to a database of typical IR/thermal imagery and also evaluate the potential for an all-electronic implementation. Phase II will construct a complete hybrid optical/electronic thermal image computer incorporating image segmentation and analysis, fractal modeling and synthesis, a dedicated fractal coprocessor for high speed characterization, and neural network training.

FOSTER-MILLER, INC. 350 SECOND AVENUE WALTHAM, MA 02154 Phone: (617) 890-3200

Title: Innovative Pulse Fired Instant Hot Water Heater

Topic#: 92-070 Office: NATICK ID#: 92NAT-098

ID#: 92NAT-119

ID#: 92TAC-015

Contract #: PI: Hans Hug

Abstract: Current hot water heating is done with antiquated immersion heaters in can or in pots held over burners. Such batch type heaters are very slow and inefficient and have no provision for filling the tank from its source of cold water, nor for supplying a pressurized flow for effective use of the hot water, unless electrical or engine driven water pumps are utilized. Foster-Miller is proposing a self powered, light weight and highly efficient resonant pulse jet burner capable of meeting the U.S. Army's requirements for a nonpowered instantaneous hot water heater. It can be powered by a wide selection of liquid fuels such as gasoline, kerosene and turbine fuels. The proposed resonant pulse jet burner an extension of resonant pulse jet tubes used in insect foggers has been successfully started and tested over a temperature range from -35 F to 100 F. The instant hot water heater features a pressurized, counterflow design with built-in steam dome from which steam can be withdrawn for the operation of a piston type boiler feedwater pump. The projected design - when fully developed - will be capable of delivering approximately 35 gal/hr of pressurized hot water at an outlet temperature of 160 F. Poster-Miller's pressurized hot water heating concept can also be commercialized for applications in camping, construction, civil emergencies and in remote areas.

FOSTER-MILLER, INC. 350 SECOND AVENUE WALTHAM, MA 02154 Phone: (617) 890-3200

Topic#: 92-071 Office: NATICK Contract #: PI: Robert Kovar

Title: Improved Toughness Ballistic Protective Fiber Through Molecular Modeling

Abstract: Current body armor polymer fibers are limited in ballistic performance by their tendency to lose axial tensile strength under the combined loading of lateral compression, lateral shear and axial tension that occurs during impact. This requires the use of heavier, bulkier, costlier body armor. The Foster-Miller team, which includes renowned rigid-rod polymer and molecular modeling consultants, will apply computer modeling for the first time and completely redesign the ballistic fiber to address its deficiencies. We will apply a micro-mechanical model to design rigid-rod and other specialized polymers for fibers that exhibit high tensile strength (>30 gpd), high modulus (>500 gpd), higher elongation (>5 percent) and strong intermolecular interaction. Such fibers will show improved ballistic performance because of higher toughness, owing to their special polymers design. In Phase I, we will identify novel polymer designs that demonstrate the potential for achieving greater than 60 percent improvement in ballistic fiber V50 performance against 17 grain FSP's in fabric form. In Phase II, we will refine and apply the technology to prepare fibers from the best polymers for complete evaluation. The principal investigator is an expert in ordered polymer design and synthesis, innovative fiber processing, advanced composites and ballistic protection.

FOSTER-MILLER, INC. 350 SECOND AVENUE WALTHAM, MA 02154 Phone: (617) 890 3200

Title: Mission Function Automation - AVLB

Topic#: 92-078
Office: TACOM
Contract #:

PI: Paul A. Chambers

Abstract: The AVLB is a combat system employed in the assault phase of land operations to provide a means for rapid narrow gap crossing. This mission dictates that the AVLB often leads the way and hence can be subject to direct and indirect enemy

fire. This fact suggests the minimization or total removal of the crew from this vehicle and the development of a remote operation system for it. The data required by the operator to ensure a successful bridge deployment is immense, including vehicle and AVLB status, vehicle location and orientation relative to the gap and gap profile. However, as the bandwidth of the operational radio fit of these vehicles precludes the use of standard video based remote control systems, a non-video based system must be developed. Foster-Miller proposes an animated graphics based remote control display system which minimizes the operator data overload possibilities by automating as many control functions as possible. This automation will minimize data flow rates and improve the efficiency of the operator in his primary role - providing a bridge for the assault forces to cross. Foster-Miller also offers an optional development of a near real-time "snapshot still video" as a means to enhance operator virtual presence at the bridging site.

FOSTER-MILLER, INC. 350 SECOND AVENUE WALTHAM, MA 02154 Phone: (617) 890-3200

Phone: (617) 890-3200 PI: John Gassner Title: Rapid High Quality Field Repair Methods for Thick Section Composite Vehicle Structures

Abstract: Field repair methods for composite aircraft structures fail to account for the unique materials, construction and failure modes associated with thick section fiberglass composite combat vehicle structures. Although acceptable repair techniques for thick laminates have been demonstrated in the laboratory, most viable techniques require the application of heat to cure an adhesive or resin. Heating blankets, hot air, heat lamps and solar radiation are field deployable, but they all rely on heat transfer from the surface through the thick, low thermal conductivity laminate. Depending on the environment, it may take many hours to effectively cure through the thickness of the laminate. Such a lengthy procedure could severely tax field maintenance assets. In or near a combat zone, time is a life or death matter. Foster-Miller proposes a practical means to drastically reduce the time required to effect high quality field repairs. Our method would combine two proven thick laminate repair methods, resin injection and through-thickness fasteners, with an ultra-rapid, simple and safe microwave heating method. We believe that this method has the potential to reduce field repair time from many hours to less than an hour. In Phase I, we will demonstrate that a man-portable microwave hood, comprised of low cost commercially available components, can be used to rapidly and safely heat repair adhesives injected into interior delamination surfaces in a fiberglass laminate. Our team member, FMC, has agreed to provide samples at no cost to the program. In Phase II, detailed repair procedures will be developed, validated, and catalogued in a field repair handbook.

FOSTER-MILLER, INC. 350 SECOND AVE. WALTHAM, MA 02154

Phone: (617) 890-3200 PI: Arnis Mangolds Title: GRID: Time-Based Seismic/Acoustic Multiple Submunition Function and Localization

Abstract: The proposed technique uses a mix of time-based acoustical and seismic information which will not only determine the functionality of the individual submunitions, as well as determine the location of their detonations. This is accomplished real-time, remotely and automatically. By optimizing the signal to noise ratios and using appropriate matched filters and sensor fusion techniques, the possibility exists for locating and determining the timing and level of detonation. The technology permits immediate feedback for optimized training and efficient acceptance testing.

FOSTER-MILLER, INC. 350 SECOND AVE. WALTHAM, MA 02154 Phone: (617) 890-3200

Title: Planar Integration for Nonlinear Micro-Optics

Topic#: 92-120 Office: HDL Contract #:

Topic#: 92-093

Contract #:

Office: TECOM

Topic#: 92-086

Contract #:

Office: TACOM

ID#: 92TAC-091

ID#: 92TEC-004

ID#: 92HDL-013

PI: Dr. Parviz Tayebati

Abstract: A variety of useful optical and electro-optical elements are normally fabrication-incompatible in that they cannot be grown on the same substrate. The ability to integrate and interconnect incompatible nonlinear and linear devices would have considerable impact on a wide range of optical and optoelectronic applications. Planar micro-optics offers a unified medium provided active nonlinear semiconductor devices can be successfully integrated. Foster-Miller proposes an interdisciplinary

concept combining the flexibility of alignable epitaxial lift-off (ELO) processes with the quasi 3-D Interconnectibility of quartz or sapphire based planar microoptics. The proposed program aims at integrating a number of thin film active devices including GaAs and InP bistable logic elements and switches, diffractive optical elements, and dynamic composite holograms - all currently under development at Foster-Miller - as well as commercially available devices such as semiconductor diode lasers, LEDs and detector arrays. Phase I will test the feasibility of the proposed unified detector device composed of a GaAs LED, two holographic interconnect gratings, mirror and GaAs detector on quartz substrate. Phase II research will demonstrate fully functional optical computing subsystems. Ultimate applications include optical memories, digital optics, optical interconnects, optical displays, and image processing computers.

FOSTER-MILLER, INC. 350 SECOND AVENUE WALTHAM, MA 02154 Phone: (617) 890-3200 Topic#: 92-133 Office: MTL ID#: 92MTL-207

Contract #: PI: Ramki Iyer

Title: Development of Advanced NDE Sensors and Related Software for Expert Composite Manufacturing

Abstract: Advanced composite materials are finding new applications in critical components of military and commercial equipment to exploit their synergistic properties. Therefore, it is necessary to monitor in real-time the integrity of critical composite components during the manufacturing processes. Accomplishing this task (producing high quality/reliable components) will reduce/eliminate the in-service catastrophic failures of the components. Additionally, manufacturing expenditures will be reduced due to a reduction in scrapped components and waste time and energy. Foster-Miller proposes a novel system consisting of advanced NDE sensors and related software to develop an "expert" manufacturing process. The concept employs magnetostrictive particles (sensors) embedded in a composite to detect the changes in magnetic signatures associated with the stress fields due to voids, cracks, holes, delaminations and thickness variations. Magnetic detectors can be used to monitor the magnetic signatures. In addition to the NDE sensors Foster-Miller will develop algorithms to collect, record, store and interpret the sensor signals. An "expert" system will be developed to make "expert" changes to the manufacturing process to increase product quality and reliability based on the sensor data. In summary, the Army will have developed an advanced technique to improve the quality and reliability of critical equipment such as composite gun barrels now under investigation; composite armor and outer skins on tanks and personnel carriers; and composite rotor blades on helicopters. Additionally, the Army will realize a savings on equipment acquisition due to reduced manufacturing costs.

GENERAL ATRONICS CORP. 1200 EAST MERMAID LANE PHILADELPHIA, PA 19118 Phone: (215) 233-4100 Topic#: 92-026 Office: BRDEC

ID#: 92BRD-096

Contract #:
PI: Thomas W. Jewitt

Title: INTRUSION DETECTION FROM A MOVING PLATFORM

Abstract: Automatic Target Recognition (ATR) broadly refers to the problems of target detection, acquisition/tracking. The processing is completely autonomous in extracting the necessary information from sensor inputs, in processing, and final decision-making. In addition to the traditional military applications, ATR algorithms can be adopted to endow a mobile sentry robot with the capability to detect intruder generated phenomena. Monocular parallax extracted by tracking objects viewed from a mobile CCD camera is converted to three-dimensional (3-D) position estimates. Simulations have demonstrated that (1) the resolution and accuracy at which a robot can sample its environment using a mobile CCD camera is significantly greater than that achieved using sonar (2) by comparing perceived angular motion of objects in its environment with that expected of Stationary objects, the robot can detect body movement of an intruder while on the move, and (3) 3-D position estimates of objects in the robot's environment can be exploited for autonomous navigation, obstacle avoidance, and map generation. It is proposed that the aforementioned capability be complemented with processing and hardware subsystems which detect different types of intruder generated phenomena as follows: By comparing the 3-D position of objects as determined on the first patrol with that of objects as determined on subsequent patrols, the robot can detect a Stationary intruder or disappearance of possessions. Also, microphones would allow the robot to detect an intruder which it can "hear" not "see."

GEO-CENTERS, INC.

7 WELLS AVE

NEWTON CENTRE, MA 02159

Phone: (201) 663-5980

Title: Formulations with Enhanced Energetic Output

Topic#: 92-002

Office: ARDEC Contract #:

ID#: 92ARD-044

ID#: 92HDL-065

ID#: 92WES-022

ID#: 92AVS-015

PI: Gerald Doyle

Abstract: 1,3,3-Trinitroazetidine (TNAZ) has emerged as an important new energetic material for warheads, main explosive fill in bombs, and as an ingredient in LOVA propellants. Initial testing has shown its detornation performance is superior to that of HMX, outperforming the calculational prediction. With good performance, thermal compatibility and sensitivity characteristics, coupled to the ability to formulate and process TNAZ, this material can be exploited in a broad spectrum of applications. The proposed effort will establish formulation and processing parameters and bring into focus performance aspects for TNAZ-based press-loadable explosives. Formulations that are 100% HE fill, such as binderless TNAZ/NTO, may result in additional energetic output due to overdriving the NTO fill when the TNAZ matrix undergoes detonation. Any formulations investigated during this study can easily be scaled-up and submitted for large-scale performance testing.

GRAPHIC RESEARCH, INC.

9334 MASON AVE

CHATSWORTH, CA 91311

Phone: (818) 886-7340

Title: Solder Plating Process Control

Topic#: 92-124

Office: HDL Contract #:

PI: Nancy Zolfagari

Abstract: The objective is to evaluate and investigate a surface oxide tester unit (SERA) Sequential Electrochemical Reduction Analysis, in order to be utilized in our solder production line. The system will be tested to assess its capabilities, limitations and the effect of its variables on the control parameters of solder plating. Also, SERA is to be evaluated as an alternative test method to typically traditional solderability test methods which are based on a subjective, visual and unreliable inspection method.

GREEN MOUNTAIN RADIO RESEARCH CO. 50 VERMONT AVENUE, FORT ETHAN ALLEN

COLCHESTER, VT 05446 Phone: (802) 655-9670 Title: RF Transmitter/Locator Topic#: 92-150

Office: WES

Contract #: DACA39-92-C0132 PI: Frederick H. Raab, PhD

Abstract: The RF transmitter/locator (TL) concept presented in this proposal enables the location and recovery of a canister such as a nose cone, artiflery shell, buoy, or instrument package. The system operates over a distance of 5 mi on the surface and several hundred feet through soil, sand, or fresh water. The RF TL is battery-powered, small in size, highly shock resistant, and it consumes a minimum amount of power. It operates at a selectable frequency with a programmable delay to conserve power. While line-of-sight (LOS) communication on or above the surface requires little power and a minimal antenna, through-the-earth communications (TEC) subjects the signal to significant attenuation. The feasibility of a low-power, miniature TEC transmitter therefore depends upon optimization of the system parameters (frequency, modulation, operating mode), receiver (noise cancellation), and transmitter (antenna and power amplifier). The proposed program therefore first reviews and optimizes various aspects of the system, including near-field location techniques, VLF (TEC) link, HF(surface-to-surface) link. and transmitting antenna. It then addresses key implementation issues including transmitter organization, ASIC implementation, and receiver considerations. The end result will be a feasibility determination and preliminary design of the system and hardware for the RF transmitter/locator.

GUIDED SYSTEMS TECHNOLOGIES 430 TENTH STREET, NW. SUITE S-002 ATLANTA, GA 30318

Phone: (404) 873-3493

Title: Intelligent Nonlinear Control of Remotely Piloted Model Scale Helicopters

Topic#: 92-007 Office: AVSCOM Contract #: PI: J. Eric Corban

Abstract: An intelligent nonlinear control methodology, based on an innovative combination of feedback linearization and artificial neural networks, is to be adapted to control remotely piloted helicopters. A mapping is derived which transforms a nonlinear dynamic model of the plant into a linear, time invariant space. A single point linear controller design is then carried

out in this linear space. The derived control is then mapped back into the nonlinear space using an inverse transformation. An artificial neural network can be trained prior to flight to realize the inverse mapping in real time. A second network can be trained in flight to learn, and correct for, the vehicle characteristics not captured in the dynamic model used to derive the control. The feasibility and value of this approach is to be demonstrated by evaluation of a controller design for the current US Army/NASA X-Cell model-scale helicopter using a high fidelity dynamic simulation. The design will include optional position feedback loops which can be used to track a prescribed trajectory. Once the computational burden of the control algorithm has been quantified, conceptual design of flight worthy hardware will begin. Detailed design, construction, test and evaluation will be carried out in Phase II.

GUMBS ASSOC., INC.

11 HARTS LANE

EAST BRUNSWIK, NJ 08816

Phone: (908) 257-9049

Title: Flexible EMI Shielding Materials Using Conducting Copolymers

Topic#: 92-068

ID#: 92NAT-037

Office: NATICK Contract #:

PI: Dr. Ronald W. Gumbs

Abstract: There is a need for flexible EMI shielding material in the construction of tactical shelters. This proposal outlines a programs to develop such a material using wire mesh or knitted wire mesh sandwiched between two sheets of an electrically conducting copolymer which is elastomeric in nature. The proposed material will maintain its flexibility so that when flexed a number of times, it will not fracture or lose its initial effectiveness. It is also anticipated that the material will be rugged and durable. The proposed work relies on prior experience at Gumbs specifically in the use of conducting polymers for EMI shielding composites and encapsulants. During Phase I, prototypes will be fabricated and tested in efforts to demonstrate feasibility of the concept. Larger panels will be prepared during Phase II to conduct full scale performance and evaluation tests.

GUMBS ASSOC., INC. 11 HARTS LANE

EAST BRUNSWICK, NJ 08816

Phone: (908) 257-9058

Title: Corrosion Resistant Composites Based on Conducting Polymers

Topic#: 92-106

Office: BRL Contract #:

PI: Dr. Guang-Way Jang

Abstract: This proposal aims to design, identify and synthesize ideal conducting polymers for the fabrication of corrosion resistant composites. Many of the material failures in military equipment are caused by galvanic corrosion. Our approach to this problem is to incorporate conducting polymers into metal/polymer composite systems. It has been demonstrated that conducting polymers are able to poise the mixed potentials of metals in the most stable region therefore interfering with the corrosive degradation process. The composites could also provide selective UV, Visible, IR and thermal signature reduction, and EMI shielding. The major advantages of the novel conducting polymer materials include: wide-range applicability, light-weight, durability, superior mechanical properties, improved environmental stability and cost effectiveness. We propose several approaches to design and fabricate novel corrosion resistant composites as detailed below. The proposed research seeks to further improve these materials by using polymeric and/or fixed dopants. A combined computational and experimental approach will be used to improve the electrochemical properties of conducting polymers and the metal/polymer interaction.

HARRIS TECHNOLOGIES, INC.

6636 TANSEY DRIVE

FALLS CHURCH, VA 22042

Phone: (703) 255-9456

Topic#: 92-096

ID#: 92STR-005

ID#: 92BRL-019

Office: STRICOM

Contract #:

PI: James C. Harris, Phd

Title: Application of Info-Geometric Instrumentation for the Interactive "Virtual" Integration of Large Scale Battlefield & TES

Combined Arms Forces

Abstract: Research associated with this Phase I Small Business Innovative Research proposal, and its possible Phase II follow-on. are expected to demonstrate the feasibility and practicality of use of affordable info-geometric instrumentation technology for accurately integrating real and virtual forces, crews and advanced weapons systems in combined laboratory (trainer) and field (operational maneuvering) tactical engagement simulations. In addition, the potential will be demonstrated for info-geometric field/trainer instrumentation to support human factors experiments and crew performance evaluation/modeling. Two powerful

info-geometric (IG) approaches to be employed in the subject research are the SESCO, Inc. "SMART WEAPON ADJUSTABLE ASPECT AND RANGING MICROINTERCEPTOR" ('SW&RM') and the Info-Geometrics, Inc. "ORGANIC SELF-ORGANIZING INFORMATION- and RANGE-BASED IFF SYSTEM" ('OSIRIS'). The two complementary, proprietary, info-geometric technologies can be employed in common, low cost 'open architecture' hardware. Harris Technologies, Inc. holds application licenses for both patent-pending technologies. The proposed six month Phase I research consists of a two month application requirements analysis task - including attendance at one or more Simulations Standards Compatibility Workshops, followed by an additional two month info-geometric instrumentations application system architecture definition phase. Application requirements analyses would include consideration of such PM-TRADE future application technology requirements as those associated with Battlefield Distributed Simulator Development (BDSD) and Mobile Automated Instrumentation Suite (MAIS). The final report, which will be submitted in the fifth month, will analysis expected technical merits and cost benefits to be derived from an application of the proposed research, together with the definition of an eight-to-ten month SBIR Phase II info-geometric instrumentation system feasibility demonstration. The proposed Phase II feasibility demonstration is expected to 'realistically project into the field' an instrumented laboratory platform surrogate that possesses a convincing ability to physically and functionally int

HITTITE MICROWAVE CORP.

21 CABOT RD WOBURN, MA 01801

Phone: (617) 933-7267

Title: Low Power Monolithic Microwave Integrated Circuits

Topic#: 92-126

Office: HDL Contract #:

PI: Leonard Reynolds

ID#: 92HDL-078

ID#: 92MIC-025

Abstract: In Phase I of DARPA MIMIC program, Hittite Microwave Corporation, in co-operation with Harry Diamond Laboratories, has developed a GaAs MMIC chip which performs complete RF functions of an FM-CW radar designed for proximity fuze applications in Army's Multi-Option Fuze for Artillery (MOFA). The RF package for this fuze is a miniature IC package measuring .25" x .25" x .09". The RF assembly integrated with a single-patch antenna is about the size of a five-cent coin. This MMIC radar consumes .9 to 1.25 watts of DC power. In Phase 2 of the MIMIC program, Hittite has a task of developing a smaller and lower-cost chip which consumes much less DC power for fuzing applications in small munitions. MMIC processes based on enhancement/depletion-mode MESFET and hetero-junction bipolar transistor (HBT) devices are becoming available as stabilized production processes. These new device technologies will be utilized to develop lower cost, less power hungry radar MMIC with added performance capabilities. In addition to the basic radar function, the new radar chips to be developed in this program will incorporate ECM-resistance and HPM protection capabilities. The MMIC functions to be developed for these added capabilities are: advanced modulation and demodulation circuits and self-activated switch/attenuator used as a limiter. The proposed Phase I study will lead to design, simulation, performance analysis, and preliminary layout of the low-cost, low-power MMIC radar chip with added jam/burn-out resistance capabilities.

HNC, INC. 5501 OBERLIN DRIVE SAN DIEGO, CA 92121 Phone: (619) 546-8877

Title: Mobius Compression

Topic#: 92-054 Office: MICOM

Contract #:

PI: Robert Hecht-Nielsen

Abstract: In 1827 mathematician August Mobius introduced a predecessor to liner algebra which he called the barycentric calculus. In Mobius scheme, an arbitrary vector x in n-dimensional Euclidean space is expressed as the center of mass (or barycenter) of N point masses located at positions w1, w2,...,wN, and having masses m1, m2,...,mN, respectively (i.e., x = summation of (mk)(wk) from k = 1 to N, where the summation of (mk) = 1 from k = 1 to N. In this project we shall explore the use of an adaptive neural network technique for selecting nearly orthogonal point mass positions embedded within a statistical population of data block vectors to dramatically improve the performance of vector quantization data compression systems for communications. The idea is to transmit not only the nearest matching codebook vector, but a small set of qualified codebook vectors and their corresponding masses. In this way the original data vector can be accurately reconstructed as the barycenter of these masses with much less error and much higher compression than fixed transform (e.g., JPEG), vector quantization, eigenimage, and principal component analysis approaches. A modest computational burden and real-time operation are inherent in the method, unlike fractal compression. The goal of Phase I will be to demonstrate 40:1 compression of video images with an RMS pixel value distortion of less than 10% in the decompressed imagery. In Phase II, the goal will be 100:1 compression

with an RMS error level below 5%.

HORIZONS TECHNOLOGY, INC. 3990 RUFFIN ROAD

SAN DIEGO, CA 92123 Phone: (619) 292-8331

Title: Electronic Map Display and Route Planner (EMD/RP)

Topic#: 92-087 Office: TACOM Contract #:

PI: James N. Treadwell

ID#: 92TAC-115

ID#: 92SDC-030

ID#: 92MED-022

Abstract: Several of today's emerging and developed technologies lend themselves to an innovative engineering solution to the challenges of battlefield situational awareness, automated route planning, navigation, and coordination for combat vehicles on the modern battlefield. HTI proposes to integrate these technologies in the development of an Electronic Map Display and Route Planner (EMD/RP). The Phase I effort will focus on the various individual technologies as well as their integration for a fully functional EMD/RP application. The specific technologies include: Geographic Information System (GIS) software; GIS databases; flat-panel displays; autorouting algorithms; Global Positioning System (GPS); and tactical communication systems, such as the Position Locating and Reporting System (PLARS). Each of these critical technologies represents a facet of a production EMD/RP. The intent is to pursue an integrated system architecture taking advantage to the greatest extent possible of existing technologies tailored for the EMD/PR application.

HUNTINGTON RESEARCH AND ENGINEERING

P.O. BOX 90118 SAN JOSE, CA 95109 Phone: (408) 293-9425

Files Machete Vill Device for Vinetic Energy ASAT Weens

Title: Machete Kill Device for Kinetic Energy ASAT Weapon System

Topic#: 92-172 Office: SDC Contract #:

PI: John H. Huntington

Abstract: Intelligent Reasoning Systems (IRS) is developing an integrated active vision system (AVS) based on design principles derived from experimental analysis of mammalian visual systems. The AVS design is based on a asynchronous analog encoding of location and motion data, and a custom VLSI Hybrid Temporal Processing Element (HTPE) developed by and available solely to IRS (patent pending). The HTPE can operate on analog data at frequencies in excess of 100 MHz, allowing rapid oversampling methods to be used for resolution enhancement, motion detection, and multiple-template matching. HTPEs have low device count and power dissipation, and can be fabricated in small layout areas. The AVS is intended for eventual on-board application in robots, intelligent machine tools, and other autonomous sensory-motor systems that require visible. IR, or similar input. The initial step in visual processing is the collection of data from the primary sensor. The goal of this Phase I proposal is to evaluate the feasibility of a silicon retina for the AVS based on the HTPE, and to investigate various methods for achieving sub-pixel resolution and enhanced motion sensitivity with such a retina...

HYGEIA PHARMACEUTICALS, INC. 6555 NANCY RIDGE DR., #300 SAN DIEGO, CA 92121

Phone: (619) 453-9393

Title: Neutralizing Monoclonal Antibodies Against Biological Toxins

Topic#: 92-162 Office: MEDICAL

Contract #:

PI: Mark C. Glassy, Ph.D.

Abstract: No specific treatment regime exists for a large number of biological toxins. These toxins pose a threat in a military context and also constitute a public health hazard, mainly when accidentally ingested. An important class of biological toxins are those which inhibit protein synthesis, found in plants as well as bacteria. Many of these share structural and mechanistic properties. They are proteins, often of about 60,000 MW, with two subunits, one responsible for binding to cells, the other for the toxic action. The most common targets of these toxins are in ribosome and the most toxic of the substances kill at one molecule per cell. Hygeia Pharmaceuticals develops human monoclonal antibodies for use as therapeutic agents. For this study, we will use ricin as a model system to demonstrate neutralizing specificity. We will perform an in vitro immunization and then fuse resulting lymphocytes with a proprietary human fusion partner. Resulting hybridomas will be cloned and assayed for antigen recognition and for the neutralization of ricin in model systems.

I-MATH ASSOC., INC. P.O. BOX 560788 ORLANDO, FL 32856 Phone: (407) 857-3213

Topic#: 92-042 Office: CECOM Contract #:

Topic#: 92-065

Topic#: 92-027

Office: BRDEC

Topic#: 92-027

Office: BRDEC

Contract #:

Contract #:

Contract #:

Office: NATICK

PI: Alan J. Zauzmer

ID#: 92NV -009

ID#: 92NAT-002

ID#: 92BRD-083

ID#: 92BRD-084

PI: Alexander Akerman III

Title: FLIR & MMW Algorithms to Detect and Classify Stationary Targets

Abstract: Six multisensor (FLIR/MMW) data bases will be accessed to include all those at CNVEOD including the VISION 1 and subsequent field tests, particularly those involving the RIMS and BWI MMW radars, along with the IIDAS and SAIRS FLIRS. Data from other government agencies will include that in TABILS and at HDL, MICOM, and AATD. A Phase II plan will be produced for training and testing three ATR algorithms not heretofore considered for tank-mounted applications but proven in related contexts: 1. An adaptive Bayesian statistical classifier, which in its operational implementation would be continually retrained upon the actual ground clutter within which the tank is operating, 2. A "genetic" algorithm, which uses the same feature sets as #1, but evolves a different polynomial discriminant function. Both the "genetic" and "adaptive" classifier algorithms are under development for the LONGBOW MMW radar by Systems Dynamics, who would be subcontracted to I-MATH for this SBIR. 3. Geometric hashing algorithms, which I-MATH has recently developed using a CNVEOD-provided FLIR imagery under a Phase II Air Force SBIR. Such algorithms provide a robust mechanism for multisensor fusion as well, since each feature is indexed by its geometric position. This greatly facilitates the incorporation of MMW range (z) profiles as a third coordinate to FLIR (x,y) has points.

INDUSTRIAL EVOLUTION

P.O. BOX 2570 KENNEBUNKPORT, ME 04046

Phone: (207) 967-8807

Title: Individual Combat Soldier Identification Technology

Abstract: The proposal offers a technology/concept to allow individual combat soldiers and components of the Electronic

Battlefield System a means of identifying friendly forces.

INDUSTRIAL HONEYCOMB STRUCTURES, INC.

3200 W. 71ST AVE., #14 WESTMINSTER, CO 80030

Phone: (303) 722-8258

PI: Jerry D. Plunkett, Ph.D. Title: A hybrid (fiberglass reinforced-polymer and paper) honeycomb panel concept for an OHC-IFP

Abstract: As a candidate OHC-IFP panel concept, Industrial Honeycomb Structures, Inc. proposes an innovative hybrid composite material composed of an impregnated paper honeycomb core material sandwiched between two fiber-reinforced-polymer skins. These materials are light weight, high strength, tough, resilient, and highly producible, but need to be qualified for bailistic protection. The impregnated paper cores appear promising as a means for limiting localized damage by ballistic impact. We propose to design, test, adjust the design, and further test 20 panels, by subjecting them to impacts at short-range, normal incidence of 7.62 mm ball ammunition. The front and back skins of the sandwich construction will be comprised of fiberglass- and/or Kevlar-reinforced woven fiber mats embedded in polymer. Based on initial testing results, the relative amounts of these reinforcements will be adjusted, and 20 panels will be designed and delivered as prototypes for further testing.

INDUSTRIAL HONEYCOMB STRUCTURES. INC.

3200 W. 71ST AVE., #14 WESTMINSTER, CO 80030

Phone: (303) 722-8258

PI: Jerry D. Plunkett, PhD

Title: A tiberglass/Kevlar-reinforced-polymer honeycomb panel concept for an OHC-IFP.

Abstract: As a candidate OHC-IFP panel concept, Industrial Honeycomb Structures, Inc. proposes an innovative fiber-reinforced-polymer honeycomb core material sandwiched between two fiber-reinforced-polymer skins. These materials are light weight, high strength, tough, resilient, and highly producible, but need to be qualified for ballistic protection. The honeycomb cores appear promising as a means for limiting localized damage by ballistic impact, we propose to design, test,

adjust the design, and further test 20 panels, by subjecting them to impacts at short-range, normal incidence of 7.62 mm ball ammunition. The front and back skins of the sandwich construction will be comprised of fiberglass- and/or Kevlar-reinforced woven fiber mats.embedded in polymer. Based on initial testing results, the relative amounts of these reinforcements will be adjusted, and 20 panels will be designed and delivered as prototypes for further testing.

Topic#: 92-095

Topic#: 92-143

Office: CERL

Topic#: 92-100

Office: ARO

Contract #:

Contract #:

Office: TECOM

ID#: 92TEC-026

ID#: 92CER-025

ID#: 92ARO-023

INDUSTRIAL QUALITY, INC. 19634 CLUB HOUSE ROAD GAITHERSBURG, MD 20879

GAITHERSBURG, MD 20879

Phone: (301) 948-2460

Title: High Energy X-Ray Stereo-Radioscopic System

Contract #:
Pl: Harold Berger

Abstract: The proposed Phase I program will result in a demonstration of three-dimensional imaging with images taken with the existing high energy x-ray inspection systems at the U.S. Army Yuma Proving Ground. These images will be processed so they can be presented as prompt-response stereo television images. In addition, the capability to measure defect dimensions using a cursor-prompted software program will be evaluated. The modifications that will be needed to make the Yuma x-ray inspection system into one with stereo/three dimensional capability will be determined so that those modifications can proceed in a Phase II program. This realistic program is proposed by a small, high technology company with broad experience in x-ray imaging and with specific prior experience with a stereo, real-time microradiographic imaging system. Differences described here include high energy x-ray inspection, additional image processing to reduce image unsharpness, probable object rotation instead of electronic source movement to generate stereo views, near real-time imaging capability and system modification instead of a complete stereo system.

INNOVATIVE DYNAMICS, INC.

CORNELL RESEARCH PARK,, LANGMUIR LABS, 95 BROWN RD ITHACA, NY 14850

Phone: (607) 257-0533 PI: Bruce W. McKee

Title: Automated In-Situ Inspection System for Underground Fuel Storage Tanks

Abstract: Currently, no commercial robotic inspection system can operate in a petrochemical bath and perform the precise, repeatable measurements required for tank inspection. Innovative Dynamics proposes to address this problem by determining the sensor requirements for robotic tank inspection. An integrated sensor module will be developed containing an ultrasonic wall thickness gage, a video inspection sensor, and a capacitance-based corrosion/crack sensor, the latter adapted from previous NDE sensor work at IDI. The combined sensor measurements will maximize the probability of detecting tank wall and tank liner defects. An evaluation of systems for registering measurements on the tank wall will be performed to enable precise and repeatable measurements. Automated fault diagnosis will be provided using a neural-network-based expert system. Lab tests on submerged tank wall specimens will be performed to evaluate the sensor module performance. Based on these sensor studies, deployment requirements will be defined during Phase II for the design and fabrication of an operational robotic inspection system. Cost effective solutions will be sought. Custom or modified commercially available robot types (such as the underwater remotely operated vehicles or magnetically-attached surface crawler will be evaluated which will fulfill these requirements.

INRAD, INC. 181 LEGRAND AVE NORTHVALE, NJ 07647

Phone: (201) 767-1910 PI: Dr. Zhenyu Zhang

Title: Low Temperature Templated Synthesis of Fullerenes

Abstract: Fullerenes form a series of new allotropes of carbon that have a myriad of unusual properties. Fullerene research has seen explosive growth since 1990 when C60 was isolated from carbon soot. However, the prohibitively high price of pure C60 (\$2000/g) is a major obstacle to fullerene research and certainly for commercial applications. These high costs are due to the low yields obtained using current technology. We propose to develop superior methods for synthesizing and purifying fullerenes with the goal of dramatically reducing the cost for pure fullerenes. We will control fullerene growth to achieve high yields of small and midsized, solvent-extractable fullerenes by minimizing the formation of soot, giant fullerenes, and buckytubes. In addition to eliminating the formation of undesirable side products, we expect to carry out the conversions at significantly lower

temperatures and to direct the formation of other fullerene materials, which are not currently available commercially. The efficient synthesis, isolation, and purification of fullerenes would greatly reduce production costs, thereby further stimulating fullerene research and helping to make potential commercial applications for fullerenes a reality.

INTELLIGENT AUTOMATION, INC. 1370 PICCARD DRIVE, SUITE 210

ROCKVILLE, MD 20850 Phone: (301) 990-2407

Title: Intrusion Detection Using Fast 3D Imaging

Topic#: 92-026

ID#: 92BRD-101

Office: BRDEC Contract #:

PI: Leonard S. Haynes

Abstract: The problem described in the RFP is to build a system which will be able to detect intrusion from a moving platform. The solution herein proposed is based on a new type of camera designed by Intelligent Automation, Incorporated. This new type of camera produces a three dimensional image of the scene at normal video frame rates of 60 frames per second. Our Fast 3D Imaging camera will generate 3 dimensional images in real time. By "3 Dimensional Image" we mean that the value of each pixel in the image will represent the distance from the camera's focal point to the corresponding point in the scene. We call this type of image a range image. Our intrusion detection approach uses the range camera for what is basically visual inspection. A conventional videotape would be made of the vehicle's patrol path where the videotape would be recording the range image from the range camera (not a normal intensity image). This can be thought of as the "teach mode," where both the path and the expected range recording is captured at normal frame rates. Then as the vehicle moves through its normal patrol path, it continually compares its real-time range image with the pre-recorded "normal" range image. Minor differences are used to control the vehicle along the pre-defined path. Significant deviations must be caused by unexpected changes in the area and would raise ail alarm. The same range camera Output can also be used for obstacle avoidance. Our Fast 3D Imaging camera can also capture normal intensity images by switching the state of a single control bit. The range image and the intensity image can therefore be used without requiring an additional camera.

INTELLIGENT REASONING SYSTEMS

647 CREED AVE LAS CRUCES, NM 88005

Phone: (505) 527-1317

Topic#: 92-172

Office: SDC Contract #:

PI: Mark R. DeYoun

Title: Resolution and Motion-Detection Enhancement Using an Oscillating Saccadi Perception System

Abstract: Intelligent Reasoning Systems (IRS) is developing an integrated active vision system (AVS) based on design principles derived from experimental analysis of mammalian visual systems. The AVS design is based on a asynchronous analog encoding of location and motion data, and a custom VLSI Hybrid Temporal Processing Element (HTPE) developed by and available solely to IRS (patent pending). The HPTE can operate on analog data at frequencies in excess of 100 MHz, allowing rapid oversampling methods to be used for resolution enhancement, motion detection, and multiple-template matching. HTPEs have low device count and power dissipation, and can be fabricated in small layout areas. The AVS is intended for eventual on-board application in robots, intelligent machine tools, and other autonomous sensory-motor systems that require visible, IR, or similar input. The initial step in visual processing is the collection of data from the primary sensor. The goal of this Phase I proposal is to evaluate the feasibility of a silicon retina for the AVS based on the HTPE, and to investigate various methods for achieving sub-pixel resolution and enhance motion sensitivity with such a retina.

INTERFACE TECHNOLOGIES **4251 SEA PINES COURT** CAPITOLA, CA 95010

Phone: (408) 475-8143

Topic#: 92-098

ID#: 92STR-015

ID#: 92SDC-036

Office: STRICOM Contract #:

PI: Kenneth Nemire, Ph.D. Title: An Immersive Virtual Prototyping Environment for the Design of Advanced Weapons System in the Battlefield Distributed

Simulation Environment

Abstract: Design of advanced weapons in the Battlefield Distributed Simulation environment requires construction and evaluation of physical prototypes before final production of the system. Faster, more efficient means of iterative construction and modification of weapon system prototypes may be accomplished in virtual, rather than physical environments. The current virtual prototyping technology may be improved by constructing an immersive virtual environment (VE) in which the designer

sees the visual and spatial characteristics of the system in a head-coupled display and interacts with the environment with instrumented gloves allows natural manipulations and gestures, and providing tactile and force stimulation representing interactions with the VE. Addition of a virtual auditory environment may enhance the kinesthetic experience. Current limitations of the hardware used in VE systems may adversely influence prototyping performance. We will conduct design task analyses and interactive experimentation to determine which combination of VE system components will provide the best VE for the designer. The research is also important for determining the fidelity of the VE system necessary for optimal performance. The research and development team has extensive experience in creating rapid prototyping tools, designing and developing virtual environments and crewstations, and conducting experimental and human factors research; it should prove to be a productive team.

INTERSCIENCE, INC. 105 JORDAN RD TROY, NY 12180

Phone: (518) 283-7500

Topic#: 92-129 Office: HDL Contract #:

PI: Eduardo Saravia

ID#: 92HDL-090

ID#: 92MIC-048

ID#: 92CRD-001

Topic#: 92-054

Office: MICOM Contract #:

PI: Alan Sloan

Title: High Sensitivity Wideband Analog Fiber-Optic Link Based on Integrated Optical Modulator

Abstract: The development of an analog optical link capable of transmitting measured currents and voltages from anechoic chambers to remote control and data acquisition systems is proposed. The system is based on integrated optical modulator (IOM) coupled to a cw 1.3 mm diode laser and to a high frequency PIN diode photodetector. The main advantage of the external modulation of a laser light, is that modulating frequencies as high as 15 GHz can be very attractive for the proposed application. Recent advances in the fabrication of these modulators, based on an Annealed Proton Exchange process, have produced IOMs that are extremely stable for high optical power of a few hundred of milliwatts. A prototype unit will be developed and fully tested under the Phase I effort to demonstrate the functional capabilities of the proposed concept.

ITERATED SYSTEMS, INC. 5550 PEACHTREE PARKWAY NORCROSS, GA 30092 Phone: (404) 840-0728

Title: Real Time Fractal Image Compression Techniques

Abstract: The objective of this proposal is to demonstrate the feasibility of a new na resolution independent digital image compression technology in the area of real time compression for imagery including types generated by electro-optical, imaging infrared and millimeter wave sensors. The technology is based on Fractal Transform technology. Digital imagery is generated at a high rate and needs to be distributed over communication links of varying bandwidth. The nature of video is evolving as sensors, training systems and displays require ever higher resolutions. High compression rates and resolution independence are needed to accommodate the varying bandwidths and evolving requirements. Image data representative of the products of Army sensors will be identified and obtained. This data will be digitized and then processed using Fractal Transform technology to obtain a compressed representation of the Army sensor imagery. A real-time test of expansion and display of imagery representative of that produced from Army type sensors will be conducted. The final report will describe the results of this test. Configurations to achieve real time compression will be evaluated and described in the final report.

J.K. RESEARCH 210 SOUTH WALLACE BOZEMAN, MT 59715

Phone: (406) 586-8744

Title: Heat Stable Alkaline Phosphatase from Thermophiles

Topic#: 92-046 Office: CRDEC

Contract #:

PI: Dr. Joan Combie

Abstract: Enzymes used as the label for most non-radioactive assays and in biosensors, are the most unstable component of these systems. As immunoassays and biosensors move from the tightly controlled laboratory environment to demanding field conditions, the need for a more stable enzyme becomes critical. Alkaline phosphatase is the most widely used enzyme for these types of applications. A heat stable enzyme would not only allow use over a range of temperatures but would also increase the shelf life of these detection systems. Alkaline phosphatase is currently obtained from mammalian sources and is not stable at elevated temperatures. Thermophilic microorganisms producing heat stable alkaline phosphatase have been isolated by J. K.

Research. The objective of this proposed research is to select a thermophile producing heat stable alkaline phosphatase and characterize the enzyme. Media will be developed to enhance enzyme production. A purification scheme will be optimized for maximum recovery of purified alkaline phosphatase. Sufficient heat stable enzyme will be produced to determine kinetic parameters and the most suitable reaction conditions.

KARS' ADVANCED MATERIALS, INC. 7271 GARDEN GROVE BLVD, SUITES C & D GARDEN GROVE, CA 92641

Phone: (714) 892-8987

Title: Failure Mechanisms in Armor Composites With Ballistic Damage

Topic#: 92-106 Office: BRL

Contract #:

PI: Dr. Ramesh J. Kar

Abstract: The overall objective is to develop a database of failure mechanisms and fracture properties in armor composites of interest to the Army. A building-block approach toward achieving this is suggested. The Phase I proposes investigating composites such as S2 glass/polyester and fiberglass/phenolic that has been subjected to ballistic damage. Phase I will choose three candidate composite systems for study, categorize required ballistic properties, and obtain panels for the test. The ballistic damage will be characterized using ultrasonic tests (through transmission and pulse-echo imaging). The panels will be ballistic tested as per MIL-STD-662. Fractures due to the ballistic damage will be characterized using scanning electron microscope (SEM) techniques. Correlations will be made between the fracture behavior, ballistic loads and material type. Phase II will propose expansion of the ballistic damage studies to include "real-world" variables including battlefield repair, fire and laser beam damage.

KARTA TECHNOLOGY, INC. 1892 GRANDSTAND SAN ANTONIO, TX 78238

Phone: (512) 681-9102

Topic#: 92-133 Office: MTL ID#: 92MTL-183

ID#: 92AVS-139

ID#: 92BRL-010

Contract #:

PI: Dr. Satish M. Nair

Title: A CAD-NDE Translator (CADNET) for the Ultrasonic Inspection of Contoured Ceramic Gas Turbine Components Abstract: The automated inspection of gas turbine components has proven to be difficult due to their complex geometry. While ultrasonics has demonstrated excellent capabilities in detecting and characterizing the erosion and corrosion on turbine components from the hot effluent gases, it's application details laborious alignment procedures for the ultrasonic transducer during inspection. The need for automated inspection systems has become more pressing with the proposed next-generation gas turbine where ceramic materials are being considered for their high temperature capability and reduced cooling requirements. Critical flaw sizes for ceramics are smaller than those for metals and the ceramics fail catastrophically due to their brittle nature. A novel method for conducting the automated ultrasonic inspection of ceramic turbine blades and other complex-geometry gas turbine components is proposed. The innovation of this method lies in the development of a software package, called the CAD-Nde Translator (CADNET), which generates motion control commands from the CAD drawings of a complex geometry part. The motion control commands are used to instruct an inspection robot to closely follow the contour of the part. In Phase I, we will develop this translator. In Phase II, we will integrate this translator into a high-frequency ultrasonic system and evaluate it by conducting the automated inspection of ceramic turbine blades.

KNOWLEDGE INDUSTRIES 125 CALIFORNIA AVENUE, SUITE 201 PALO ALTO, CA 94306

Phone: (415) 321-9521

Title: Probabilistic Expert Systems for Gas Turbine Diagnostics

Topic#: 92-022 Office: AVSCOM

Contract #:

PI: John S. Breese

Abstract: Knowledge Industries (KI) will explore the technical feasibility of applying probabilistic expert systems to development of T800 gas turbine diagnostics. KI is a leading developer of probabilistic expert systems and has developed other gas turbine diagnostic systems. In this project, KI will develop a prototype probabilistic expert system for the T800, investigate use of thermodynamic modeling as a component of a diagnostic system, and develop a software architecture and development plan for fielding a Phase II developed expert system. The basis of a probabilistic expert system is a probabilistic model of the faults and observables for a given diagnostic problem. We will use probabilistic causal networks called belief networks to model the relationships among important variables for the T800 gas turbine. Belief networks are a flexible and maintainable methodology

for construction of large diagnostic systems. KI has developed state-of-the-art software tools and techniques for constructing and evaluating belief networks and we will evaluate the feasibility of probabilistic modeling of the T800 by constructing a prototype belief network and expert system, including a thermodynamic analysis of the engine. A major component of the program will focus on development of a software development and delivery plan for shop-based, line-based, and on-board diagnostics.

KNOWLEDGE SCIENCES, INC. 510 HIGHLANDS OVERLOOK

ROSWELL, GA 30075 Phone: (404) 641-0988

Title: Expert Diagnostics for Gas Turbine Engines

Topic#: 92-022 ID#: 92AVS-136

Office: AVSCOM Contract #:

PI: Brian D. Leighty

Abstract: A modern gas turbine engine such as the T800-LHT-800, which is to be used in the Army's Light Helicopter Experimental (LHX) Helicopter (now referred to as the RAH-66 Comanche), is among the most complex mechanical systems in use today. The parameters involved in diagnosing a fault are numerous and often subtly interrelated. The objective of Phase I is to define a system architecture for a diagnostic expert system that will aid engine maintenance personnel in locating engine faults. Phase I activities define the architecture for such a diagnostic expert system and demonstrate its feasibility and adequacy using a computer based simulation. A complete set of hardware and software components will be defined for subsequent detailed design and construction in Phase II. An approach using a diagnostic knowledge base consisting of both experiential knowledge (symptom-fault relationships) and functional engine knowledge (model based) will be investigated. The diagnostic reasoning process knowledge (meta-knowledge) will be defined that governs how the knowledge in the diagnostic knowledge base is to be used. The requirements for the inferencing mechanism used in processing all knowledge base data structures will be identified. Host computer component requirements will be identified including all system interface modules.

KTECH CORP.
901 PENNSYLVANIA AVE. NE
ALBUQUERQUE, AL 87110

Phone: (505) 268-3379

Title: EM Enhanced KE Projectile

Topic#: 92-173
Office: SDC
Contract #

PI: Frank W. Davies

Abstract: A feasibility study of an EM enhanced kinetic energy penetrator (EME penetrator) for ASAT application is proposed that negates the satellite's functional capabilities while minimizing space debris. The projectile is designed to penetrate the satellite and then generate a high amplitude EMP. Energizing the pulser after penetration minimizes the effectiveness of the satellite EM shielding and penetration minimizes the effectiveness of the satellite's EM Shielding and closely couples the EMP signal to the targets electronic systems. This permits the modest electrical energies that can be stored in the projectile to be lethal. Since the Kill Mechanism is EM rather than KE debris production can be minimized. Confirmation that a satellite has been intercepted can be detected by monitoring. The study will determine the feasibility of the concept, define the critical characteristics of each functional element, identify the risks associated with the development of the concept, and plan for the mitigation of those risks. Each of the critical technologies has been demonstrated. The challenge therefore is to synthesize a militarily useful system.

KVH INDUSTRIES, INC. 110 ENTERPRISE CENTER MIDDLETOWN, RI 02840

Phone: (401) 847-3327

Title: Acoustic Buoy Release for Locating Underwater Instruments

Topic#: 92-152 ID#: 92WES-026 Office: WES

ID#: 92SDC-043

Contract #: DACA39-92-C0141 PI: A. Kits van Heyningen

Abstract: KVH Industries proposes to design and demonstrate a low cost short range acoustic buoy release system designed to locate and retrieve underwater instruments. The proposed design effort will address the problems of search rate, identification, homing, slant range measurement, localization and buoy acknowledgement. The focus of the Phase I effort will be optimization of correct response to address and command while minimizing the probability of a false trigger. The Phase I development model will consist of a waterproof, single channel, control deck unit with a sealed steering and range display and a sea floor unit. The latter unit will operate in a dual mode; a sleep mode where the unit is waiting to be called and an operational mode following

awakening. This prototype effort will demonstrate the feasibility of an acoustic buoy release system for shallow water operation.

LB&M ASSOC., INC.

Phone: (405) 355-1471

Topic#: 92-177

ID#: 92TRA-001

211 A AVE

Office: TRADOC LAWTON, OK 73501

Contract #: DABT60-93-C-0004

PI: John C. Haley

Title: Concept-Based Requirements Decision Support System (CBRDSS)

Abstract: The purpose of this project is to develop an Artificial Intelligence (AI)-based Decision Support System (DSS) to support the preparation of the Program Objective Memorandum (POM) by TRADOC and other MACOMS. Phase I includes the development of an operational prototype which proves the worth of the system. Phase II will produce a fully operational system that can be used by action officers and decision makers in preparing the POM input. The key feature of the CBRDSS is the ability to generate an optimal mix of doctrine, training, force structure, leadership, and materiel requirements to meet the challenge of future combat. This is accomplished within the constraints imposed by DoD, the Administration, Congress, and international treaties. The approach links the DTOLMS solutions to the assigned missions, making them more sensitive to the changing threat and less sensitive to parochial interests. The methodology facilitates rapid analysis of trade-off decisions when funding levels of other external influences mandate change. The methodology will establish a set of DTOLMS projects for the resolution of each mission deficiency, and having determined the degree of membership of each project in the solution set for each deficiency will use fuzzy set theory to derive an overall contribution of each project to the total Army mission. Since all Army missions cannot be completely or simultaneously maximized with the available funds, weighted goal programming will be used.

LEEP SYSTEMS, INC. 241 CRESCENT STREET WALTHAM, MA 02154 Phone: (617) 647-1395

Topic#: 92-011 Office: AVSCOM ID#: 92AVS-049

Contract #: PI: Eric Howlett

Title: A Head-Coupled Visual and Aural Sensor System for Teleoperated Rotorcraft Research Vehicle

Abstract: The objective of the Phase I program is a design of a stereoscopic and binaural telepresence system for remote piloting of the FFRRV helicopter. The system must afford the pilot on the ground a sense of "presence" in the cockpit - both visually and aurally - complete enough to permit aggressive and precise maneuvers. LEEP Systems will design a system based on its present technology, having a very wide angle of view for fast and accurate orientation in space as well as high resolution inserts for sharp views of distant features of the terrain. By this means the benefits of high resolution and wide angle can be simultaneously realized by just doubling the video bandwidth and of the electronic hardware, whereas without the inserts, getting vision substantially better than legal blindness requires unavailable components and a one hundred-fold increase in video bandwidth, which is not feasible. Along with AACOM Data Links, major consultants for telemetry equipment, LEEP brings to this task a unique breadth of experience and depth of skill, which is quite adequate to the task, as demonstrated repeatedly by innovations and by directly related products brought successfully to market. The anticipated work load will be readily accommodated.

LYNNTECH, INC. 111 EAST 27TH STREET, SUITE 204 Topic#: 92-151

ID#: 92WES-017

BRYAN, TX 77803 Phone: (409) 822-3149 Office: WES

Contract #: DACA39-92-C0183

PI: Dalibor Hodko

Title: Pulsed EC Electric Fields for Heavy Metal Decontamination of Soil

Abstract: The removal of heavy metals and/or radionuclides from contaminated subsurface soils and groundwaters is an expensive and time-consuming part of any contaminated site-cleanup process. Development of new techniques for soil remediation is particularly needed for contaminated sites on which nuclear facilities are located. Many remediation methods investigated have been found to be less than satisfactory due to a combination of their short- and/or long-term ineffectiveness, low removal rates of toxic elemental species and high implementation costs. Decontamination of soil using pulsed DC electric fields is a new novel approach for hazardous waste site remediation based on electrochemically induced transport of contaminants through the soil. This technique has the potential to be effective in facilitating the removal of certain types of hazardous wastes

from soils, particularly heavy metals. The objective of this proposal is to evaluate the feasibility of electrochemically based remediation technology for removal of heavy metal contaminants from soil and to implement an innovative approach based on the application of pulsed DC electric fields, in combination with periodic pumping. It is anticipated that increasing the turbulence in the soil/contaminant/water system, both by application of an "electrochemical stirring" of the soil and by forced hydraulic flow, will increase the rate of removal of contaminants. Different long-term pulsing-type regimes, including increasing voltage amplitudes and voltage reversals, combined with intermittent pumping, will be investigated in order to enhance the effectiveness of the electrochemically based remediation process.

ID#: 92MIC-047

M-DOT, INC. Topic#: 92-052

3416 SOUTH 48TH STREET, SUITE 2

PHOENIX, AZ 85040

Phone: (602) 921-4128

Office: MICOM
Contract #:
PI: Bryan J. Seegers

Title: Design, Fabrication and Test of a Thrust Spoiler/Reverser System for a Low Cost, Expendable Turbojet

Abstract: M-Dot, Inc. ("M-DOT") proposes to design, fabricate and test a thrust reverser system for low cost expendable turbojet engines. The system will be designed for application on the Sunstrand TJ-90 engine and will be configured for application on a bifurcated exhaust duct. The system will consist of the following: 1. Custom fabricated bifurcated exhaust duct for the TJ-90 engine. 2. Two pivoting vectoring ducts. One located at each exist. 3. Linkage and actuator for positioning the vectoring ducts. The Phase I program would accomplish the following: 1. Design and construction of a heavy wall thrust reversing system for ground test. 2. Bench testing to verify functionality of system. 3. Engine testing to verify performance and durability. 4. Compilation of design and test data. 5. Design layout of a flight weight system.

M.L. ENERGIA, INC. Topic#: 92-061 ID#: 92MIC-049

P.O. BOX 1468 Office: MICOM PRINCETON, NJ 08542 Contract #:

Phone: (609) 799-7970 PI: Dr. Moshe Lavid

Title: Fluctuating Flowfield Density Measurement Over Wide Mach Number Range

Abstract: The Army has identified a need for fluctuating flowfield density measurements over a wide range of velocities. We propose to employ a new non-intrusive optical diagnostic technique which is applicable over a Mach number range from subsonic to hypersonic. The method is based on specially filtered rotational Raman scattering and uses a newly developed ultraviolet solid state laser system, in conjunction with an atomic mercury vapor filter at 254.7 nm. The filter is used yo block elastic and Rayleigh scattering, and transmit rotational Raman scattering. The use of an ultraviolet laser, and atomic vapor filter (as opposed to conventional spectrometer), results in significantly greater sensitivity than that of traditional vibrational Raman scattering. Modeling calculations indicate a potential density accuracy of +/- 1% at mean densities as low as 0.002 amagat. In this effort we propose a detailed study, including laboratory proof-of-concept measurements. An isotopically pure Hg vapor filter will be constructed, and its absorption characteristics determined. The study will employ a new, state-of-the-art, injection-seeded, frequency tripled, pulsed titanium-sapphire laser system. Extension to flow velocity and temperature measurement will also be explored.

MAINSTREAM ENGINEERING CORP.

Topic#: 92-074

ID#: 92NAT-129

PINES INDUSTRIAL CENTER, 200 YELLOW PLACE

Office: NATICK

ROCKLEDGE, FL 32955 Contract #:
Phone: (407) 631-3550 PI: R.P. Scaringe

Title: Demonstration of the use of Hydrogen Fuel for Food Service

Abstract: Mainstream has a long and successful history of developing useful, easy-to-use hardware for heat and cooling applications [3-37]. This Phase I effort will investigate and demonstrate the use of hydrogen-powered food service system. Phase I will systematically investigate and define the best approach to integrate hydrogen fuel into food service operations. Included will be a study to determine optimum storage, transmission, and utilization methods. Based on the results of this study a conceptual model of a complete hydrogen-powered food service facility will be developed to demonstrate benefits and characterize the salient technical features (weight, cube, fuel usage and storage capacity, output). Phase I will also investigate the basic operating conditions required by the Army and design and demonstrate a working proof-of-principal prototype (to allow

Army engineers to completely evaluate the concept's feasibility). Phase II will result in a development of fieldable-hardware for demonstration and evaluation in the field.

MAK TECHNOLOGIES, INC.

386 GREEN STREET CAMBRIDGE, MA 02139

Phone: (617) 876-8085

Title: Distributed Interactive Virtual Reality to Support Weapons Systems Concept Evaluations

Abstract: Evaluation of hypothetical weapons systems is costly in a BDS environment for two reasons. First, construction and modification of man-machine interfaces is costly and time-consuming. Secondly, construction and modification of network interfaces is costly and time-consuming, and often entails changes to older, pre-existing BDS software. Mak proposes to develop a Distributed Virtual Reality: an innovative, two-pronged approach to applying Virtual Reality to hypothetical weapons system concept evaluations. First, VR man-machine interface (MMI) technology will be evaluated for application to reconfigurable man-machine interfaces. Second, dynamic adaptive VR network protocols will be designed for application to reconfigurable inter-simulator interfaces. Based on extensive SIMNET simulator-construction experience and on on-going research. MaK proposes trade studies to determine the suitability of current and planned VR MMI offerings for simulator MMIs, based on extensive experience with SIMNET network protocols, and on prior experience designing DIS protocol extensions. Mak will design dynamic, adaptive VR extensions to DIS 1.0 for inter-simulator interfaces.

MANAGEMENT RESEARCH INSTITUTE

6701 DEMOCRACY BOULEVARD, SUITE 300 BETHESDA, MD 20817

Phone: (703) 993-1344

PI: Michael D. Mumford, Ph.D. Title: Cognitive and Metacognitive Skill Development: Alternative Measures for Predicting Leadership Potential

Abstract: Leaders must be able to solve the kind of complex, ambiguous problems that arise in organizational settings. Prior research on the determinants of leader performance indicates that metacognitive skills, such as problem construction and integration, have a marked impact on people's ability to solve complex, ambiguous problems. In the effort proposed herein, the literature on cognitive processes and cognitive development in adulthood will be used to construct a model describing how metacognitive skills influence (1) the development of viable knowledge structures and (2) effective processing of knowledge in problem solving. This model will then be used to identify potential measures of each of these metacognitive skills, and automated measures of certain crucial skills will be developed. The reliability and validity of these measures will then be established in a pilot study. Additionally, this model will be used to identify interventions that might accelerate skills development. A set of self-paced, computer-interactive training programs will then be constructed, and their influence on effective application of metacognitive skills in problem solving will be assessed. The validation evidence provided by these studies should provide the infrastructure for future efforts intended to enhance leaders' problem solving skills.

MATERIALS & ELECTROCHEMICAL RESEARCH

7960 S. KOLB RD TUCSON, AZ 85706 Phone: (602) 574-1980

Office: ARO

Contract #:

Topic#: 92-102

Topic#: 92-098

Contract #:

Office: STRICOM

PI: John Morrison

Topic#: 92-154

Office: ARI

Contract #:

ID#: 92STR-016

ID#: 92ARI-011

ID#: 92ARO-039

PI: Dr. R.O. Loutfy

Title: Novel Materials for Hydrogen Supplies and Storage for Fuel Cells

Abstract: A novel and newly discovered C60 carbon material was found to exhibit unique electrochemical and physical properties. C60 and catalyzed C60 electrodes for hydrogen storage and supplies will be fabricated by vapor deposition and dry pressing. These electrodes will be fully characterized as hydrogen electrodes in C60Hx-air fuel cells. The nature of the electrochemical hydrogenation and dehydrogenation of C60 as a function of environmental conditions will be established. A fuel cell will also be characterized including its self-discharge, charge and discharge characteristics and efficiency to establish the viability of this system as a low cost, light weight, high power density secondary battery for producing power on the battlefield.

MATERIALS & ELECTROCHEMICAL RESEARCH

7960 S. KOLB RD. TUCSON, AZ 85706 Phone: (602) 574-1980 Topic#: 92-131 Office: MTL ID#: 92MTL-164

ID#: 92SDC-018

ID#: 92MTL-215

Contract #:
PI: Dr. S. Guha

Topic#: 92-171

PI: Dr. T. A. Miller

Office: SDC

Title: Low Cost Method for Synthesis of [100]-W Reinforced Heavy Ailoys for Kinetic Energy Penetrators

Abstract: Single crystals of tungsten (W) with [100] orientation have been demonstrated to exhibit ballistically equivalent performance to depleted uranium (DU) projectiles. Single crystals of W are unfortunately brittle. Also, the state-of-the-art crystal growing techniques limits the diameter of such crystals to less than 10mm. Hence, it is proposed to fabricate tungsten heavy alloy (WHA) projectiles consisting of [100] oriented whiskers/fibers held in a Ni-Fe type matrix. This proposal will address the problems of growing {100] W whiskers/fibers in a heavy alloy matrix. The whiskers/fibers will be grown by the proven VLS process in which MER has considerable expertise (prior experience in growth of SiC and TiB2 whiskers) using a [100] W single crystal substrate, a mixture of WCl6 and H2 as the reactant gases and a Ni-based catalyst (Ni-Fe, Ni-Co, Ni-Cu). The whiskers/fibers will be harvested, cold-pressed and infiltrated in-situ by the catalyst (by varying temperature and atmosphere to promote wetting). This will demonstrate processing that can produce projectiles (>10mm in diameter) for ballistic evaluation. A test scale WHA composite synthesized through the above process will be delivered to the program technical monitor.

MATERIALS & ELECTROCHEMICAL RESEARCH

7960 S. KOLB ROAD TUCSON, AZ 85706

Phone: (602) 574-1980

Title: Use of High Energy Lasers for Materials Synthesis

Abstract: In High Energy Lasers (HEL) a large percentage of the laser energy is wasted typically by switching onto beam dumps. Some of this wasted energy could be utilized to synthesize exotic materials which have useful commercial applications. In order to utilize this wasted energy to synthesize new and exotic materials, specialty chambers and equipment are needed. This program will review previous efforts to create new material using HELs and other laser synthesis, define the possible methodologies to create exotic new material using HELs, design possible experiments and perform preliminary design for experimental chambers and equipment needed to utilize the waste HEL to synthesize, select materials that have commercial markets. An additional variation is to retrofit existing reaction chamber(s) for scouting experiments to demonstrate the viability of using HELs to synthesize exotic materials including fullerenes and collect data for the design of the equipment that will

subsequently be designed and fabricated.

MATERIALS MODIFICATION, INC. 2929-P1 ESKRIDGE CENTER FAIRFAX, VA 22031

Phone: (703) 560-1371

Title: Synthesis of Nanocrystalline Tungsten Powder

Topic#: 92-137

Contract #: DASG60-93-C-0003

Office: MTL
Contract #:

PI: Dr. T. S. Sudarshan

Abstract: Kinetic energy projectiles and shaped charge liners as well as explosively formed projectile warheads would be more effective if tungsten having significant room temperature ductility were available. Nano-sized particles are known to provide these levels of desired ductility. In this Phase I effort, we propose three different approaches to producing tungsten nano-particles. Each technology is unique and nano-particles will be produced under optimal processing conditions. In Phase II we will concentrate on one of the three approaches, optimize the processing parameters so that mechanical properties evaluation and fabrication of a penetrator shape will be feasible.

MAY Topic#: 92-085 ID#: 92TAC-094

12310 SARAGLEN DR. Office: TACOM SARATOGA, CA 95070 Contract #:

Phone: (408) 252-4462 PI: Dr. Anita Wong

Title: An Embedded Robotic Controller Using a Distributed Processing Concept

Abstract: With the advent of force reduction, the benefits of robotic systems in military applications will become more apparent. However, the need for manned systems will still continue. Given that both manned and unmanned systems will be in the future

military inventory, there will be significant benefits to embed robotic automotive control into the design of manned vehicles. Some of the benefits are: * Reduced operation and support costs * Reduced maintenance cost * Flexible force structuring and deployment * Well integrated automotive control system. The current generation of robotic vehicles are usually developed through adaptations or retrofits of manned vehicles. The results are usually sub-optimal and would be problematic if robotic control is to become a significant part of the force structure. In this project, we propose to develop and test a distributed embedded robutic control concept using low cost microcontrollers.

MAYFLOWER COMMUNICATIONS CO., INC.

80 MAIN STREET READING, MA 01867 Phone: (617) 942-2666

PI: Dr. Jorge I. Galdos Title: Improved Real-Time Ionospheric Compensation for Kwajalein Missile Range (KMR) Radars

Abstract: ALTAIR range correction when dual-frequency tracking is unavailable, and ALTAIR elevation corrections with or without dual-frequency tracking depend critically on the accurate characterization of the ionosphere along the ray paths to the trajectory of the traced object. The techniques currently implemented at ALTAIR and other KWR radars do not reflect the advances in ionospheric modeling and sensor technology that have become available during the last ten years. This proposal formulates an innovative advanced development program to upgrade these techniques and maximize radar tracking accuracy. The proposed work will analyze the capabilities of the most advanced low-latitude ionospheric model ---SLIM, FAIM, ICED, and PRISM -- for use in ALTAIR range and elevation corrections. Because significant spatial and temporal fluctuations of the ionosphere cannot be predicted by any model, a concept is developed to update the ionospheric model in real-time using a sensor integration approach which uses the capabilities made available by the Global Positioning Systems (GPS).

MERIX CORP. 77 CHARLES STREET NEEDHAM HEIGHTS, MA 02194

Phone: (617) 455-8877

Title: Improved Pressurized Fabric Arches

Topic#: 92-073 Office: NATICK Contract #:

Topic#: 92-012

Office: AVSCOM

Topic#: 92-175

Office: SDC

Contract #:

ID#: 92SDC-072

ID#: 92NAT-124

ID#: 92AVS-062

PI: Dr. Thomas W. Mix

Abstract: Pressure stabilized arches, consisting of curved fabric tubes with closed ends and a valve for inflation and air retention, show promise as lightweight, quickly-erectable support structures for Army tents. Various methods for producing the pressurized air beams have been explored. The current method of arch fabrication is to cut patterns from flat fabric, and sew or cement seams to form the curved tube and end closure, with air-retention provided by a separate internal bladder or a coating. This method is labor intensive, and the resulting seams provide a large number of potential initiation sites for tube failure. The Army is currently pursuing both 3-D weaving and braiding approaches for producing the curved arches; however, these techniques are still in the developmental stages. Merix proposes to develop an automated method to inexpensively form the arches directly form non-woven fabric, with no seams. The Merix process should be less expensive that 3-D weaving and braiding, and should eliminate the possibility for defects in the 3-D weaving and braiding processes to degrade the arch support capabilities of the structure.

MICRO COMPOSITE MATERIALS CORP. **4608-D INDUSTRY LANE** DURHAM, NC 27713

Contract #: Phone: (919) 361-3535 PI: Dr. Steve R. Wright Title: Novel Inlet Protection System for Auxiliary Power Units using Boundary-Layer Momentum Transfer Technology

Abstract: Ingested particulates, especially sand, severely degrade performance and increase wear in small gas turbine engines used in helicopter auxiliary and secondary power units. Existing Inlet Particle Separator (IPS) systems based on Bortex tube designs have two major limitations: their efficiency decreases with the size of particulate matter, and they are difficult and expensive to retrofit in existing APU/SPUs. The objectives of this project are to develop and assess a novel IPS system based on a boundary-layer momentum transfer concept that will greatly improve the efficiency of particle removal while operating within the performance and spatial parameters of existing APU/SPus. Prior research has shown this technique to be very efficient at removing particulates from unconstrained gaseous streams. The thrust of Phase I research is to use computer simulation

modelling to analyze the trade-offs between particle removal efficiency, pressure loss, airflow, size and weight of an IPS that can be adapted to existing APU/SPUs. The resulting criteria will be used to evaluate production/retrofit costs and to create a preliminary IPS design emphasizing the highest efficiency for the lowest cost and size. Subsequent development, fabrication and testing of a prototype in Phase II will confirm the efficiency and airworthiness of the novel IPS.

Topic#: 92-113

Topic#: 92-056

Office: MICOM

Topic#: 92-039

PI: Ellen L. Moore

Contract #:

Office: ETDL

Contract #:

ID#: 92ETD-004

ID#: 92MIC-033

ID#: 92SW -004

MICROSYSTEMS ENGINEERING, INC.

300 31ST ST. NO. SUITE 238 ST. PETERSBURG, FL 33713

Phone: (813) 327-8676 PI: Cesar E. Alvarez, Jr.

Title: Enhanced Architecture for Direct Digital Synthesizer (DDS) Designs

Abstract: The proposed research is in the area of new architectures for a Direct Digital Synthesizer (DDS). Current DDS architectures employ a phase accumulator, incremented each sample clock by a phase increment word. By controlling this word the rate (frequency) at which the accumulator overflows is controlled. The result is a stable programmable frequency source. The accumulator phase information is applied to a ROM in order to convert the phase information into a digitized in order to convert the phase information into a digitized sine waveform. The digitized wave is applied to a D/A converter and a low pass filter to generate the final waveform. Due to finite word lengths and the physical limitations of the architecture, phase and amplitude noise spurs are introduced during this process. Increasing the word lengths can reduce the noise spurs by about 6 db. per bit. What is proposes is two innovations that could reduce the noise spurs by more than 6db. per bit and thereby enhance the spectral purity of the generated waveform. To accomplish this the research proposes the use of: 1) New number systems with certain more desirable properties. 2) Approximation theory involving reduced computed computations.

MILLITECH CORP.

P.O. BOX 109, SOUTH DEERFIELD RESEARCH PARK SOUTH DEERFIELD, MA 01373

Phone: (413) 665-8551

Title: Millimeter Wave Spatial Power Combining Techniques

Abstract: Many millimeter wave radar and communications applications require total RF output power of 30W or more. Since one solid state three-terminal amplifier can deliver less than a Watt at these frequencies, the outputs of several devices must be combined to achieve the power levels desired. Conventional power combining circuits become expensive and inefficient for large numbers of devices. However, spatial power combining via quasioptical techniques improves efficiency by replacing much of the transmission line with lenses and feeds, thus allowing arrays with many amplifiers to give a net power increase. Our study will include practical tradeoffs of a quasioptical power combiner having an output power goal of 10-100W in the millimeter wave range. The study will include improved lenses, feeds and planar media giving optimum efficiency, size, weight, thermal performance, impedance matching and manufacturability. Phase I will comprise a goal definition and block diagram followed by a study of tradeoffs in packing density, area, volume, antennas and amplifier transmission media. The prototype we design in Phase I will be built in Phase II. These devices can be commercialized in automobile collision avoidance radars and all weather landing systems, already under development at Millitech.

MINARET SYSTEMS 3435 OCEAN PARK BLVD., SUITE 206 SANTA MONICA, CA 90405

Phone: (310) 306-0604

N PARK BLVD., SUITE 206 Office: CECOM ONICA, CA 90405 Contract #:

9) 306-0604 PI: Maria King

Title: A Secure Shell Toolkit for Unix Based Intelligence and Electronic Warfare (IEW) Applications

Abstract: This research proposes the development of a toolkit that provides security functionality required by IEW applications targeted for Unix platforms in order to meet DIA accreditation criteria for System High mode. Many versions of Unix are available and only a few are considered to be secure thus requiring security functionality to be implemented in the IEW application. The idea of the toolkit is to move the required security functionality out of the application and the operating system, regardless of the targeted version of Unix. A well-defined and controlled interface to the toolkit will be implemented using object-oriented techniques. Interaction with the toolkit is restricted to this interface. The toolkit interface and behavior will always remain the same, only its internals may change in order to port the toolkit to another platform. The advantage of this

object-oriented approach is that it forces the application to access the toolkit through a well-defined, controlled interface, thus isolating the application from the Unix operating system.

Topic#: 92-071

Contract #:

Office: NATICK

ID#: 92NAT-117

ID#: 92NV -031

ID#: 92MTL-116

MISSION RESEARCH CORP. 735 STATE STREET, P.O. DRAWER 719 SANTA BARBARA, CA 93102

Phone: (714) 754-1300 PI: Mr. Robert Eisler

Title: Improved Individual Ballistic Protective Fibers/Material Systems for Body Armor

Abstract: The proposed effort incorporates an analytical approach to support development and optimization of an improved individual ballistic protective material system for body armor which incorporates poly vinyl alcohol (PVA) fibers. The approach relies on a hierarchy of analytical models describing the mechanical and ballistic performance of fibers, yarns, and fabrics. The models are then exercised to determine parametric sensitivities in terms of fiber, yarn, and fabric properties. Insights garnered from this activity are then used to guide subsequent PVA fiber development. The five tasks proposed include: (1) Analytical Model Development; (2) Parameter Studies; (3) Experimental determination of fiber and yarn deformation modes; (4) Development of a Phase II Plan; and, (5) Preparation of deliverables. The analytical model development is also divided into four subtasks which describe: (a) Fiber mechanical properties in the longitudinal and lateral direction; (b) Multitow mechanical properties; (c) Favorable yarn geometries; and, (d) Deformation and failure modes of the fiber, yarn, and fabric.

MOSET CORP.

2507 RIVENDELL

LAKE FOREST, CA 92630

Phone: (714) 768-8549

Topic#: 92-043

Office: CECOM

Contract #:
PI: Ken R, Zanio

Title: Infrared (IR) Materials Growth and Detector Processing Technology for Monolithic Dual-Band Detectors

Abstract: The overall objective of this effort is to provide monolithic activity on GaAs/Si substrates for dual-band (3-5 and 8-12

micron) focal plane arrays (FPAs). More specifically to: 1) Determine the most promising GaAs/Si monolithic dual-band approach, 2) Identify Si readout (R/O) circuits, 3) Plan critical material and detector experiments, 4) Provide a monolithic dual-band FPA process, and 5) Layout FPAs and test circuits for 4" Si wafers. This effort will be based upon the authors' earlier work which replaced In bonds in hybrid FPAs by conformal thin films that interconnect HgCdTe detectors to R/Os in the same Si wafer. The proposed effort will extend this single-band monolithic technology to dual-band FPAs. The effort will determine the best dual-band unit cell in either a tandem or adjacent configuration using HgCdTe for the MWIR and either HgCdTe or AlGaAs quantum wells for the LWIR. R/O design will share charge between the unit cell capacitors and columns to increase signal-to-noise but yet maintain a small cell. The effort will plan experiments for processing the R/Os and detectors and for growing and fabricating detectors on GaAs/Si. The effort will deliver a dual-band process and a layout for 4" Si wafers that will include test structures and a 8 x 8 and another larger dual-band FPA.

MSNW, INC. Topic#: 92-135
P. O. BOX 865
Office: MTL
SAN MARCOS, CA 92079
Contract #:

Phone: (619) 489-9471 PI: Dr. George H. Reynolds
Title: Continuous Titanium Carbide Monofilaments for Reinforcement of Titanium Metal Matrix Composites

Abstract: The Phase I research will produce and evaluate continuous TiC1-x monofilaments having improved thermochemical and thermomechanical compatibility in high Ti content (beta alloys, orthorhombics, and a-2 titanium aluminide) matrices. Continuous binary carbide monofilament compositions will be prepared by direct chemical vapor deposition onto small diameter resistance-heated core monofilaments or wires or, alternatively, by reactive conversion of small diameter Ti core wires. The product monofilaments will be characterized by optical and electron microscopy with x-ray analysis for microstructure and chemical uniformity and through room temperature mechanical property measurements. Specimen continuous monofilaments will be supplied to MTL for independent evaluation. Prototype composites will be prepared and the thermochemical stability of the binary composition monofilaments determined by microchemical analysis of near-interfacial composition profiles. The project will be performed with the assistance of Pratt & Whitney Aircraft-Florida, who will prepare the prototype composites for joint evaluation.

MSP CORP.

1313 FIFTH STREET SE, SUITE 206 MINNEAPOLIS, MN 55414

Phone: (612) 379-3963

Topic#: 92-048

Office: CRDEC

ID#: 92CRD-015

ID#: 92BRD-035

ID#: 92MED-030

ID#: 92TAC-114

Contract #:

PI: David Thimsen

Title: Lightweight TOF Mass Spectrometer with Atmospheric Pressure Inlet

Abstract: The objective of the proposed work is to design a lightweight mass spectrometer system based on a time of flight mass spectrometer with atmospheric pressure ion source. It is expected that this device will be able to measure ppb concentrations of atomic species in the 50-300 charge-to-atomic mass ratio range. Supporting electronics will be engineered from experience on constructing electronics packages for rocket launching into the upper atmosphere of Earth and Mars. The supporting vacuum system will be engineered as part of the entire package. Design limitations for the package are a maximum weight of 201b, maximum power consumption of 250 wt.

NAMBETECH, INC.

RT. 1, BOX 204H SANTA FE, NM 87501

Phone: (505) 455-7620

Topic#: 92-025

Office: BRDEC Contract #:

PI: Dr. Daniel C. Barnes

Title: PORTABLE, LIGHTWEIGHT NEUTRON SOURCE FOR MINE DETECTION

Abstract: It is proposed to develop a portable, lightweight neutron source for detection and location of mines via nuclear activation of the high-explosive material (HE). It is further proposed to develop the technical base required to plan a demonstration of neutron activation of HE base mine detection in a field environment. The latter task requires a study of neutron transport from the source, through the intervening soil, and the interaction of the resulting neutron spectrum with a HE target surrounded by the remaining components of a mine. In addition, a combined boom-mounted scurce/detector package will be conceptually designed.

NOISE REMOVAL SYSTEMS

DR. TOM HARLEY, ROUTE 2 BOX 635

OXFORD, MS 38655 Phone: (601) 234-5359

Topic#: 92-160

Office: MEDICAL Contract #:

PI: Dr. Tom Harley

Title: An Active Noise Control Stethoscope Abstract: The objective of the proposed work is to develop an electronic stethoscope that enables emergency medical personnel to check vital signs in the presence of high background noise levels. Often physicians in military vehicles and other noisy environments are unable to auscultate. The relevant stethoscope audio signal becomes unintelligible when masked by prohibitively loud noises. The proposed electronic stethoscope will allow physicians to clearly hear sounds used to monitor the lung, heart, and blood pressure of patients. The design of the electronic stethoscope incorporates active noise control and adaptive ligital signal processing technology. A functional breadboard prototype has already been developed for removing cyclical or repetitive noise. During Phase I of the project, the software used by the controller will be combined with previously developed algorithms for canceling (non-eriodic) noise. A detailed cost analysis of the targeted commercial project will be made. Several specific noisy environments of interest will be simulated in the laboratory. Demonstrations f the active noise control breadboard prototype will be given to stethoscope manufacturing companies in an effort to obtain a contingency commitment for follow-on support and licensing at the completion of Phase II.

NOVA MANAGEMENT, INC. 1029 LOCHNESS COURT

SUNNYVALE, CA 94087 Phone: (408) 373-1056

Title: Electronic Map Display and Route Planner

Topic#: 92-087 Office: TACOM

Contract #: PI: John E. Tope

Abstract: Manual planning with paper maps will be even more difficult and time consuming if combat vehicle crew sizes are reduced. Robotic combat vehicle systems require electronic map display and route planning as an essential element of these systems. This project will develop an electronic map display and route planner (EMDRP). This project is the first phase of a development program that will end with an electronic circuit board module that will perform the electronic map display and

route planner functions. The module hardware and software will be compatible with the Standard Army Vetronics Architecture. The project will: 1. Review research and formulate plans and software for EMDRP. 2. Evaluate potential of flat panel display technology. 3. Define an EMDRP concept. 4. Validate software algorithms to support the system. 5. Provide a final report. In performing this project NOVA Management, Inc. will draw upon the experience of its subcontractor FMC Corporation Corporate Technology Center in route planning technology. Specific emphasis will be placed on the FMC High Speed Path Optimization Co-Processor (HSPOP) based on advanced dynamic programming techniques in an ASIC form that does the route selection functions.

NOVA MANAGEMENT, INC. 1029 LOCHNESS COURT SUNNYVALE, CA 94087

Phone: (408) 373-1056

Office: TACOM
Contract #:
Pl: John E. Tope

Topic#: 92-089

ID#: 92TAC-141

Title: Embedded Training for Integrated Two-Man Crew Station

Abstract: The Integrated Two-Man Crew Station (ITCS) will be used with the Vetronics Crew Control Demonstrator (VCDD) in experiments to define the optimum crew size and crew station configuration for vehicles of the future. These laboratory facilities will be integrated with items from the Standard Army Vetronics Architecture (SAVA) program. This project will define and demonstrate an embedded training system that will permit combat vehicle crew persons to train in their simulated vehicle crew station. The embedded training system will be integrated into hardware and software of VCDD, ITCS and SAVA modules. The project will: 1. Define requirements for ETITCS software based upon prior research with specific emphasis on the M2/M3 type infantry fighting vehicle. 2. Design and develop specific training and special hardware or software items for use with the VCDD and ITCS systems. 3. Conduct a demonstration using the ETITCS software on a VCDD crew station in the Vetronics Laboratory. 4. Provide a final report and Phase II Plan. In performing this project NOVA Management, Inc. will draw upon the experience of its subcontractor FMC Corporation Corporate Technology Center in training system development.

OCA APPLIED OPTICS 7421 ORANGEWOOD AVENUE GARDEN GROVE, CA 92641 Phone: (714) 895-1667

Topic#: 92-060 Office: MICOM Contract #: PI: Fred Hesse ID#: 92MIC-084

Title: Day/Night Low Light Level TV Sensor

Abstract: As a Phase I effort, OCA proposes to develop a design for a day/night low light level TV camera system. This is a system composed of a lens assembly with variable iris, a Gen III (dual microchannel plate) image intensifier with variable gain and a gated photo-cathode, a CCD camera with automatic gain control, auto level control and noise reduction filter that performs under illumination levels between 10 E-4 to 10 E 4 foot candles. OCA will adapt a major part of its present Brilliant Pebbles intensives CCD camery design to meet these requirements. OCA will evaluate a number of recent technical advancements with the goal of incorporating these into a new and improved design. These innovations include utilization of new application specific analog integrated circuits for CCD signal processing; miniaturization through the use of multi-chip-modules for electronic packaging; use of 5 to 8 micron diameter microchannel plates; an intensifier power supply with auto brightness control, variable gain, bright source protection, and that operates at 800 KHz; tapered fractal fiberoptics; variable edge control for intensifier gating, vapor deposited Paralene insulation in place of solid potting for high voltage. OCA will apply a systems approach to the design in order to prepare a System Requirements Specification, perform an end to end photometry analysis, and develop the subsystem design.

ONTAR CORP. 129 UNIVERSITY ROAD BROOKLINE, MA 02146 Phone: (617) 739-6607 Topic#: 92-092 Office: TECOM Contract #:

ID#: 92TEC-043

PI: Dr. John Schroeder

Title: Automatic Smoke and Obscurant Cloud PR from Visible and Thermal Imagery

Abstract: The US Army has a requirement to develop and deploy systems to automatically detect smoke and obscurant clouds using visible and infrared imagery. The proposed program will implement a method to determine the spatial extent of clouds using a combination of techniques such as advanced image processing, pattern recognition, knowledge based procedures (KBP),

and neural networks (NN). The complexity of detection systems requires highly sophisticated algorithms for operations such as classification, recognition identification and characterization. The capabilities of systems to perform on-board, real-time processing has increased enormously over the past several years. The objectives of this work are to perform the research and implement the software to develop a system for the development and evaluation of algorithms for cloud detection and classification. Phase I will encompass the implementation of a simple system for algorithm evaluation, and make recommendations for a hardware platform and software development. Extensive development and validation will be completed in Phase II.

Topic#: 92-153

Topic#: 92-063

Office: MICOM

PI: David Jared

Topic#: 92-026

Office: BRDEC

Contract #:

Contract #:

Office: ARI

Contract #:

ID#: 92ARI-010

ID#: 92MIC-080

ID#: 92BRD-072

OPERATIONAL TECHNOLOGIES CORP. 4100 N.W. LOOP 410, SUITE 230 SAN ANTONIO, TX 78229

Phone: (512) 731-0000 PI: Benjamin A. Fairbank, Ph.

Title: A Propensity Score Model of Costs and Benefits Related to Army Service

Abstract: A major obstacle to the establishment and measurement of valid cause and effect relationships between Army service and the costs and benefits of such service is the impossibility of performing experiments with random assignment of individuals to service and non-service groups. A recent innovation in statistical theory, propensity score methodology, allows one to draw from an observational (or retrospective) study virtually the same kind of causal inferences that previously have been possible only with experimental studies. Propensity score methodology has been successfully used in medical, social science, and educational contexts. Phase I will develop a specimen propensity score model of costs and benefits of Army service, will identify and specify the data sources necessary to implement and test the model, and will determine the procedures and scope of the effort needed to test the model. Phase I will include a preliminary specification of the variables appropriate for use in the final model. Attention will be given to the question of oversampling women and minorities so that separate models may be developed for them. Not only are such separate models desirable heuristically, they are also particularly appropriate when using propensity scores. Phase II will be devoted to the elaboration, detailed specification, testing, and evaluation of the model.

OPTOELECTRONIC DATA SYSTEMS 310 SOUTH 42ND STREET BOULDER, CO 80303 Phone: (303) 541-9220

Title: Convolving Optically Addressed VLSI Liquid Crystal Spatial Light Modulator

Abstract: The principle objective of the proposed research program is the development of a noval spatial light modulator that calculates a 3 x 3 kernel convolution on an input image. The spatial light modulator consists of a ferroelectric liquid crystal modulator on top of a CMOS VLSI chip. During Phase I, a comprehensive study of several convolving SLM designs will be performed. The study will examine circuit level details and system level details. A test chip containing sub-circuits of several SLM designs will be designed, fabricated and tested.

ORINCON CORP. 9363 TOWNE CENTRE DRIVE SAN DIEGO, CA 92121

Phone: (619) 455-5530 PI: Mr. Donald K. Owen

Title: Intrusion Detection from a Moving Platform

Abstract: Intruder detection using a mobile platform with multiple sensor suites is difficult because of the ever-changing warehouse environments in which the robots operate. Doppler shifts caused by platform motion or intruder motion also add to the problem. ORINCON proposes a novel approach to intruder detection that uses a statistical differencing technique on multiple-sensor-suite digitized snapshots at preprogrammed locations in the environment. Image differencing of digitized video camera frames has been used successfully in industry to detect intruders by detecting changes in the background from frame to frame. ORINCON takes this notion a step further. First, during initialization, a robot takes several digitized sensor snapshot measurements along a preprogrammed path and stores the data and the measurement locations. On subsequent path passes, the snapshot measurements-taken at the same locations-are compared to the initialization measurements by differencing. If "significant" discrepancic exist, then an intruder detection is determined to have occurred. If not, then the most recent snapshot

is stored for the next pass. The main thrust of the proposed work will be to determine what "significant" discrepancies are and how they are related to probability of detection and probability of false alarm.

ORINCON CORP. 9363 TOWNE CENTRE DRIVE SAN DIEGO, CA 92121

Phone: (619) 455-5530

Topic#: 92-121

Office: HDL

Contract #: PI: Dr Thomas W. Brotherton ID#: 92HDL-031

ID#: 92HDL-059

ID#: 92EW -007

Title: Knowledge-Based Target Classification Using Baseband Doppler Audio Frequency

Abstract: In analysis of basebanded Doppler radar signals, it has been noted that trained operators can classify target types by aural analysis of the baseband signals. This implies that there is sufficient structure in the signal so that automated analysis using speech processing techniques can perform classification. Standard analysis techniques assume that the data is stationary and well modeled using Fourier transformations of the data. The resulting spectrum is used to determine signal components that are then used for classification. Unfortunately, the audio signals of interest are highly nonstationary and can even contain sequences of pulses. The standard Fourier spectral analysis techniques cannot determine the time-varying structure within the data and thus do not provide sufficient features for classification. It is this time-varying structure that gives the operator the clues he needs for classification. ORINCON proposes to develop and demonstrate an automated system that uses high-resolution time/frequency representations to characterize the data. The feature extractor is coupled with a neural network to solve the classification problems. Neural networks have been used extensively and successfully at ORICON to solve detection/classification problems in underwater acoustics, as well as for fault detection/classification problems in rotating machinery. This technology is directly applicable to the classification problem for baseband Doppler radar return signals.

P C DYNAMICS 2906 FM 720 EAST FRISCO, TX 75034

Phone: (214) 335-9841

Title: Solder Plating Process Control

Topic#: 92-124 Office: HDL

Contract #: PI: Lawrence D. Harvey

Abstract: The objective of this proposal is to develop and implement a scientifically based solderability tester as a process control tool during the fabrication process for printed circuit boards. Using the sequential electrochemical reduction analysis (SERA) process as invented by Rockwell International, data will be gathered to correlate the coulomb density values determined by SERA to current, commercial solderability testing as described in IPC-5-804. Designed experimentation methods will be used to determine the key process characteristics that can be controlled as a result of the information available through the SERA test method. In addition, the SERA test equipment will be evaluated for its ability to withstand the normal production environment and possible design improvement recommendations will be made to enhance its ability to withstand the environment.

PACIFIC ADVANCED TECHNOLOGY P.O. BOX 679, 1001 CROFT LANE SOLVANG, CA 93464

Phone: (805) 688-2088

Title: Continuous Wave (CW) Laser Detection Techniques

Topic#: 92-036 Office: CECOM

PI: Michele Hinnrichs

Contract #:

Abstract: Pacific Advanced Technology (PAT) is pleased to propose a new and creative solution to single aperture multi-spectral laser warning. Our proposed approach to laser warning can detect multiple laser spectral bands with a single aperture over a wide field of view and determine angle of arrival with in less than a degree. As an example of the multi-spectral nature of this approach, a laser in the midwave infrared as well as a longwave infrared can be detected with a single aperture, thus minimizing modifications to existing platforms and reduce sensor costs due to less components needed. This proposal approach to laser warning uses speckle gram interferometry to perform optical signal processing for coherence detection, coupled with neural network signal processing for classification and direction of arrival. Using neural networks on the focal plane array to perform the post signal processing will enable real time detection, discrimination and warning in a light weight small package. This new technology allows the straight forward manufacture of a simple, compact optical system which will detect and warn against laser threats. During the Phase I portion of this SBIR we will model the PAT proposed laser warning approach for the Army's CW threats using the PAT laser warning computer simulation model. We will also perform a first order design of the neural network

signal processor that is an integral part of the PAT approach to a laser warning system. To our knowledge this approach to laser warning has not been discussed, offered or pursued elsewhere in the Department of Defense.

116 MILAN WAY Office: CERL OAK RIDGE, TN 37830 Contract #:

Phone: (615) 483-0666 PI: Herbert W. Hoffman, Ph.D.

Title: Lead Paint Removal by Confined Hydraulic Jet

Abstract: This project will devise and develop an efficient and cost-effective technique for removing lead-contaminated paint films from painted surfaces in Army buildings scheduled for demolition. High-pressure water jets confined within a shield (operating head) remove the paint from the surface. The operating head is sealed against the work surface by flexible flange. Small channels in the flange allow the air entering the operating head at high velocity. The air/water/paint film residue mixture is drawn out by an air compressor which discharged the mixture through a centrifugal separator and a filter into the atmosphere. The separated water and paint mixture passes to a series of tanks in which centrifugation, settling, and filtration processes remove the paint residue from the wash water. Recirculation of the cleaned wash water through a positive-displacement pump supplying the jets minimizes the volume of waste water requiring disposal. The film solids are collected and concentrated for disposal as hazardous waste. The process raises no institutional issues. Phase I will compare the proposed technique with extant processes, identify feasibility issues, prepare a verification test plan, perform necessary performance scoping tests, and gauge development success probability. Phase II will design, procure, and assemble a prototype device; carry out laboratory and field verification tests; and identify commercial/industrial participants.

PHOTONICS RESEARCH, INC. Topic#: 92-120 ID#: 92HDL-005

350 INTERLOCKEN PKWY., SUITE 245

BROOMFIELD, CO 80021

Phone: (303) 465-6497

Office: HDL

Contract #:
PI: Jack L. Jewell

Title: Two-Dimensional Microlaser Smart Pixel Arrays for Optical Signal Processing

Abstract: We propose to develop compact, high-speed, highly-functional III-V semiconductor optoelectronic modules optimized for implementation into optical signal processing (OSP) systems under development at government and university laboratories. The modules will be based on vertical-cavity surface-emitting lasers integrated discretely or monolithically with other optoelectronic or electronic circuitry. This technology has the attributes sought for OSPs: compactness, high speed, low power, high gain, high contrast, versatility, robustness to environmental changes, simple implementation into systems, and reconfigurability. The principle and co-investigators will utilize their extensive pioneering experience in this technology, optimizing the designs for analog systems such as image processing and neural networks. Close interaction with groups presently working on OSPs will insure utility for systems under development. Objectives are: 1)evaluate the usefulness to OSPs of device configurations; 2)determine the performance limits; 3)identify potential users of the technology; 4)identify the optimum module; 5)develop a fabrication process for the module; and 6)develop a Phase II project plan to demonstrate and deliver 2-D arrays to HDL and arrange financing to bring components to commercial availability. Photonic Research Inc. has successfully introduced another SBIR-sponsored technology to the commercial market.

PHYSICAL OPTICS CORP. Topic#: 92-036 ID#: 92EW -008

20600 GRAMERCY PLACE, SUITE 103 Office: CECOM TORRANCE, CA 90501 Contract #:

Phone: (310) 320-3088 PI: Mr. Lev Sadovnik

Title: A Small, Signal Block Laser Coherence Discriminator

Abstract: The problem of low-power CW laser detection in not detector sensitivity but detector selectivity. the only reliable laser feature that is not modified by propagation through the atmosphere is its temporal coherence. Based on this, Physical Optics Corporation (POC) proposes to develop and fabricate a new type of coherence discriminator that is capable of detecting the presence of low-power laser illumination against a background of much brighter natural and man-made incoherent light sources. This is achievable because only temporally coherent radiation will be modulated and consequently, synchronously demodulated by the proposed coherence discriminator. The proposed device would be usable in all spectral bands of interest.

The sensor itself is expected to be rugged, small (< = 8 inches 3), lightweight (< = 200 grams), and inexpensive to fabricate. Thus, a proliferation of devices could be placed on the surfaces of tactical platforms, and eventually, the device concept could be incorporated into "smart skin" designs. In Phase I of this program, a breadboard model of the proposed laser discriminator for the IR spectral region will be built, and its high discrimination capability will be proved experimentally. In Phase II, two field testable prototypes will be fabricated.

PHYSICAL OPTICS CORP.

20600 GRAMERCY PLACE, SUITE 103

Phone: (310) 530-1416

TORRANCE, CA 90501

Title: A Generic Bio-Alarm Based on the Application of Immunowaveguide and Neural Networks

Abstract: It is frequently the case that a biological alarm is required to provide GO/NOGO information for a user to make a decision in a minimum amount of time. That means bio-alarms should have the ability to identify a large number of biological agents, monitor the change in concentration of these dangerous materials, and make intelligent decisions in a very short time. In response to the need for this technology, Physical Optics Corporation (POC) proposes to develop a generic bio-alarm with selectivity, speed, and sensitivity. The POC approach is based on the combination of two state-of-the-art technologies: waveguide fluoroimmunoasay (WFIA) and artificial neural networks (ANN). The proposed WFIA can have many parallel channels and large sensing areas for simultaneous multiple analyze sensing. ANNs have been applied to various pattern recognition, classification, and intelligent decision making tasks. Both techniques have been independently investigated and have been proven to work. The merger of these technologies will provide the framework for the construction of a biological agent monitor that meets the Army's requirements. POC proposes an innovative and technically unparalleled concept for a highly sensitive fluoroimmunoassay device for biological agent monitoring.

PHYSICAL OPTICS CORP.

20600 GRAMERCY PLACE, SUITE 103

TORRANCE, CA 90501

Phone: (310) 320-3088

Topic#: 92-049 Office: CRDEC

Topic#: 92-047

Office: CRDEC

PI: Z.Z. Ho, PH.D.

Contract #:

ID#: 92CRD-006

ID#: 92CRD-031

ID#: 92NAT-011

Contract #:

PI: Mr. Mark W. Foster

Title: Handheld Surface Plasmon Resonance Biosensor with Replaceable Sensing Cartridge

Abstract: Advances in biochemical warfare technology have necessitated a commensurate advancement in biosensor technology in order to detect the presence of military biological agents in the field. During the past five years, immunosensors utilizing surface plasmon resonance (SPR) have received substantial attention for use in both civilian and military biosensing applications. Physical Optics Corporation (POC) proposes to develop a novel handheld surface plasmon resonance biosensor using a replaceable "multibounce" waveguide sensor cartridge. The waveguide sensor alleviates the requirement of using a prism coupler and rotation stage for SPR measurements. By slightly focusing the waveguided light, the entire surface plasmon resonance is probed passively without any angular adjustments. A simple detector array can be used to monitor the resonance profile and changes arising from the presence of target bioagents. The sensor uses multiple reflections at the sensor interface to increase sensitivity to small amounts of target analyses. The proposed detection scheme allows the possibility of sensing multiple bioagents simultaneously with a single sensor unit. Using POC's "substrate mode" waveguide sensor, well-developed immunoassay thin film chemistries currently used with TIR prisms can be directly incorporated in the miniaturized SPR system.

PHYSICAL OPTICS CORP.

20600 GRAMERCY PLACE, SUITE 103

TORRENCE, CA 90501

Phone: (310) 320-3088

Topic#: 92-065

Office: NATICK Contract #:

PI: Dr. Vladimir Manasson

Title: Helmet-Mounted Fiber Optic Emitter For Individual Soldier Identification

Abstract: Physical Optics Corporation (POC) proposes a fully integrated soldier identifier based on a "leaky" emission optical fiber (i.e. thread) interlaced into a soldiers combat uniform. A low power, battery operative infrared (IR) light source provides the optical fiber pattern detection from all angles and required distances by ground-based night vision devices. In order to minimize possible interception and counterfeiting, the identifier will have an option of remote activation in a pulsed regime. A short emitted pulse will be unnoticeable by an enemy's IR vision device but will be reliably detected by the designated

observer due to synchronous framing. The identifier will be made of inexpensive and commercially available parts. Only minor modification is required for the night vision device in order to perform synchronous detection. The Phase I part of the program will deliver a fully operational identifier prototype and IR detection system.

PHYSICAL OPTICS CORP.

20600 GRAMERCY PLACE, SUITE 103

TORRANCE, CA 90501

Phone: (310) 320-3088

Topic#: 92-149

Office: TOP

Contract #:

PI: Mr. Jeremy Lerner

ID#: 92TOP-052

ID#: 92SDC-003

ID#: 92C3 -010

Title: Smart Environmental Monitor Based on Neural Networks and Multi-Specked Pattern Recognition

Abstract: Accelerating industrialization has caused an increasing demand for environmental monitoring. Because of this, physical Optics Corporation (POC) proposes to develop a novel real-time smart environmental monitor (SEM), utilizing a novel holographic optical neural network (HONN) recently developed at POC for pattern recognition applications. These new architectures combine an optical implementation of the so called N4 neural network architecture, high efficiency compact holographic memory matrices, and new fast electronic algorithms for feature extraction and statistical data analysis. The proposed system will be extremely fast and highly rugged. It will be capable of detecting various contaminants simultaneously with extremely high resolution and sensitivity. POC's HONN can also be made compatible with imaging and mass spectrometers. POC's HONN system can be further expanded in Phase II to contain 64,000 fully interconnected neurons, with over 4x10 9 interconnections. POC's HONN will be capable of "learning" over 20,000 features of different spectral patterns and perform real-time spectral analysis and classifications. The success of this project will result in the most advanced level of a field deployable multi-spectral detection technology.

PHYSICAL SCIENCES, INC.

20 NEW ENGLAND BUSINESS CENTER

ANDOVER, MA 01810

Phone: (508) 689-0030

Topic#: 92-169

Office: SDC

Contract #:

PI: William J. Marinelli

Abstract: A novel, non-intrusive technique is proposed for the temporal and spatial imaging of high-intensity infrared laser beams. The technique employs a visible probe laser to excite phosphorescence in a gas seeded into a flow of N2. The high intensity, IR laser beam passes through this gas jet flow. Irradiation of the emitting gas by the IR laser causes a reduction in emission proportional to the laser intensity. Cylindrical optics are employed to define an emitting sheet in a plane transverse to the IR laser beam. This emission is spatially resolved using a image-intensified TV camera synched to the probe laser to obtain the laser beam intensity profile. The temporal resolution of the device is defined by the emission lifetime of the gas of approximately 1 ms with a framing rate of 30 Hz. Commercially available image processing software may be employed to provide real-time diagnostic capability and images may be stored on standard video tape for post-processing. The proposed beam diagnostic technique is directly applicable to target plane beam diagnostics requirements at the High Energy Laser Systems Test Facility (HELSTF) in the various test areas. It will provide the accuracy and the reliability needed to make high quality, rapid target plane beam diagnostics a reality.

PLASMATRON COATINGS & SYSTEMS, INC.

1704 TAYLORS LANE, TAYLORS LANE BUSINESS CENTER

Title: Temporal and Spatial Beam Diagnostics for High Power Lasers

CINNAMINSON, NJ 08077

Phone: (609) 786-3399

Topic#: 92-028

Office: CECOM

Contract #:

Pl: Dr. Ravi Rastogi

Title: Method for Advanced Production Techniques for In-line Deposition of Diamond Scratch Resistant Coatings on Optical Glass Fibers

Abstract: We propose a SBIR Phase I project to develop and demonstrate the technology for coating optical glass fibers with a hard, hermetic and chemically inert and scratch resistant layers of Diamond-Like Carbon (DLC). The DLC coatings will provide improved reliability and performance, and maintain the design and dimensional characteristics of the optical fibers against the abrasion, chemical erosion and environmental degradation. DLC layers are inert, moisture and H2 impermeable and will be applied at near room temperature. The DLC films will be applied on commercially available optical glass fibers by magnetically enhanced plasma chemical vapor deposition using an innovative high-intensity cylindrical magnetron reactor

developed and pioneered by Plasmatron Coatings and Systems, Inc. Systematic investigations of (i) dependence of hermeticity, (ii) adhesion of DLC to the fiber, (iii) hardness, (iv) scratch resistance and (v) optical and micro-bend losses as a function of microstructure, structure, composition and process parameters will be performed to achieve the proposed objectives. Different layer configuration of DLC films will be studied in Phase I. The cylindrical magnetron reactor, studies in Phase I will be scaled-up to produce an in-line, high-rate, deposition system for coatings optical fibers during manufacturing in Phase II.

POLHEMUS LABORATORIES, INC.

P.O. BOX 5

CAMBRIDGE, VT 05444

Phone: (802) 644-5569

Topic#: 92-011 Office: AVSCOM Contract #:

ID#: 92AVS-052

ID#: 92ETD-038

ID#: 92SDC-056

PI: Wm. L. Polhemus

Title: A Head-Coupled Visual and Aural Sensor System for Teleoperated Rotorcraft Research Vehicle

Abstract: Inside Out vs Outside In! It seems reasonable to hypothesize that the pilot of an air vehicle will feel more in harmony with the actions of his vehicle when he is at the relative "origin" of the coordinate frame of reference of that vehicle ... and will respond more quickly and with greater accuracy, precision, and efficiency. Experience teaches that this occurs for a pilot when utilizing an "inside-out" configuration of cues which square with his physiological sensations. Our goal is to supply those cues utilizing the visual and aural stimuli acquired by appropriate placement of a stereo camera and directional microphone array. A customized version of Polhemus Laboratories binocular, color, high resolution, head-worn display (Looking Glass) system, modified to include a six DOF head tracker and stereo audio system will be provided as the key components of the forthcoming FFRRV ground-based Virtual Cockpit. A PLI Eyeglass display was delivered to NASA-ARC on 16 June '92 for integration with teleoperated camera platforms mounted on an unmanned vehicle. The head tracker (there are three candidates) will supply orientation commands to cameras mounted in the FFRRV, and will be an interactive component in the isolation or confirmation of significant aural cues, an interactive component in the isolation

PRINCETON MICROWAVE TECHNOLOGY, INC.

P.O. BOX 113

PRINCETON JUNCTION, NJ 08540

Phone: (609) 586-8140

Topic#: 92-110

Office: ETDL

Contract #: PI: Sarjit Singh

Title: Low Cost Microwave/Millimeter-Wave Drop-In Ferrite Components

Abstract: The recent advent in Personal Communications Networks, PCN, and Cellular communications has demanded low cost ferrite components for the RF front ends operating at 9GHz cellular and 1.8GHz GSM bands. The thrust of Personal communication is now being directed towards other ISM (instrumentation, scientific and Medical) bands which allow unlicensed operation at frequencies of 2.4GHz, 5.8GHz, and 39 GHZ. Additionally licensed cellular systems are being developed at 28GHz. The theme, and reality, for the success of such system is low cost components which are amenable to production methods for mass manufacture. The 28 GHz and 39 GHz cellular systems will operate in large cities where reflections from large buildings and structures will enable long distance inter-city communications using very small antennas. Ferrite components, such as circulators and latching circulators are used in the front-ends of two way communication systems. The requirement of low cost and high performance demand ferrite components in formats that utilize minimum parts, surface or drop in mounting, small size and minimum interference with interface with other transmission medium. Princeton Microwave Technology, a microwave component manufacturer, and Xtalonix, a microwave ferrite material manufacturer, are proposing to address the low cost manufacture of ferrite components by using novel injection molding methods. The original ferrite components, developed by ETDL, will be prototyped in Phase I using isostatic and hot pressing methods and the ferrite material optimized for high performance. The Phase II plan will then advance the manufacture of the low cost components using state of art injection molding methods and will directly address the forthcoming communication markets that are fast emerging.

PRINCETON SCIENTIFIC INSTRUMENTS, INC.

7 DEER PARK DRIVE

MONMOUTH JUNCTION, NJ 08852

Phone: (908) 274-0774

Title: Improved Visible Image Sensor

Topic#: 92-174 Office: SDC

Contract #:

Pl: John L. Lowrance

Abstract: This proposal is to develop a back illuminated Charged Coupling Device solid state image sensor with improved

quantum efficiency in the ultraviolet as well as the visible. the high quantum efficiency that can be attained with back illuminated CCDs, combined with the low readout noise at fast frame rates, makes it possible for this unintensified CCD to replace an improve on the performance of image intensifier-CCD image sensors currently used for low light level imaging and star trackers and faint target acquisition in ASAT systems. This CCD will allow smaller and more reliable cameras to be made. Eliminating the image intensifier results in longer term storage reliability, higher spatial resolution and broader spectral response. Developing this CCD for ASAT also presents a significant commercial opportunity in the area of low light level cameras needed by law enforcement night vision, industrial surveillance and scientific research.

Topic#: 92-045

Office: CRDEC

Topic#: 92-094

Office: TECOM

Topic#: 92-095

Office: TECOM

Contract #:

Contract #:

Contract #:

ID#: 92CRD-039

ID#: 92TEC-016

ID#: 92TEC-018

PRODUCT DEVELOPMENT ASSISTANCE, INC. 13511 EAST BOUNDARY ROAD, SUITES D & E MIDLOTHIAN, VA 23112

Phone: (804) 744-0604 PI: Rajan A. Jaisinghani Title: High Efficiency Low Pressure Drop Electrostatic Enhanced Filtration for NBC Aerosols.

Abstract: An Electrostatic Enhanced Filtration (EEF) technology is proposed for NBC collective protective systems such that the efficiency of the current NBC filter medium can be enhanced to at least 99.997 at 0.3 micron, without any increase in the pressure drop of the current medium. This technology also has the potential to kill bacterial components of the aerosol, and possibly also viruses. On the other hand, some amount of ozone is generated by the process (which can be reduced by optimizing the electrode and field configurations). This is a feasibility study, aimed at establishing the required design parameters (e.g. field strength, and electrode geometry) such that the efficiency enhancement is maximized and the ozone production is minimized. A 500-1000 scfm prototype will be constructed and evaluated for efficiency and pressure drop. The effect of the minimized ozone production on ventilation requirements to meet NIOSH standards for ozone, will also be established by means of a material balance model (Jaisinghani et al. 1989). Additionally, a preliminary evaluation of the effectiveness of the device in terms of killing bacteria, will be conducted.

PSR SERVICES, INC. P.O. BOX 369 WSMR, NM 88002 Phone: (505) 678-9365

Phone: (505) 678-9365 PI: Jimmy D. Shirley

Title: Modular Laser Beam Analyzer

Abstract: PSR Services, Inc. (PSRS) proposes to develop and demonstrate a concept for a High Resolution Laser Target Plane Image Analysis System to measure laser beam near and far-field intensities, total power, jitter, divergence, and quality. Primary device features include: (1) a modular scalable sensor area, (2) a wide spectral range, (3) full-frame data capture, (4) variable integration time and frame rate, (5) real-time beam diagnostics, (6) portability, (7) suitability for mobile/airborne applications, (8) built-in diagnostics, and (9) calibration simplicity.

QUEST INTEGRATED, INC. 21414-68TH AVE. SOUTH KENT, WA 98032

Phone: (206) 872-9500 PI: Dr. H.-T. (Peter) Liu

Title: 3-D Radiography and Image Analysis of Defect Detection

Abstract: In Phase I of this project, we will investigate the feasibility of adding a "real-time" or "near real-time" stereoscopic imaging capability to the armaments radiographic inspection system already in place at Yuma Proving Ground. We will determine the best way to implement rapid, accurate, and cost-effective automated stereoscopic inspection with minimal modifications to existing equipment. We propose to do this by (1) providing a stereoscopic imaging demonstration on a PC-type computer with a stereo-scoping display, (2) using this demo to obtain stereo radiographs of Yuma's actual test items in the context of the ultimate automated system, (3) analyzing the configuration and capabilities of the present facilities (which include the radiographic systems and the image processing computer system) to determine the best way to take the necessary multi-aspect radiography, and (4) determining the functional requirements of the ultimate system (with respect to, for example, image quality and resolution, throughput, the need for image processing and measurements, and operator ease of use). Phase II would implement such a system at the Yuma Proving Ground. We look forward to taking this technology to the broader industrial

inspection community in Phase III.

QUEST INTEGRATED, INC.

21414-68TH AVENUE SOUTH **KENT, WA 98032**

Phone: (206) 872-9500

Topic#: 92-104

Office: ASL

Contract #:

PI: Dr. Paul A. Hwang

ID#: 92ASL-007

ID#: 92MIC-020

ID#: 92SW -012

Title: Size Distribution and Number Density of Airborne Particles Near the Ground Level -- Vertical Distribution and Wind

Speed Dependence

Abstract: To enhance characterization of the propagation path of assorted Army electro-optical and electro-acoustic devices, a detailed understanding of atmospheric conditions near the ground surface is needed. This proposal concentrates on the effects due to the presence of airborne particles. The ground-level aerosol model currently implemented is rather crude and needs to be refined. In the proposed study, the generation of airborne particles from local soil sources will be investigated theoretically based on our understanding of turbulence diffusion and sediment transport processes. The results will allow us to evaluate the error in estimates of aerosol number density due to the negligence of the vertical gradient and wind dependence close to the ground. Building upon this theoretical framework, as well as field data assimilation, we will establish an aerosol model for the lower boundary layer that contains explicit functional dependence of the elevation and wind speed. The new aerosol model will be used for extinction and scatter computations, which will enable enhancement of the performance of optical and acoustic sensors in ground-level applications. The computation of extinction, visibility, transmission attenuation, target acquisition probability, image obscuration, and image resolution will be improved through more accurate estimation of the number density and size distribution of airborne particles along ground-level propagation paths.

RADAR GUIDANCE, INC. 7 DONORE SQUARE SAN ANTONIO, TX 78229

Phone: (214) 250-0334

Topic#: 92-057 Office: MICOM

Topic#: 92-040 Office: CECOM

Contract #:

Contract #:

PI: Aubrey I. Chapman

Title: Low Cost, LPI, All Weather, Automated Optical Microwave Technology for IFF of Unmanned Aerial Vehicles (UAV) Abstract: RGI proposes to demonstrate through analysis the feasibility of using modified versions of the proven OMAR (Optical Microwave Approach and Ranging) technology to enhance the reliability and survivability of UAV's by using the OMAR technology for UAV, IFF, tracking and flight commands for evasive action when necessary. OMAR, currently under development as a low cost, stand alone, precision, all weather landing system for VTOL aircraft lends itself uniquely to these UAV requirements. Modifications to the exiting OMAR design will be required for this specialized UAV use but basic concepts of Luneberg lens beam shaping with angel/range processing will remain valid. Basic OMAR characteristics, including the ability to operate in a passive (covert) mode, makes it attractive as a portable 3-dimensional military IFF, positioning, tracking and command system with many commercial applications. For UAV applications, its response to authentication coded interrogation, structured in directional low-power reflective needle beams, provides a low probability of intercept and a positive identification of friend or foe (IFF) for unsophisticated, lethal and unmanned aerial vehicles. It's small, all, weather, unique operational characteristics makes it possible for OMAR to monitor more than 50 IFF targets and provide its 3-dimensional positioning information in digital form into intel networks such as the NOMAD and SAMURAI systems and/or Patriot Missile System in real time.

RADIX TECHNOLOGIES, INC. 4020 MOORPARK AVENUE, SUITE 212

Phone: (408) 345-4900

SAN JOSE, CA 95117 Title: Robust Techniques for Acquisition and Processing of PH, PH/DS and Conventional Communications Signals

PI: Brian G. Agee

Abstract: An SBIR project is proposed to apply optimal detection and estimation theory to acquisition (detection/classification), copy, and localization (DF) of frequency agile, hybrid FH/DS, and conventional telecommunications signals. A two-stage baseline system is proposed to accomplish this, consisting of a multisensor processor front-end, which employs dominant-mode prediction (DMP) and polychannel DMP (PC-DMP) to detect, copy, and localize emitters on the basis of their variation in time-frequency support (temporal burstiness and/or bandwidth extent); and a signal-sensor processor back-end, which employs

log-likelihood functions (LLFs) and per-survivor-processing (PSP) algorithms to classify and demodulate the dehopped/downconverted emitters provided by the processor front-end. Both stages provide optimal (GLRT) statistics for detection and classification of the emitter waveforms, and provide optimal (ML) estimates of the emitter waveforms under appropriate modelling conditions. In addition, the baseline processor is compatible with channelized digital reconnaissance systems under current development, such as the TACJAM A system, in that they can operate against emitters with bandwidths larger than the frequency channelization of the reconnaissance system, even if that system employs undersampled frequency channelizers that do not allow complete regeneration of the emitter time series

RADKOWSKI ASSOC.

P.O. BOX 5474 RIVERSIDE, CA 92517

Phone: (714) 684-6794

Title: Proof-of-Concept of Innovative Soft-Kill Pellets

Topic#: 92-173

-173 ID#: 92SDC-045

Office: SDC Contract #:

PI: Peter P. F. Radkowski III

Abstract: Radkowski Associates has developed an innovative soft-kill concept that offers to significantly enhance kinetic energy lethality against satellites. The proposed research effort would use advanced modeling, material fabrication, and gun range testing to prove the Soft-Kill Pellet Concept. Advanced hydrocode calculations of conceptual design performance indicate that, in comparison to other kinetic energy kill devices, the Soft-Kill Pellets offer significant performance enhancements, including: * Lethal diameters ar increased by a factor of two (or more) * Orbital space debris is significantly decreased (or eliminated) * mechanisms are included for enhance sensor-detection of lethal impact; * fabrication and deployment costs are low; and * safety and durability are increased. The Soft-Kill Pellets can be deployed singularly or as clouds by a variety of kill vehicles.

REDZONE ROBOTICS, INC. 2425 LIBERTY AVENUE PITTSBURGH, PA 15222

Phone: (412) 765-3064

Topic#: 92-143

ID#: 92CER-044

ID#: 92MED-046

Office: CERL Contract #: PI: Chris Fromme

Title: In Situ Tank Inspection System (ITIS)

Abstract: RedZone Robotics, Inc. proposes to develop a system capable of performing automated inspections on a variety of underground storage tanks (UST) configurations. The system will consist of the following parts: 1) manipulator/mechanism for sensor delivery; 2) collision avoidance sensing; 3) force or other feedback sensor for proper sensor placement; 4) computer feedback and control; 5) software for automated inspection/data gathering. The objectives of the Phase I efforts are to develop a suitable mechanism which can be deployed into a variety of different UST configurations. Also, the sensing system used to determine the robot's location within the tank is a key technology which must be adapted from current techniques. A prototype of the mechanism will be built to prove the selected concept. After testing on a UST mock-up, the design will be refined and modified with the goal of providing a hardened design. Phase II and III will be used to develop the controller to drive the system and develop custom software and procedures for performing inspections.

REID LABORATORIES 100 INMAN STREET CAMBRIDGE, MA 02139

Phone: (617) 576-8611

Topic#: 92-158

Office: MEDICAL Contract #:

PI: Dr. Kittie Murray

Title: A Test Device for Organic Pollutants at the Low PPB Level

Abstract: We propose to develop a test device for the measurement of trace organic materials in water. The device is specifically targeted at the analysis of herbicides and pesticides in water. The target level of detection is the low part per billion concentration range for materials with a molecular weight of about 300. The approach is a modification of a commercially available medical diagnostic test. The modification consists of a proprietary amplification method that will increase sensitivity while not sacrificing the original ease and convenience of use. The test will require no user operations except to place the device in the sample. The readout will show either a positive or negative response where positive represents a level above a set concentration. This will be the EPA limit or others specified by the DoD. The device should be stable for many years at room temperature.

RESEARCH & DEVELOPMENT LABORATORIES

5800 UPLANDER WAY CULVER CITY, CA 90230

Phone: (310) 410-1244

Title: Suppression of Vibration-Induced Sidebands

Topic#: 92-108 Office: ETDL

ID#: 92ETD-017

ID#: 92SDC-076

ID#: 92TOP-022

ID#: 92HDL-034

Contract #: PI: ERIK Unit

Abstract: Study and define the feasibility and the possible improvements from the suppression of vibration-induced sidebands in crystal oscillators. Task A: Study and define and optimal design for obtaining the sum and difference frequencies from two nominally identifical SC-cut crystal oscillators appropriately arranged with respect to each other so as to obtain maximum cancellation of steady-state acceleration sensitivities. Task B: Study and design an analog circuit to use the information in the difference frequency to obtain optimal correction of the sum frequency. Task C: Study and define A/D and D/A converters to support digital compensation. Study the impact of clock instability on conversion accuracy. Task D: Study and define digital compensation schemes. In particular study the adequacy of using the crystal oscillator to be compensated for the clock for the digital processing.

RESEARCH ASSOC. OF SYRACUSE, INC.

510 STEWARD DRIVE NORTH SYRACUSE, NY 13207

Phone: (315) 455-7157

Topic#: 92-175 Office: SDC

Contract #:

PI: George Millman

Title: Improved Real-Time Ionospheric Compensation for Kwajalein Missile Range (KMR) Radars

Abstract: The objective of this study is to identify an ionospheric model for improving, in real time, the ionospheric propagation error corrections for the ARPA long range tracking and instrumentation radar (ALTAIR) located at the Kwajalein Missile Range (KMR). The study consists of (1) performing a state-of-the-art review of the various ionospheric models, (2) designating an ionospheric model for ALTAIR based on low-latitude transionospheric propagation comparison of the various ionospheric models, (3) comparing the selected model with the present ALTAIR ionospheric model and with the electron content data recorded at KMR, (4) identifying the ionospheric measurements which should be conducted at KMR prior to incorporating the ionospheric model in ALTAIR and (5) assessing the potential use of the ionospheric model at other geographic locations.

ROBERT LEVI ASSOC.

3320 W. MACARTHUR BLVD, SUITE B SANTA ANA, CA 92704

Phone: (714) 557-6180

Title: Personal Navigation and Reporting

Topic#: 92-147

Office: TOP Contract #:

PI: Robert W. Levi

Abstract: Troop movements in the battle field must be done precisely to achieve combat objectives. Modern weapons can be accurately targeted, but to prevent "friendly fire" accidents, actual troop positions must be known by commanders precisely with a high degree of confidence. Combining GPS with advanced dead reckoning sensors, a data link, digital map technology and a microcomputer would provide the soldier with a reliable position finding means and the capability to relate his position to others. The proposed project will develop a compact man-portable, soldier navigation and reporting system that is not wholly dependent on one navigational aid such as GPS. The system will provide the capability for uniquely identifying and tracking a virtually unlimited number of troops without pre-arranged synchronization or prior knowledge of troop positions. Concepts for several unique sensors that will aid dead reckoning for the foot soldier are discussed. The proposed project represents extensions of ideas based on previously developed position location transponders and our experience with navigation systems.

ROCHESTER PHOTONICS CORP.

80 O'CONNOR ROAD FAIRPORT, NY 14450

Phone: (716) 377-7990

Topic#: 92-122

Office: HDL Contract #:

PI: Dr. John P. Bowen

Title: Laser Pattern generator for the fabrication of diffractive optical elements

Abstract: A single-point laserwriting system for the fabrication of multi-phase level surface-relief diffractive optics will be designed and analyzed. The instrument will be designed to generate diffractive structures in photoresist. The minimum feature size obtained from such an instrument directly influences the maximum diffraction angle, wavefront performance, and diffraction

efficiency of the resulting optical element. The overall performance of the optical element is a strong function of the instrument accuracy. In the Phase I research and development effort, a user interface and the associated software routines for developing generalized phase structures will be developed. Optical elements of interest include diffractive lenses and interconnect distributions for optical processing applications. Compared to electron-beam or vlsi-lithographic methods, a laser offers the potential for small feature sizes at reasonable cost. Direct writing on the substrate will allow the optic to be manufactured at one station. The goal of the SBIR Phase II development effort is to construct and evaluate an integrated workstation for the fabrication of a wide range of diffractive components.

S.R. TAYLOR AND ASSOC.

6105 S.E. NOWATA RD., SUITE 12 BARTLEVILLE, OK 74006

Phone: (918) 333-7502

Title: Novel Ultrasonic Method for Food Dehydration

Topic#: 92-066

ID#: 92NAT-027 Office: NATICK

Contract #:

PI: Dr. Scott Taylor

Abstract: Foods are dehydrated to make them more easily packaged and stored at room temperature. The removal of water reduces the opportunity for harmful chemical reactions. Dehydrated food powders and particles are also used in "liquid meals" for dental patients. However, dehydrated foods traditionally have been difficult to rehydrate and are of relatively poor quality. The reasons for these difficulties are from thermal damage due to the high temperatures necessary to dehydrate the foods. A process useful for heat sensitive foods, which is presently being used by the U.S. Army for their dehydration needs, is freeze drying. Freeze drying, although effective, has its drawbacks. Freeze drying is a very expensive process involving high capital costs and high energy cost. S.R. Taylor and Associates proposes an alternative method to do dehydration for the U.S. Army. Ultrasonic drying has been proven effective for certain types of heat-sensitive materials, such as many fresh foods. Phase I will determine which food-types would be appropriately dried ultrasonically, and at which processing variables. Phase II would involve process optimization for the highest quality dried rehydrated product at the lowest cost. S.R. Taylor and Associates has actively been involved in developing a novel ultrasonic flexural plate design to deliver a highly axisymmetric sound beam into gaseous and liquid media. This unique flexural plate will produce the desired sound wave pattern to enhance food dehydration at unharmful temperatures and conditions.

SAG CORP. 900 S. WASHINGTON STREET, SUITE 109

FALLS CHURCH, VA 22046 Phone: (703) 538-4500

Title: Measuring the Costs and Benefits of Army Service

Topic#: 92-153

ID#: 92ARI-006

ID#: 92MED-063

Office: ARI Centract #: PI: Lee S. Mairs

Abstract: SAG Corporation proposes to develop a framework for measuring the economic and social costs and benefits of an Army career. The research will focus on identifying and evaluating data sources and developing quantitative methods and procedures for comparing these costs and benefits. The resulting model will go beyond traditional retention models to look at the total impact of an Army career on an individual's present and future participation in the work force. The Phase I research will explore how costs and benefits vary with occupation, race and gender as well as career length. The research will incorporate elements of econometric and psychometric analysis as well as cost-benefit modeling. Phase I will result in a conceptual model to serve as the foundation for Phase II development of a policy analysis tool that Army analysts can use to objectively evaluate personnel and compensation policies. The model will allow for comparisons involving career lengths and differing assumptions about underlying determinants of the career decision. Costs and benefits will be tracked for an individual's entire career in the labor force.

SAN'DOIL COMPANY 600 LOYOLA AVENUE, SUITE 202

NEW ORLEANS, LA 70113

Phone: (504) 646-1493 Title: Rapid Field Toxicity Test for Water Supplies Topic#: 92-163 Office: MEDICAL

Contract #:

PI: Dr. Arthur V. Stiffey

Abstract: A patented (U.S. Patent #4,950,594-1990) inexpensive, quick, precise method of testing substances for toxicity has been developed, LUMITOX (R), which measures quenching, in the presence of toxins, of the natural bioluminescence of the

abundant marine dinoflagellate Pyrocystis lunula. The LUMITOX (R) microbiological assay is a compact laboratory procedure that has been proven effective on all common toxins tested. Specific applications have included mycotoxins, exfoliates, insecticides, waterbottom sediments (Chukchi Sea), marine antifouling paints, and oil-well drilling fluids. The procedure has demonstrated a variation of less than 10%, sensitivity to a few parts per million, and effectiveness in darkly colored and turbid media. At its present stage of development, in the laboratory LUMITOX (R) yields results in a few hours, rather than the days required for existing bioassays. A project is under way to isolate the test organism's operative enzymes in order to develop a field-testing reagent. Design and construction of portable device consisting of a sample chamber, agitator, photodiode, metering circuit (also patented, U.S. Patent #4,689,305-1987), and LED or other readout mode also are necessary to complete a portable field toxicity testing unit, which as obvious potential for both military and civilian environmental applications.

SATCON TECHNOLOGY CORP. 12 EMILY STREET CAMBRIDGE, MA 02139

Phone: (617) 661-0540

Title: Innovative Blade Design Concepts for Highly Maneuverable Rotors

Topic#: 92-008

Office: AVSCOM

ID#: 92AVS-028

ID#: 92AVS-106

Contract #:

PI: Richard L. Hockney

Abstract: Future military rotorcraft will require significant increase in maneuverability and handling qualities with low detectability for air-to-air combat and nap of the earth operations. SatCon Technology Corporation proposes to develop innovative blade design concepts using smart material/structures to meet this requirement by substantially enhancing the maneuver capability of the rotor. These concepts, consisting of piezoelectric, electro-strictive, magnetostrictive and other advanced actuators integrated into the blade design, would allow individual control of the rotor blades. This approach will improve operability by improving maneuverability, agility, and speed; improve supportability by increasing reliability; and improve survivability by decreasing signature (noise and vibration). Phase I will identify and compare advanced and innovative blade design concepts using smart materials/structures which enhance the maneuver capability without performance and weight penalties. The most promising concepts which are representative of current future technology will be traded-off considering both benefits and disadvantages in terms of attributes such as rotor performance, weight, and complexity. In Phase II additional evaluation of the most promising concepts will be performed to verify benefits and disadvantages. A 10-ft. diameter scale model of the most promising concept will be fabricated and tested to validate the theoretical predictions.

SATCON TECHNOLOGY CORP. 12 EMILY STREET CAMBRIDGE, MA 02139

Phone: (617) 661-0540

Topic#: 92-019

Office: AVSCOM

Contract #:

PI: Dariusz A. Bushko

Title: High Bandwidth Magnetostrictive Actuator for Helicopter Electric Flight Control

Abstract: Progress in electric flight control has been hindered by the lack of a high bandwidth actuator. The challenge is to identify an efficient, responsive, and power dense source of mechanical displacement. Actuators based on "giant" magnetostrictive materials, such as Terfenol, achieve very high magnetic strain (up to 2,000 ppm) and therefore provide power density unmatched in electromechanical systems. They outperform all known piezoelectric materials in terms of mechanical properties. SatCon has used Terfenol in several high performance actuators for space applications. In a large-stroke actuator, however, strain must be amplified while preserving power density. SatCon proposes to demonstrate an innovative actuator which uses local hydraulics to transform magnetostrictive strain into an arbitrarily long stroke. Magnetostriction generates pressurized fluid flow which powers a linear hydraulic actuator. The benefits of high performance hydraulics are retained without sacrificing the weight, redundancy, reliability, and simplicity of electric actuation. During Phase I, SatCon will develop a preliminary actuator design suitable for a cyclic/collective application. During Phase II, SatCon will detail design, fabricate, and bench test the actuator. Specifications will be at stated (3 inch stroke, 25 hp rating, and a response comparable to hydraulics). Alternate forms of electric power will be studied. Air cooling will be maximized.

SATCON TECHNOLOGY CORP.

12 EMILY STREET CAMBRIDGE, MA 02139 Phone: (617) 661-0540

Topic#: 92-023 ID#: 92AVS-157

Office: AVSCOM Contract #:

PI: Monique Gaffney

Title: High Power Density Magnetostrictive Reaction-Mass Actuator

Abstract: Magnetostrictive materials have been successfully used in single-axis actuator designs to produce forces over 3500 pounds, strains of 1200 ppm, and have bandwidths past 10,000 Hertz. Terfenol-D, the "giant strain" magnetostrictive material is an excellent candidate to produce a high power density reaction mass actuator for helicopter gearbox noise cancellation. Using magnetostrictives, the single axis actuator can meet the weight, volume and durability requirements, without compromising the force or frequency range specifications. In contrast to piezoelectric materials, magnetostrictive materials have seven times larger strain and fifteen times higher energy density, resulting in more actuation effort for the given mass and volume budget. Unlike piezoelectrics, magnetostrictives do not require high voltages to operate efficiently. Compared with piezoelectrics. magnetostrictives have greater reliability and longer life advantages. The propered work is to demonstrate the feasibility of using a magnetostrictive driven reaction-mass actuator for helicopter gearbox noise cancellation. During Phase I, the objective is to design, fabricate, test, and deliver a high-force density, magnetostrictive-based eaction-mass actuator. This actuator shall be capable of exceeding the suggested specifications of over 100 pounds at frequencies between 1000 and 4000 Hz. During Phase II, this work will be extended to multi-degree-of-freedom designs.

SATCON TECHNOLOGY CORP. 12 EMILY STREET CAMBRIDGE, MA 02139

Prione: (617) 661-0540

PI: James R. Downer, Ph.D. Title: High Efficiency, Low Weight Electric Inlet Particle Separator (IPS) Blower for a Turboshaft Engine

Abstract: An electric-motor driven Inlet Particle Separator (IPS) blower is an ideal solution to a number of technical problems related to eliminating sand and dust erosion of turboshaft engine components. A motor which does not require liquid lubricant would be even more desirable since the inlet area of turboshaft engines is a difficult one for the installation of lines. SatCoa proposes to develop a flux-concentrating permanent-magnet brushless motor and its associated controller as an IPS blower motor. This motor design makes the best use enacted magnetic materials technology since the total weight and power consumption of components is critical. The electronic interface design will make use of either AC or DC (28 V or 270 V) primary power to determine the optimum approach for minimum size and weight. A maximum weight of five pounds has been established. Oiless bearings based on solid lubricant or an advanced bearing grease will be used. During Phase I, SatCon will generate a preliminary design for the motor and electronic drive system using the T800 engine. During Phase II, SatCon will detail design, fabricate, and bench test the IPS electric blower. Testing will simulate To00 IPS operation over full engine operating range.

SATCON TECHNOLOGY CORP. 12 EMILY STREET CAMBRIDGE, MA 02139 Phone: (776) 611-0540

Topic#: 92-080 Office: TACOM Contract #:

Topic#: 92-024

Contract #:

Office: AVSCOM

PI: James H. Goldie

Title. The Development of an All-Electric Active Vehicle Suspension Based on a Linear Reluctance Machine

Abstract: SatCon Technology Corporation proposes to develop an ail-electric vehicle suspension which utilizes a switched linear reluctance machine (LRM) and associated drive and control electronics. The low losses of switched reluctance machines, while operating under high loads and motions of varying direction, suggest that a linear version is uniquely suited for this application. The low losses indicate that it can be compactly packaged into an active suspension relative to other efectric actuators without risk of overheating. Combining the LRM with the similar compactness and low loss of pulse width modulation inverters and the flexibility of a DSP-based controller permits development of an all-electric suspension which is compact, reliable, user adjustable, and adaptable to changing road or terrain conditions. Furthermore, the energy absorbed by the proposed suspension system during operation may be recovered rather than dissipated as heat, significantly improving fuel economy. During Phase T Satcon proposes to design a complete suspension system, it sting the LRM actuator, the drive electronics, and the programmable controller, such that various susp insion control algorithm could be easily implemented. In addition, SatCon will fabricate and test a small-scale LEN, to demonstrate the remarkable high force-to-loss ratio of this type of machine.

SAUNDERS PRODUCT DEVELOPMENT 208 SOUTH PULASKI STREET BALTIMORE, MD 21223

Topic#: 92-141 Office: CERL

ID#: 92CER-050

ID#: 92AVS-165

ID#- 52TAC-035

Contract #:

Phone: (410) 624-4187

PI: Selden Saunders

Title: Development of Vacuum Supported Automated Platform and Method of Paint Removal and Dust Collection

Abstract: The project will develop a unique vacuum supported platform which will automate the process of removal of toxic paint from Army buildings. The platform will traverse wall and ceilings and position the paint removal system for optimum results. A unique dust collection system will be developed to work in conjunction with the platform with high efficiency. The best method of paint removal to use in conjunction with the platform will be determined, so that the system is very cost effective.

SBS ENGINEERING, INC.

Topic#: 92-037

ID#: 92SE -005

18333 EGRET BAY BLVD, SUITE 340 HOUSTON, TX 77058

Office: CECOM

Contract #:

Phone: (713) 333-5040

PI: Patrick Rogers

Title: An Extended Ada Runtime Environment for Distributed, Fault Tolerant Applications

Abstract: In response to ever-increasing requirements, next-generation embedded systems will typically consist of several physically dispersed uniprocessor or multiprocessor nodes. In order to harness the potential of such architectures, a definition of distributed, fault-tolerant Ada must exist. Because the language standard does not meaningfully address distribution or fault tolerance, an extension of the underlying runtime support environment is both appropriate and cost effective. This proposal outlines initial baselines for the necessary models of distribution, fault tolerance and dynamic reconfiguration, and proposes to refine these models into a preliminary systems architecture design.

SCHWARTZ ELECTRO-OPTICS, INC.

Topic#: 92-035

ID#: 92NV -095

3404 N. ORANGE BLOSSOM TRAIL ORLANDO, FL 32804

Office: CECOM

ID#: 92TEC-041

Phone: (407) 298-1802

Contract #:

PI: Dr. Madhu Acharekar

Title: Non-Cooperative Combat Identification

Abstract: Generally, detection and recognition of a target can be made at distances greater than those for positive identification. In an effort to extend the identification. In an effort to extend the identification range, Schwartz Electro-Optics, Inc. (SEO) proposes to develop a concept for Non-Cooperative Combat Identification by sensing the vibrations of targets with Doppler Laser Radar, Vibrational signature measurement with Doppler laser radar has been successfully demonstrated using CO2 lasers. Issues of size, cost, weight, and reliability of the laser have prevented deployment of these sensors. Recent developments in two micron solid state lasers can allow vibrational signature measurement in a compact, reliable sensor. Eyesafe operation is maintained at this wavelength, as is the ability to penetrate obscurant and dust on the battlefield. The proposed Phase I effort draws on past and on-going activities at SEO to prove the feasibility of target identification, and to develop a preliminary design of a prototype sensor. The effort will include an analysis and assessment of available signature data, a parametric design study of the sensor parameters, and development of a top-level, prototype sensor design.

SCIENCE & TECHNOLOGY CORP.

Topic#: 92-092

101 RESEARCH DR. HAMPTON, VA 23666 Office: TECOM Contract #:

Phone: (505) 521-4353

PI: Roger E. Davis

Title: Automatic Smoke and Obscurant Cloud Pattern Recognition from Visible and Thermal Imagery

Abstract: U.S. Army smoke and obscurant field testing programs produce information and data for assessment of inventory and developmental obscurants. Determinations of obscurant cloud dimensions, locations, and centroids are often used for quantifying performance. To determine geometric cloud characterization parameters, current data reduction procedures require time-sensitive and potentially inconsistent manual (human) location of cloud perimeters from visible and infrared video imagery. The Phase I work plan proposes to identify both software and hardware components necessary to create an automated cloud perimeter location system. The plan seeks to integrate human cues into a knowledge base which will utilize image processing techniques and algorithms. The Phase I effort will also explore algorithms for the extraction of additional obscurant information, e.g., path radiance and cloud density, from the video imagery. Successful techniques and algorithms will be recommended for inclusion in the Phase II engineering of the perimeter detection system.

SCIENTIFIC AERO MONITORING, INC. 8300 NORTH HAYDEN ROAD, SUITE 111 SCOTTSDALE, AZ 85258

Phone: (602) 991-5577

Title: Active/Passive Clearance Control for Small Turbine Engines

Topic#: 92-010 Office: AVSCOM

Contract #:

PI: Dr. Link C. Jaw

ID#: 92AVS-036

ID#: 92MIC-116

ID#: 92ETD-076

Abstract: Active clearance control promises considerable improvements in rotating component efficiencies and compressor surge margin. These improvements are essential to meet stringent performance requirements for next generation propulsion systems. The improvements are more pronounced for small engines, because clearance effect in small engines accounts for a bigger portion of rotating component losses than large engines. Scientific Aero Monitoring, Inc. proposes to conduct a research program on active clearance control for a small turboshaft engine. The firm should like to evaluate the feasibility of current and innovative clearance control concepts, and carry out the design, simulation, and demonstration of the most feasible concept in a test rig. The firm should like to focus its research on centrifugal compressors, because it is the preferred type for small turboshaft engines. The firm presented a candidate clearance control system in this proposal, although the candidate control system should not limit the firm's assessment of other feasible control concepts. Scientific Aero Monitoring, Inc. was founded with a vision to utilize the efficiency and concentration of a small business to facilitate technology development and adaptation. The firm emphasizes accountability and goal-oriented work ethics. The investigators for the proposed program offer more than 35 years of combined experience in aerospace system modeling, design, development and testing. A major portion of this combined pool of experience is directly related to the gas turbine engine field.

SCIENTIFIC RESEARCH ASSOC., INC. 50 NEY ROAD, P.O. BOX 1058 GLASTONBURY, CT 06033

Phone: (203) 659-0333

Title: Quasi-Optical Power Combiner Modeling

Topic#: 92-055 Office: MICOM

Contract #:

PI: Harold L. Grubin

Abstract: This document describes a program for numerically predicting the performance of hundreds of millimeter wave oscillators that are combined through quasi-optical techniques. The focus of this program will be on combining three terminal field effect transistors. The basis of the analysis centers around the interjection locking of canonical oscillators. Among the issues to be addressed during the Phase I are: (1) What is the locking bandwidth of the system of injection locked oscillators? (2) After an initial turn-on transient, how many cycles are needed before the oscillators synchronize to a common frequency and phase? (3) Are there restrictions on the distribution of amplitudes of the oscillators in order to achieve synchronization? (4) How will device and circuit variations influence the locking properties? (5) What constraints are to be imposed to operate the couple-oscillator arrays as mode-locked arrays? (6) Choices of oscillator configurations. (7) Best use of Fabry-Perot resonators. (8) Limitations on packing density. The out of the calculations will also provide (1) the radiation patterns for a finite set of coupled oscillators, for prespecified values of the coupling phase; and (2) the time dependence of the output signal power envelop of a number of mode locked oscillators.

SENSORS UNLIMITED, INC. 3490 U.S. ROUTE 1, BUILDING 8 PRINCETON, NJ 08540

Phone: (609) 520-0610

Title: "A Merged Hydride/OMVPE Expitaxial Growth System for InGaAsP Alloys

Topic#: 92-107 Office: ETDL

Contract #: PI: Dr. Marvin S. Abrahams

Abstract: We propose to design, construct, and optimize a novel vapor phase crystal growth system for semiconductor optoelectronic devices which combine the best features of organometallic (OM) vapor phase epitaxy (VPE) and hydride VPE. The system will use OM compounds such as triethyl gallium (TEG) and trimethyl indium (TMI) mixed with HC1 to produce volatile chlorides in a hydride-style hot wall reactor. These two features will allow the growth of very thin, abrupt interface layers (an OMVPE advantage) with a high growth rate (about 10um/hr) and low arsine consumption in a hot-wall system (a hydride advantage). In Phase I, we will (1) modify an existing vapor phase reactor by designing and installing a rapid gas switching manifold, (2) grow 3 nm alternate layers of In.53Ga.47As/InP to demonstrate thin-layer growth capability, and (3) grow and fabricate a 3 um thick In.53Ga.47As detector structure to demonstrate thin-layer growth capability, and (3) grow and fabricate a 3 um thick In.53Ga.47As detector structure to demonstrate overall quality of the materials. We will also submit a design for a compact, low-cost, but flexible merged system. In Phase II, we will build and optimize this growth system

including a safer arsine delivery - and fabricate thin-layer multi-quantum-well devices including 1.55 um DFB lasers and strained-layer infrared detectors.

SIERRA MONOLITHICS, INC. 103 W TORRANCE BLVD., STE. 102 REDONDO BEACH, CA 90277

Phone: (310) 379-2005

Title: High Power Solid State Ku-band Transmitter

Topic#: 92-116 Office: ETDL

Contract #:

PI: Dr. Binneg Y Lao

ID#: 92ETD-022

ID#: 92ETD-060

ID#: 92HDL-045

Abstract: A high power portable Ku-band transmitter using a DRO/FET/Doubler approach is proposed to replace a Magnetron for beacon transponder applications. The proposed technique can satisfy the system specifications in frequency stability, operating temperature, RF power, pulse modulation, pulse width and rise/fall time, pulse repetition rate, power consumption, and spur and harmonics levels. The Proposed Phase I effort will provide a proof-of-concept system with an efficient frequency doubler to provide the required RF power at 17 GHz. The Phase I program will also include investigations regarding the use of high power FETs and MIMIC amplifiers directly at 17 GHz. A design using state-of-the-art higher power FETs satisfying the specifications in size, weight, and cost will be completed in Phase I and fabricated in Phase II. The proposed approach provides advantages in excellent temperature stability for output power and frequency, reliability, multiple device suppliers, simple power upgrading modular repairability, and the potential for CW operations.

SIGMA LABS, INC. 10960 NORTH STALLARD PLACE TUCSON, AZ 85737

Phone: (602) 575-8013

Topic#: 92-109 Office: ETDL

Office: ETDI
Contract #:

PI: Dr. Angelo Yializis Ph.D

Title: Scale-up of RF Plasma Treated Capacitors for High Energy Density Applications

Abstract: Work by M. Binder and the Army ETDL has shown that the RF plasma treatment of capacitor films, electrode foils and wound rolls, can result in significant and in some cases dramatic improvements, in the electrical breakdown strength of certain capacitor films and capacitor rolls. In this investigation we will demonstrate potential commercial applications of the RF plasma treatment that will allow this technology to be licensed by film producers and capacitor manufacturers. In order to identify the commercialization potential of the film surface treatment, a high power hollow cathode RF reactor will be used to reduce the treatment time so that the process can be used to treat webs of film that are moving at production-like speeds. Contact angle, adhesion and ESCA analysis will be done on the surface of the films, to relate the data to the work done by the ETDL and further quantity effects of the O2 and CF4/02 plasmas. Treated films will be metallized with and with out exposure to air, and the self healing characteristics will be studied. Aluminum and tin foils with widths varying from 0.25" to 6.0" will be plasma treated and treated in wound capacitors, to determine the relationship of the foil edge treatment to the breakdown strength of the capacitors. Wound rolls will be plasma treated in a box etcher both by mechanical fixuring and by placing the rolls inside a cage that is rotating in the plasma chamber. The latter method will allow large quantities of small capacitors to be treated uniformly at a low enough cost, that will make this process cost effective even for marginal enhancements in the dielectric strength of the parts.

SILHOUETTE TECHNOLOGY, INC.

P.O.BOX 1479 MORRISTOWN, NJ 07962

Phone: (201) 539-2110

Topic#: 92-122

Office: HDL Contract #:

PI: Gene Dwyer, Ph.D

Title: Low Cost, PC-Based Diffractive Optical Element Mask Generator and Fabricator

Abstract: Diffractive Optical Elements (DOEs) are finding applications in areas of Artificial Intelligence, optical computing, interferometry, holographic optical elements and mask and lens fabrication. However, research and development has been hampered by the lack of an affordable and practical method of printing computer generated DOEs. Silhouette Technology has developed a new technology to make a low cost, reliable, PC based, DOE film printer offering a high space-bandwidth product. The device offers performance which exceeds the capability of existing systems such as electron beam recorders and laser printers. It will be able to print with a resolution of 2 microns and a positioning accuracy of less than 1 micron. The system output will be directly to film and provide hard copy and photoresist printing. A complete system is proposed that offers software

to print and generate computer generated DOEs.

SIMPEX TECHNOLOGIES, INC.

732 N. DIAMOND BAR BLVD, SUITE 116 DIAMOND BAR, CA 91765

Phone: (714) 396-0720

Title: Panoramic Image Translation of Microelectronic Assemblies

Topic#. 92-123 Office: HDL ID#: 92HDL-055

ID#: 92HDL-057

ID#: 92C3 -033

Contract #: PI: Bernard K. Siu

Abstract: Many inspection criteria for microelectronics and surface mount device manufacturing processes require a 360 degree view of the component. Due to the limitation of traditional 2D sensor array technologies such as machine vision and laser dimensional measurement equipment, multiple views of the chip and its fillets must be taken for flaw detection and analysis. These methods require intensive image processing and is time consuming. High Speed Panoramic Inspection System (HSPIS) combines coherent image guide technology, structured illumination, panoramic image translation algorithm, machine vision and computer interface technologies into a system that "unfolds" a 360 degree view of an object into a 2D image array. This technique has two major benefits: (a) it improves current automated inspection speed by at least 400% and, (b) a portable or downloadable Panoramic Image Translation Function Library consisting of microelectronics flaw detection routines will be developed and available for other vision systems. With the support of Brunswick, this technique will be applied (Tech-Transfer) to surface inspection of composite launch tubes and miniaturized pressured vessels as well. The HSPIS will be integrated as an automated inspection system which can inspect all sides of a component in a 30 milliseconds time frame. This system will have the intelligence to identify, locate and document the flaws with that time frame. Simpex will integrate and demonstrate the performance of this inspection system, using actual samples, to the Government representatives and guests.

SIMPEX TECHNOLOGIES, INC.

732 N. DIAMOND BAR BLVD, SUITE 116 DIAMOND BAR, CA 91765

Phone: (714) 396-0720

Title: Solder-Plating Process Control

Topic#: 92-124 Office: HDL

Contract #:

PI: Bernard K. Siu

Abstract: The objective of this effort is to develop and implement a scientifically based solderability tester (Sequential Electrochemical Reduction Analysis - SERA) as a process control tool during solder plating of electronic circuit boards. The study is to minimize "weak knee" solderibility problems on the curved radius of plated thru-holes. In addition, the design concept for an automated & ruggedized version of the present SERA tester will be developed. Simpex, with its factory automation expertise, will be integrating and implementing the SERA tester at Cedko Inc.'s printed circuit board manufacturing facility. Understanding the cause of oxidized metallization at "weak knee" locations, SERA test data will be collected at five strategic points in the printed circuit board plating line. Procedures specified in Mil-Std-105/E Level II AQL 1.5 will be used for data collection to ensure the largest sample size with minimum labor expenditure. Data collected at these locations will be analyzed to determine the type and amount of oxidation present. These statistical data or oxidation signatures, will in turn, be used to monitor and control the plating processes. In addition to the data collection and interpretation effort, software algorithms will be developed to interpret SERA readings or oxidation signatures in real-time, such that corrective actions can be recommended immediately by the system controller at each of the process control points. From the lessons learned in implementing the SERA tester, the design concept for an automated SERA test station with ruggedized features will be developed. This effort is anticipated to be completed in 6 months.

SONEX ENTERPRISES, INC.

12150 EAST MONUMENT DRIVE, SUITE 301

FAIRFAX, VA 22033 Phone: (703) 691-8122

Title: Tool Kit for Distributed Data Base Architecture

Topic#: 92-038 Office: CECOM

Contract #:

PI: Dr. David C. Rine

Abstract: The Information Distribution System concept provides the framework for establishment, distribution, and maintenance of object oriented databases within the future Army tactical command and control systems. This concept requires rules that completely describe the needs for combat information at each individual database maintained within the system, processes that locally compute updated values from the data in these databases, and triggers that permit data distribution based upon deviations

from the computed norm. This effort will focus on the development of a toolkit of procedures to permit construction of the sets of rules, processes and triggers needed for generation and timely update of the Army tactical command and control systems databases. The SONEX approach centers on the utilization of Object-Oriented and Intelligent reconfigurable software engineering technologies. Through these technologies distributed data systems can be developed more efficiently and will be more reliable and maintainable. To ensure the tool kits performance test bed design will also be a critical part of this project. Test methodologies that will be investigated include statistical analysis and modeling techniques.

SOUTHWALL TECHNOLOGIES, INC.

1029 CORPORATION WAY PALO ALTO, CA 94303

Phone: (415) 962-9111

Title: Development of Low frequency, Flexible EMI Shielding Materials

Topic#: 92-068

Office: NATICK Contract #:

PI: Craig A. Grimes

ID#: 92NAT-057

ID#: 92ETD-032

ID#: 92NAT-003

Abstract: The electromagnetic interference (EMI) shielding effectiveness of a material of fixed thickness is a function of the incident wave frequency and the conductivity/permeability product of the shielding material. Effective low frequency shielding requires either a high conductivity/permeability product or a relatively thick piece of material. Current low frequency shielding materials compensate for limited conductivity/permeability values by increasing the thickness of the shielding material, which generally limits their application. This proposal is for the development of a low frequency, flexible EMI shield. To maintain flexibility the shielding material must be quite thin, typically below 20 um, therefore the conductivity/permeability product must be high. We propose to use an amorphous, non-magnetostrictive ferromagnetic alloy in a multilayer structure, with a metallic interlayer, to achieve high permeability and high conductivity. A moderate value coercive force is required to avoid saturation of the shielding material. The design of the multilayer structure will be guided by analytic models developed for modelling shielding effectiveness. Other design issues include selection of substrate and shielding material combinations for superior adhesion, durability, and low cost as well as shielding effectiveness. Promising candidates will be fabricated to demonstrate the feasibility of such products.

SPACE EXPLORATION ASSOC. 141 WEST XENIA AVE. PO BOX 579

CEDARVILLE, OH 45314

Phone: (513) 766-2050

Topic#: 92-111

Office: ETDL Contract #:

PI: Elliot B. Kennel

Title: Very Compact Cathode Ray tubes Using Diamond P-N Junction Cold Cathode

Abstract: Very compact cathode ray tubes could be fabricated if high voltages presently required for normal operation could be reduced by a factor of ten. This requires a very effective cold cathode. A cold cathode capable of delivering several hundred amps per square centimeter (under ambient conditions without the introduction of cesium vapor) would be valuable for a number of applications in high power high frequency electronics. One of the most highly sought applications is that of cathode ray tube visual displays. Decreased voltage requirements would simplify the power supply requirements and allow a shorter CRT to be manufactured. This is of obvious utility of aerospace applications and could also be very attractive for consumer video displays as well. A method is described herein for manufacturing a cold cathode device using p-type diamond in direct contact with highly doped n-type silicon. Unlike other schemes for using diamonds as a cathode material, there is no need to manufacture n-type diamond.

SPECTRA RESEARCH, INC.

P.O. BOX -:95 DAYTON, OH 45459

Phone: (513) 436-4454

Title: Individual Combat Soldier Identification Technology

Topic#: 92-065

Office: NATICK Contract #:

PI: Paul D. Zidek

Abstract: For this Phase I SBIR, Spectra Research, Inc. proposes to research rugged, non-intrusive IFF concepts which employ unique low cost discrimination techniques to detect and positively identify friendly combat soldiers. The proposed design operates on passive non-cooperative emissive radiation and backscatter, augmented by cooperative multispectral retroreflective IFF devices. These devices digitally encode multispectral EO/IR and RF retroflection to assure high accuracy, robustness, and low intercept non-compromising operation. This combination provides secure sensor source data for operations over a broad

set of adverse battlefield conditions. Neural net signal processing techniques fuse this data to enhance reliability over this diverse set of battlefield conditions.

SPECTRA RESEARCH, INC.

7071 CORPORATE WAY, SUITE 108

DAYTON, OH 45459

Phone: (513) 436-4454

PI: John W. Sellers Title: A Next Generation Audio and Visual Cueing System for Tactical Engagement Simulation

Abstract: The firing of indirect fire weapons and the effect of incoming rounds have historically been simulated pyrotechnically. Weapon firing has been simulated by firing blank rounds and the effect of incoming rounds has been simulated by small explosive charges. Pyrotechnics have the advantage of being the simplest way to create the sound of an explosion, which is difficult to duplicate by other means. Moreover, the pyrotechnic mixture can be compounded to produce the desired levels of flash and smoke. Pyrotechnics also have several disadvantages. Being explosive devices, the charges present storage and handling hazards, and firing the charges carries the risk of igniting accidental fires. Spectra Research (S*R) proposes to overcome these limitations with a non-pyrotechnic explosion simulator that is compact, reusable, and configurable for a range of effects. The proposed simulator uses a pneumatic shock tube to generate the sound, a non-toxic aerosol agent to generate the smoke, and a flash tube to generate the flash of an explosion.

SPECTRAL SCIENCES, INC. 99 SOUTH BEDFORD STREET, #7 **BURLINGTON, MA 01803**

Phone: (617) 273-4770

Title: Gallium Arsenide Semiconductor-laser Multigas Analyzer (GASMAN)

Topic#: 92-159 Office: MEDICAL

Topic#: 92-097

Contract #:

Office: STRICOM

ID#: 92STR-009

ID#: 92MED-019

ID#: 92NV -046

Contract #:

PI: Dr. Neil Boldstein

Abstract: The need exists for portable instrumentation with the capability of real-time monitoring of human environments for a variety of toxic gases generated by military weapons systems. Spectral Sciences, Inc. (SSI) proposes to build a Gallium Arsenide Semiconductor-laser Multigas Analyzer (GASMAN) which will provide automatic, unattended, real-time monitoring of several toxic gases. GASMAN employs multiple diode-laser in conjunction with multiplexing techniques to simultaneously monitor air samples for five or more toxic species in a common flow-through sampling cell. GASMAN uses techniques of wavelength modulation and line-locked absorption detection common to several gallium arsenide-based sensors developed by SSI for automated and unattended operation in the detection of single species in open air. GASMAN incorporates these features, along with a long-path absorption cell, multiple diode-laser sources, and multiplexing techniques. An internal microprocessor system controls experimental sequencing and stores several hours of continuous concentration data with sub-second time resolution. The resulting system is portable, compact, lightweight, and has low power consumption requirements. The objective of this work is to develop a prototype system for deployment in military applications. Phase I will demonstrate the feasibility of the GASMAN approach by monitoring representative toxic gases using a breadboard incorporating three basic elements;

line-locked detection, a multiple-pass absorption cell, and multiplexed laser-diodes. Phase Ii development will lead to a working

SPIRE CORP. ONE PATRIOTS PARK

prototype.

BEDFORD, MA 01730

Phone: (617) 275-6000

Topic#: 92-044

Office: CECOM Contract #:

PI: Anton C. Greenwald, Ph.D.

Title: Epitaxial MOCVD of Thin Film Ceramics for Pyroelectric Detectors

Abstract: Spire proposes to deposit very thin films of lead-titanate by Metal Organic Chemical Vapor Deposition (MOCVD) for use as pyroelectric detectors. A multilayer structure will be fabricated to create an epitaxial, thermally isolated detector element with higher sensitivity than that of the thick films presently being used. MOCVD is an innovative technique which allows sequential heteroepitaxial growth of electrical and thermal insulators, electrically conducting layers, and pyroelectric materials. In Phase I, Spire will use its unique capabilities to deposit (metal)/PbTiO3/CoSi2 on silicon and will measure lead titanate's pyroelectric coefficient. Prototype infrared sensors with integrated FET's would be fabricated in Phase II. Integrated pyroelectric detector arrays made possible by this technology would have greater sensitivity and resolution arrays produced by

existing hybrid fabrication processes.

STANNOUS TECHNOLOGIES CORP.

65 NEW SALEM ST WAKEFIELD, MA 01880

Phone: (617) 246-1119

Topic#: 92-124

ID#: 92HDL-061

ID#: 92MTL-131

ID#: 92MED-043

Office: HDL Contract #:

PI: Pranjivan V. Popat, Ph.D

Title: Extend SERA to Improve Solderability of Components by Controlling the Formation, Growth & Oxidation of Cu-Sn

Intermatallics

Abstract: The proposal describes an innovative R & D program to improve solderability of electronic components by controlling the formation, growth and oxidation of Cu-Sn intermetallic compounds (IMC). The rate and extent of IMC growth depends, among other factors, on the microstructure of the finish plate on the Cu substrate. Differences in microstructure such as porosity, grain boundaries, fissures, delamination and other defects, provide variable paths for solidstate diffusion of Sn and oxidants to Cu substrate. These results in different rates of solderability degradation on aging. Three different types of plating and thickness will be used to produce different types of microstructures. These will include (1) Electroplate at 3 levels of current densities to get 1,3, and 6um thickness. (2) Hot tin dip coating using 3 different coating cycles to produce 1,3, and 6um finish. (3) Solder reflow of electroplated samples. Finish thickness and composition will be measured by XRF and microsection. Solderability at various stages of aging will be measured quantitatively by SERA. "Dip and Look" and wetting balance methods will be used as required. Accelerated aging will be accomplished by (1) Steam aging below 95 degrees C. (2) Controlled heating in inert atmosphere. (3) Anodic oxidation of samples in SERA apparatus. Microstructure will be determined using optical microscopy as well as modern surface science techniques (SEM, TEM, AUGER/ESCA) as needed. This part will be performed at the Center for Materials Characterization, University of North Texas, Denton, Texas.

STARFIRE SYSTEMS, INC.

P. O. BOX 2628

GLENVILLE, NY 12302

Phone: (518) 276-2673

Topic#: 92-134

Office: MTL Contract #:

PI: Dr. Chris Whitmarsh

Title: Engineered, Ceramic Reinforced, Ceramic Matrix Composites

Abstract: A processing route to fiber-reinforced, SiC matrix composites which involves resin transfer molding with a hydridopolycarbosilane preceramic polymer is proposed. This proprietary liquid resin thermosets to a rubbery solid at 200-400 C, permitting fabrication of free-standing, molded parts. Pyrolysis at 1000 C gives near-stoichiometric SiC with 80-90% ceramic yield. Multiple infiltration, cure, and pyrolysis cycles would be used to prepare composites with less than 10% porosity. Test specimens for bend, fracture toughness, and interlaminar shear testing would be produced. The microstructure, mechanical properties, and thermal stability of the composites would be evaluated.

STEROIDS, LTD.

CHICAGO TECHNOLOGY PARK, 2201 WEST CAMPBELL PARK D

CHICAGO, IL 60612 Phone: (312) 421-7158

Topic#: 92-162

Office: MEDICAL Contract #:

PI: Kaiming Liu

Title: Monoclonal Catalytic Antibodies Directed Towards Organophosphorus Agents

Abstract: The hapten molecule CF3(CH3)P(OR)3 which mimics the transition state for hydrolysis of organophosphates such as soman will be synthesized. A protein conjugate will be used for monoclonal catalytic antibody production. A key element of the hapten is that it is a phosphorane (pentacoordinate phosphorus) and contains the CF3PCH3 group. The synthesis depends upon new chemistry which we have discovered for phosphoranes and trifluoromethyl phosphorus compounds. The highly electronegative CF3 mimics an anionic oxygen bond to phosphorus and also stabilizes the phosphorane hapten towards hydrolytic decomposition. This novel hapten represents a closely proximate model for the transition state in organophosphate hydrolytic cleavage and should enable production of a highly effective catalytic antibody for organophosphate neutralization. The project is a collaborative effort between Steroids, Ltd which will do the synthesis, conjugation and haptn-protein ratio determination, and USAMRICD with will generate monoclonal catalytic antibodies and determine their activity towards hydrolytic cleavage of soman.

STRATTON PARK ENGRG CO, INC. 5401 WESTERN AVENUE, SUITE B

BOULDER, CO 80301 Phone: (303) 449-1105 Topic#: 92-144

ID#: 92CRR-002

ID#: 92ETD-052

ID#: 92ARD-030

ID#: 92MED-012

Office: CRREL

Contract #: DACA33-93-C-0006

PI: Robert H. Cormack

Title: An Optical Instrument to Measure Cloud Liquid Water Content and Droplet Spectra

Abstract: In fogs, accretion of supercooled water drops is responsible for icing of power lines and structures. In clouds, the same process causes icing on aircraft. In both cases the concentration and size of liquid water drops, along with their velocity relative to the icing surface, primarily determines the shape and mass of the accreted ice. Better measurements of the concentration and size of water drops in fogs and clouds are needed to improve predictions of ice accretion. In Phase I, we do numerical simulations and perform laboratory tests of a new optical instrument for measuring liquid water content and drop spectra. The new device makes high-resolution measurements of the angular distribution of diffracted light from an 'ensemble' of water drops. Using weighting functions, liquid water content is computed in software. Using inversion techniques, the same set of measurements are then used to compute drop spectra without a priori assumption of the shape of the spectra. The new instruments works without the need to measure air velocity and temperature. In Phase II, we will build a ruggedized, microprocessor-based, field version of the instrument that functions without operator intervention.

SUPERCONDUCTOR TECHNOLOGIES, INC.

460 WARD DR., SUITE F SANTA BARBARA, CA 93111

Phone: (805) 683-7646

Title: HTS Microwave Receiver

Topic#: 92-117 Office: ETDL

Contract #:

PI: Roger J. Forse

Abstract: Superconductor Technologies Inc. (STI) proposes to analyze an 8x8 antenna patch array with feed network at 30 GHz and integrate it with a cryogenic receiver to achieve superior sensitivity and small size in a 2 phase SBIR effort. STI plans to take advantage of current development efforts in cryo-cooled HEMT amplifiers, low loss HTS filters and antennas, and iow phase noise HTS stabilized oscillators.

SURFACE SOLUTIONS, INC. 1727 CONESTOGA ST. BOULDER, CO 80303

Phone: (303) 442-0156

Title: Advanced Materials/Coatings for Gun Barrels

Topic#: 92-003 Office: ARDEC

Contract #:

PI: John Marshall III

Abstract: The application of advanced barrel coatings to provide extended erosion and wear life with high performance ammunition for existing and proposed weapons systems has been limited by the available process technologies capable of applying the required/desired coatings. Electroplating, Chemical Vapor Deposition (CVD), and Physical Vapor Deposition (PVD) have all been attempted with varying degrees of success. Desired coating materials are best applied using PVD, however PVD has suffered from geometric constraints due to a line-of-sight requirement from target to substrate. SURFACE SOLUTIONS (SSI) has developed a new form of PVD deposition, DC Linear Magnetron Sputtering (LMS), capable of uniform deposition inside a gun barrel with a length to diameter ratio exceeding 100: 1. SSI believes that LMS will be capable of uniformly depositing high-temperature, corrosion resistant materials such as tantalum, alloys of tantalum, molybdenum, niobium, etc. LMS is a line-of-sight PVD process whereby the target(coating material) is tubular and is aligned coaxially with the substrate (gun barrel). Sputtering occurs radially and uniformly down the entire length of the target and requires no external magnets to contain the plasma. The required uniform magnetic field is generated electrically and is the basis of SSI's LMS process.

SYMBIOTECH, INC. 8 FAIRFIELD BLVD. WALLINGFORD, CT 06492

Phone: (203) 284-7465 Title: Toxin Prophylaxis Topic#: 92-166 Office: MEDICAL

Contract #:

PI: Edward M. Davis, Ph.D.

Abstract: A novel approach for developing prophylactic agents against ricin is proposed. During Phase I, a prototype of the

proposed prophylactic will be synthesized and tested for its ability to detoxify ricin. The work aims to demonstrate feasibility of the proposed approach. It is anticipated that the proposed approach may be used to develop broad spectrum protection against toxin and biological warfare agents.

SYSTEM ENGINEERING TECHNOLOGY SERV. 478 WEST HAMILTON AVENUE, SUITE 284

CAMPBELL, CA 95008

Phone: (408) 241-0860

Title: Autonomous Satellite Location Using a Hand-Held Theodolite

Topic#: 92-034 Office: CECOM

Contract #: PI: David M. Theobold ID#: 92SS -001

ID#: 92CRD-005

ID#: 92TOP-057

Abstract: A hand-held theodolite shall be developed which has the capability to autonomously locate satellites, given multiple satellite ephermerides, date, time, and ground terminal location. The theodolite shall provide a local reference of azimuth and elevation angles via electronic sensors, calculate antenna pointing angles for the time during which the satellite is in view, and display the times for which a satellite will be visible. The first phase of this development shall provide detailed system requirements, functional specifications, and a preliminary design approach for the theodolite hardware and software. Brasshoard evaluation of the key sensor technologies and processing algorithms shall also be performed in this phase.

SYSTEMS & PROCESSES ENGINEERING CORP.

1406 SMITH ROAD AUSTIN, TX 78721

Phone: (512) 385-2067

Topic#: 92-047

Office: CRDEC Contract #:

PI: Dr. Robert C. Chin

Title: Early Warning and Monitoring of Dangerous Biological Materials by Phase-Resolved Fluorescence Spectroscopy

Abstract: Systems & Processes Engineering Corp. (SPEC) has developed a Phase Resolved Fluorescence Spectroscopy (PRFS) biosensor which is capable of detecting and classifying biological materials. SPEC's PRFS biosensor uses lifetime fluorescence to provide: (1) enhanced sensitivity to structural differences associated with various classes and species of bacteria, and (2) a means to reduce fluorescence interference from other bacterial fluorophores. SPEC has shown that lifetime determination by phase and frequency can achieve picosecond resolution. This resolution is sufficient for discriminating between bacterial species and classes. PRFS is based on the physical phenomena occurring when a fluorescent bacteria is excited with sinusoidally modulated light, inducing a phase shifted emission corresponding to the time lag between absorption and fluorescence. These "phase" fluorescence parameters are used to generate Excitation Emission Frequency Arrays (EEFAs) for use in detecting, classifying and monitoring concentration changes of potentially dangerous bacterial/tiological materials. In Phase I, SPEC will: (1) develop a PRFS Biosensor System specification; (2) design a signal processing scheme; (3) perform PRFS biosensor laboratory investigations and demonstrations; (4) design a miniaturized PRFS Biosensor, incorporated Multi-Chip Module (MCM) technology and leading to a Phase II PRFS Biosensor prototype, which will be delivered to the Army for field evaluation.

SYSTEMS ENGINEERING ASSOC. (SEA CORP)

ADMIRAL'S GATE TOWER,5TH FLOOR, 221 THIRD STREET NEWPORT, RI 02840

Phone: (401) 847-2260

Topic#: 92-149 Office: TOP

Contract #:

PI: Michael G. Fisk

Title: Develop Environmental Monitoring Capability for Integrating Recent Technological Advancements into a Hybrid Artificial Neural Network System

Abstract: We propose to develop an Environmental Monitoring System by integrating various technologies to create a hybrid artificial neural network system. By functionally decomposing the requirements of environmental monitoring we can apply emerging technologies to fulfill these modularized requirements. Ten (10) years of experience indicate that the technologies directly applicable to specific requirements are: Artificial Neural Networks, Fuzzy Logic, Artificial Intelligence, and Object-oriented Database Management Systems. We feel that to successfully develop a system using such diverse technologies. the major technical problem is the integration of these modules. By functionally decomposing the requirement the hybrid system can be build in a modular, object oriented manner. This ensures that the best, effective technology has been applied to the respective requirement. Any new technological advances can then be easily integrated into the hybrid system. Scientists presently involved in environmental research, ANN, AI, Fuzzy Logic, data comparison, and advanced system engineering will

be used. These personnel will apply existing designs which successfully resolved similar problems in their respective technologies, minimizing risk of completion while leveraging available funds. GEOPHYSICS, a commercial environmental firm, has expressed a strong desire to use and commercialize the Environmental monitoring System to support their own business and profession.

SYSTEMS ENGINEERING GROUP, INC. 9841 BROKEN LAND PARKWAY #214

COLUMBIA, MD 21046 Phone: (410) 381-8740 Office: SDC
Contract #:

Topic#: 92-176

ID#: 92SDC-079

ID#: 92AVS-071

ID#: 92ARI-025

PI: Robert Bulk

Title: Real-Time Drag Determination for Kwajalein Missile Range (KMR) Tracking Development

Abstract: The primary goal of the Phase I effort is to develop an algorithm and determine its feasibility, for Kwajalein Radars, to estimate and correct for drag acceleration on reentry objects. In developing the design an evaluation of both KMR radar tracking performance and reentry object trajectories will be performed to determine the performance requirements of the drag estimation and correction algorithm. Using these requirements an algorithm will be designed that recursively estimates the aerodynamic characteristics for an object and then uses this information to predict the location of the object at the next update. This design will be analyzed to determine its performance on specific KMR Radars (ALCOR, MMW, FPQ-19). The result of Phase I will indicate the effectiveness of the algorithm and its applicability to KMR (and other test range) tracking needs. Phase II will validate the algorithm using simulation and real KMR data and then deliver the algorithm. Phase II will also include an assessment of the commercial applications for the tracking filter.

SYSTEMS TECHNOLOGY, INC. 13766 S. HAWTHORNE BLVD. HAWTHORNE, CA 90250 Phone: (310) 679-2281

Title: Reconfigurable Flight Controls

Topic#: 92-013 Office: AVSCOM

Contract #:

PI: David G. Mitchell

Abstract: For the military helicopter in combat, the loss of a control surface under any circumstance usually translates into either an emergency landing or complete loss of control. A critical factor in determining the pilot's chance of maintaining control is the level of redundancy in control effectors, or more correctly, the lack of such redundancy. Unlike fixed-wing aircraft, the control effectors on the conventional helicopter are integrated, so that, in the event of a failure, the pilot's task of determining the proper control strategies and continuing to a safe landing is extremely difficult. There is a potential for assisting the pilot on future designs by implementing reconfigurable flight control system (RFCS) algorithms. Such approaches are showing promise for fixed-wing aircraft; their application to helicopters, however, requires a recognition of the distinct differences between fixed- and rotary-wing aircraft controls and responses. This proposal presents an approach to the subject starting with demonstrating the feasibility of producing a controllable impaired aircraft. If funded, the Phase I work will examine all possible failures for a current helicopter, focusing on one example critical failure. For this failure the feasible flight control laws to provide Level 3 (or better) flying qualities will be developed.

SYUKHTUN RESEARCH 2740 WILLIAMS WAY SANTA BARBARA, CA 93105

Phone: (805) 682-2835

Topic#: 93-155

Office: ARI
Contract #:
PI: Jim Kornell

Title: Training-based Requirements for Semi-Automated Forces

Abstract: "The training of soldiers, leaders and units to win in combat will remain the Army's single most important task"-US Army Fiscal Year 1993 Posture Statement (quoted in Military Review, May 1992). The Department of Defense spends an estimated \$5 billion per year on training. Simulations can aid training, but there is no reliable method for generating simulation requirement from training objectives, nor are there productive automated aids. Yet people perform the task, some with high degrees of expertise. We propose research to develop a well defined method for performing the task. We also propose to construct a knowledge based system to support portions of the task. In combination, this can be expected to improve efficiency and effectiveness in the training-objective-to-performance-requirement task.

TE TECHNOLOGY, INC. 10345 CHERRY BEND ROAD TRAVERSE CITY, MI 49684

Topic#: 92-077 Office: TACOM Contract #:

ID#: 92TAC-012

ID#: 92TAC-138

ID#: 92TAC-145

Phone: (616) 929-3966

PI: Richard J. Buist Title: Thermoelectric Thick Film Technology for Application onto Substrates .

Abstract: New advances in Ultra-Supersonic Plasma-Spray technologies present new opportunities for creating a superior thermoelectric (TE) thick-film technology. Via extremely rapid solidification, these processes can maintain the purity and complex stoichiometry of multi-component TE alloy. This process will eliminate the use of solders yielding unprecedented ruggedness and low cost. Unlike sputtering and other deposition processes which require high vacuum, ultra-clean systems and hours to build up a few microinches, the proposed process can be operated in open air and deposit several thousand microinches in a single pass. These thick-film layers will have the capacity to provide practical cooling in the presence of significant heat loads. TE Technology, Inc. will draw on its experience and success on previous SBIR programs using the wide range of TE material compositions developed under its Navy SBIR program. Forty different N and P-type films will be designed, fabricated and tested to establish the feasibility of the plasma-spray, thick-film technology. Testing will include full characterization of all TE transport parameters. Actual cooling performance tests will also be made including the use of temperature sensitive, liquid crystal films to visually observe temperature gradients under operation.

TECHNICAL SOLUTIONS, INC.

P.O. BOX 1148

MESILLA PARK, NM 88047

Phone: (505) 524-2154

Title: Generation of Terrain Databases for VCDD

Topic#: 92-088 Office: TACOM Contract #:

PI: Dr. Alton L. Gilbert

Abstract: The Defense Mapping Agency (DMA) is the primary provider of terrain data to the military services. Other agencies, such as the US Army Engineering Topographical Laboratory, provide terrain data products as well. DMA currently provides Digital Terrain Elevation Data (DTED) and Interim Terrain Data (ITD) as the high resolution terrain data products usable by maneuver forces. Also emerging, but in very limited data sets, is the follow on to ITD called the Tactical Terrain Database (TTD). The generation of terrain data for plan-view and perspective-view display from the DMA data will vary in complexity depending upon the display requirements, including resolution; the source and resolution of the data; and the icons/symbols added to the display to meet a military planning, control, or training objective. US Army TACOM, in developing Soldier-Machine Interfaces (SMI), has developed the Vetronics Crew Display Demonstrator (VCDD) to display data to the surrogate crew member and evaluate data presentation requirements, data presentation efficiency (human factors), and control mechanisms. The VCDD requires new and additional terrain data for meaningful evaluation of SMI, which is the purpose of this proposal.

TECHNICAL SOLUTIONS, INC.

P.O. BOX 1148

MESILLA PARK, NM 88047

Phone: (505) 524-2154

Topic#: 92-089 Office: TACOM

Contract #:

PI: Dr. Alton L. Gilbert

Title: Embedded Training for ITCS

Abstract: The US Army is continually faced with the task of providing the crew members of weapon systems with realistic, high-quality training. This training must be based on known principles of instructional design, yet meet the needs of specific weapon system based training issues. The problem of providing quality training compounded by a reduction in force, resulting in smaller crews. There will also be few trainers, training developers, and smaller support staff for production of training materials. In addition, training production costs are rising. The Crew size reductions in Army weapons systems have been made possible by Intelligent functions such as Decision Support Systems/Decision Aids which perform operations normally associated with crew members. These cooperative, computer-based systems will require a different level of training than was previously provided. Decision Support Systems are now being developed for armor and artillery, and these systems will require Embedded Training for all crew members. U.S. Army TACOM has developed a Vetronics Crew Display Demonstrator (VCDD) for development and evaluation of concepts relating to future vehicle-based weapons systems requirements. A major focus of this effort are the requirements for the Integrated Two-man Crew Station (ITCS). The ITCS architecture will integrate the physical, electronic, intelligent subsystems, training and control functions into a fieldable configuration. The effort proposed here is

directed at the Embedded Training component.

TECHNO-SCIENCES, INC.

7833 WALKER DRIVE, SUITE 620 GREENBELT, MD 20770

Phone: (301) 345-0375

Title: ProtoFlex Multibody Dynamical Analysis System

Topic#: 92-082

Office: TACOM Contract #:

ID#: 92TAC-054

ID#: 92NAT-026

ID#: 92SS -020

ID#: 92SDC-078

PI: William Bennett

Abstract: The objective of the proposed work is the development of a CAD system for the design and analysis of multibody dynamical systems with flexible substructures. We shall start with multibody modeling formalisms developed and used by TSI for large scale flexible structures and combine these with the PROTOFLEX system developed by the Grumman Corp. The project will involve a collaboration between TSI and Grumman to achieve the final product.

TECHNOLOGY INTERNATIONAL, INC.

429W. AIRLINE HIGHWAY, SUITE S LAPLACE, LA 70068

Phone: (504) 652-1127 Title: Ultrasonic Dehydration for Dental Liquid Meals Topic#: 92-066

Office: NATICK Contract #:

PI: Mr. Sherman Richardson

Abstract: Technology International Incorporated (TII) will develop, design, fabricate, and test an ultrasonic dehydration process that can be used to dry ingredients in as little as 10 seconds, to produce ingredients with excellent quality for dental liquid meals, high calorie compact food modules, and other ration applications using a relatively inexpensive dehydration process. The energy cost will be far less than the freeze drying method currently being used to produce the same items. The ability to rehydrate and to retain the nutrients would be greatly improved due to the extremely short residence time at high temperatures. The Phase I work will involve identifying the ingredients most suitable for ultrasonic drying and establishing the range of process parameters applicable to them. Also, a bench test will be performed to validate the range and assure compatibility of the ingredients with ultrasonic drying.

TORREY SCIENCE & TECHNOLOGY CORP.

9725 SCRANTON ROAD, SUITE 100 SAN DIEGO, CA 92121

Phone: (619) 552-1052

Title: Tracking & Reporting System (TRS)

Topic#: 92-030

Office: CECOM Contract #:

PI: Thomas S. Seay

Abstract: A surveillance tracking and report system (TRS) capable of self position determination combined with a means of communicating its position through satellite data links to a tactical monitoring and control center would provide valuable assistance to counternarcotics and other special operations forces. A TRS system is proposed which would utilize small (shirt-pocket size or less), light weight, low power consumption terminals with omni-directional antennas. The system should provide position location to better than 25 meters anywhere over land or ocean. Terminals would be capable of 2-way data communications, would be inexpensive (many may be lost or non-recoverable) and would have a battery life goal of 36 to 48 hours minimum. Such a system would also include a second version of the terminal for use by law enforcement officers. This terminal would contain a small readout LCD display and a keyboard for sending short messages in the field or to the tactical control and monitoring center. The officer's terminal would have an emergency button to immediately transmit an officer-in-trouble message with a location.

TOYON RESEARCH CORP.

SUITE A, 75 AERO CAMINO GOLETA, CA 93117

Phone: (805) 968-6787

Topic#: 92-176 Office: SDC

Contract #:

PI: A. Vincent Mrstik

Title: Real-Time Drag Determination for Kwajalein Missile Range (KMR) Tracking Development

Abstract: Although the wideband, narrow beam radars at KMR are capable of tracking well-behaved targets during reentry, the radars do not reliably maintain track on targets whose drag profiles deviate significantly from a priori predictions. The objective

of this effort is to determine the feasibility of augmenting existing tracking filters for the KMR radars to allow real-time computation, correction, ad prediction of reentry drag experienced by objects in track. The existing KMR track filters attempt to compensate for drag excursions by increasing the process noise when predictions are observed to deviate from the measurements. Rather than simply increase the process noise, our proposed approach is to use the observed deviations between the predicted and observed measurements to modify/improve on our a priori estimate of vehicle drag profile. Our approach can be described as one of using drag as an additional state variable which is estimated in real time using the predictor/corrector processes of Kalman filtering. A digital simulation will be used to refine our new algorithm and to compare its performance with the existing KMR track filters for a wide spectrum of drag profiles. Feasibility of the revised tracker will be evaluated in terms of its ease of implementation in the existing real-time programs of the KMR radars, and the ability of the existing computing hardware to absorb the additional computational load.

TPL, INC. 3754 HAWKINS NE

ALBUQUERQUE, NM 87109

Phone: (505) 345-5668

Title: TNAZ Formulations with Enhanced Energetic Output

Topic#: 92-002

02 ID#: 92ARD-041

ID#: 92ARD-042

ID#: 92ETD-045

Office: ARDEC Contract #:

PI: Dr. Robert D. Chapman

Abstract: 1,3,3-Trinitroazetidine (TNAZ) exhibits some unusual and potentially valuable properties for explosives applications. Objectives of Phase I program include the selection of candidate energetic formulations using computational methods. A technical prerequisite to performing valid computations of energetic performance of composition is a basic understanding of their physical properties. In the case of binary formulation, this must include the parameters of solid-state solutions. Performance calculations of formulations of greatest theoretical interest (following characterization of phase equilibria) will be conducted. ARDEC's TIGER PC will be of greatest utility in this project for determining thermochemical and hydrodynamic properties of formulations. The most theoretically promising candidates will be formulated in small batches, and formal thermal stability and sensitivity testing will be conducted.

TPL, INC. 3754 HAWKINS NE ALBUQUERQUE, NM 87109

Phone: (505) 345-5668

Title: Development of Non-Lethal Weapon Mechanisms

Topic#: 92-004

Office: ARDEC Contract #: PI: H.M. Stoller

Abstract: There is growing interest in non-lethal weapons. Minimization of U.S. forces and non-combatant casualties are primary personnel considerations. Other targets of interest include sensors, electronic systems, thermal sights, missile seekers, missile guidance, and TV's. Previous non-lethal weapon development has emphasized personnel targets, riots, and hostage situations. Civilian applications included kinetic energy weapons and electrical shock devices. Military developments have included riot control (chemical) agents and kinetic energy weapons. These weapon concepts have limitations and/or restrictions applied to combat situations. New concepts are needed for personnel targets. This innovation need is emphasized for consideration of electronic, electrooptic, and electronic targets. Acoustic, optical and electromagnetic effects have the greatest potential for multi-target uses in broad area applications. Enhancement techniques have been identified particularly for optical and EMP effects. Application scenarios will be defined. Non-lethal weapons concepts will be identified and quantified. Incapacitation requirements will be established. Interaction effectiveness of selected non-lethal mechanisms with selected targets will be predicted. Based on a relative merit index, recommendations will be made for Phase II development.

TPL, INC.
3754 HAWKINS NE

ALBUQUERQUE, NM 87109

Phone: (505) 345-5668

Topic#: 92-109

Office: ETDL Contract #:

PI: Dr. Richard W. Brotzman,

Title: High Energy Density Polymer Capacitor Development

Abstract: The development of low loss, high energy/high power density storage materials is important for Army applications ranging from capacitors to pulse power component technologies. To maximize the energy density of a high energy density polymer capacitor, not only must the constituent polymer material properties be optimized, but the best capacitor

fabrication/production techniques must be employed. Adhesion of vapor deposited aluminum as well as the breakdown voltages of a number of polymer films have been markedly increased after these polymer films have been briefly exposed to various low pressure, low temperature gas plasmas. Initial evaluations on prototypes, spirally wound polymer capacitors (capacitor was briefly exposed to a 96% CF4/4% 02 gas plasma) have shown that breakdown voltage can be increased by a factor of 2-4. Why does plasma processing significantly improve breakdown strength, and what are the optimum plasma processing conditions that produce these improvements without causing any undesirable effects on other bulk properties of the capacitor polymer? TPL will develop and demonstrate various spirally wound, capacitors based on specific ETDL inventions/patents which have already been prototyped and successfully demonstrated. Selected polymer films and capacitors will be fabricated and subjected to plasma treatments to identify both the optimum processing conditions and the fundamental basis for the dielectric breakdown improvements. TPL will identify specific military and commercial candidate applications and users for the optimized technology.

TPL, INC. 3754 HAWKINS NE

ALBUQUERQUE, NM 87109 Phone: (505) 345-5668

Title: Reuse of Nitrocellulose-Based Propellants in Industrial Processes

Abstract: The DoD is faced with a large and growing inventory of surplus and obsolete propellants, currently in excess of 75,000 short tons. Environmental restrictions are significantly increasing incineration costs, with pr. hibition a potential occurrence. A need clists to develop an environmentally acceptable means of disposal. High temperature industrial processes offer one such opportunity. TPL is active in the demilitarization of explosives and propellants for both commercial and military applications. Concurrently, TPL is developing industrial processes which employ propellants as a fast release, gas source. This expertise provides the capability to develop an industrial process use for surplus propellants. Potential industrial processes will be identified and requirements compiled. Related end use properties of surplus propellants will be determined and matched with possible applications. Critical issues regarding the specific end use will be defined. Feasibility experiments to evaluate these issues will be performed. Alternate uses will be evaluated. Phase II recommendations will be formulated.

TRF TECHNOLOGIES, INC. 701 SE SALMON REDMOND, OR 97756

Phone: (503) 923-0804

Title: Miniature Rugged RF Filters and Low Power Oscillators

Topic#: 92-125 Office: HDL Contract #:

Topic#: 92-140

PI: H.M. Stoller

Office: CERL

Contract #:

ID#: 9. CER-029

ID#: 92HDL-073

ID#. 92MT1.-212

PI: Kenneth Lakin

Abstract: Future artillery launched systems will take advantage of high levels of circuit integration to achieve sophisticated signal processing capabilities in a small rugged package. Two areas that do not presently lend themselves to miniaturization are filters and oscillators. This project will develop miniature rugged RF circuits using thin film microwave acoustic bulk wave resonators and filters and a new rugged multi-chip module concept. The thin film resonator technology offers significant size reductions and high performance compared to ceramic or other conventional frequency control technologies. The Phase I tasks will demonstrate a high performance narrow band filter for use in fuzing and GPS telemetry application and design a low power oscillator using high performance microwave acoustic resonators to control oscillator frequency. The special issue of circuit packaging for the high G environment will be investigated and a rugged simple multi-chip module concept will be demonstrated in Phase I with more complex circuits fabricated during Phase II. Potential commercial applications include personal communications systems and remote environmental sensor telemetry systems.

TRITON SYSTEMS, INC. 184 CEDAR HILL STREET MARLBOROUGH, MA 01752

Phone: (508) 263-6636

Topic#: 92-134 Office: MT1

Contract #:

PI R. Ross Haghighat

Title: Modified Resin Transfer Molding for Fiber Reinforced Ceramic Matrix Composites

Abstract: The proposed Phase I SBIR program will demonstrate a simple, reproducible, cost-effective and near net-shape approach to "transfer molding" of advanced fiber reinforced ceramic matrix composites using a revolutionary and entirely new process developed by scientists at Triton Systems, Inc. We have dready successfully demonstrated the feasibility of this unique

t ocess. The proposed effort will expand this technology to better understand it's processing parameters and optimize this technique in terms of mechanical, physical and thermal performance of the final composite. The result will be complex-shaped, fiber reinforced CMC's which are designed to outperform CMC's processed by alternative processes. Our approach is based on "Resin Transfer Molding" (RTM) of organic matrix composites (OMC) which has been in use for several decades as a lower-cost alternative to autoclave curing and other labor and capital intensive processes used in high performance applications. The main advantages of this process are it's ability to deliver near-net-shape complex shapes in high volume and low cost with good surface topography. Other advantages include flexibility in tooling and materials, easy part consolidation through molded-in parts and fittings, fast production cycles and less than 2 percent voids. The Phase I program will optimize the process conditions, fabricate and characterize several fiber reinforced CMC specimens using a "Ceramic Transfer Molding" technique. The Phase II program will optimize the process for maximum strength, toughness and high temperature performance.

UBC, INC.

8405-A BENJAMINE RD. TAMPA, FL 33634

Phone: (813) 884-6076

Title: Low Cost, Polarization Diverse MMW Integrated Antenna/Transceiver

Topic#: 92-058

ID#: 92MIC-112

ID#: 92ETD-047

ID#: 92ARD-019

Office: MICOM Contract #:

PI: Patrick E. Crane

Abstract: A unique dual polarized monopulse sensor configuration providing full compatibility with MLRS, Longbow, but also providing a means of extending polarimetry to low cost systems without sacrificing performance, is utilized to propose a nearly universal sensor head appropriate to both low and high performance systems. Extremely high levels of transmit-to-receive isolation are achieved while eliminating all RF components from the assembly.

ULTRALIFE BATTERIES, INC.

P.O. BOX 622

NEWARK, NY 14513

Phone: (315) 332-7100

Title: High Energy Density, Ultra-safe, Li-Mn02 Pouch Cell

Topic#: 92-114

Office: ETDL Contract #:

PI: Dr. M.L. Gopikanth

Abstract: The Army is one of the major users of Li batteries, as they are reliable, have high energy density and shelf life. Present lithium systems are not safe and require special care and caution by the user. An Ultra-safe, high rate, high energy density Li/Mn02 cell packaged in soft pouch material is being proposed for development of BA-5590/U cell. This new system is safe, low cost and has potential to replace all of the present primary cells/batteries used by the Army. A Phase I program to prove the feasibility of BA-5590/U cell with Li/Mn02 chemistry and U.B.I.'s patented safety separator, and package with a soft pouch material is proposed. During this program, work will focus on hermetic sealing, manufacturing process and fabrication of high rate cathode. Also, assembled cells will be evaluated for electrical performance and safety. U.B.I is uniquely qualified to conduct this program, as we have in place manufacturing process necessary for manufacture of Li/Mn02 batteries and owns a safety-shutdown separator process. During Phase II, U.B.I. will fabricate BA-5590/U cells and assemble them in to a battery. then evaluate battery for electrical performance and prove use of Li/MN02 chemistry and soft pouch packaging material to replace present chemistry. An Ultra-safe, high rate, high energy density battery with low cost is desirable to Army to reduce their cost without sacrificing safety, reliability and performance.

U'.TRAMET 12173 MONTAGUE ST.

PACOIMA, CA 91331

Phone: (818) 899-0236

Title: Advanced Materials and Fabrication Processes for Gun Barrels

Topic#: 92-003 Office: ARDEC

Contract #:

PI: Andrew J. Sherman

Abstract: High rate of fire, high velocity, medium-caliber (20-, 25-, and 30-mm) gun barrels have been used extensively by U.S. armed forces over the past 20 years. A major problem with such systems is that the barrel must be replaced far too often due to excessive wear and corrosion at the breech end, which limits weapons system accuracy and dramatically accelerates with extended high-rate-of-fire bursts and/or higher energy propellants. In this Phase I program, Ultramet proposes a baseline solution to this generic problem through the use of rhenium inserts. Refractory metals and alloys and fabrication process will be evaluated for cost, performance, and compatibility improvements over the baseline rhenium and tantalum/tungsten (Ta-10W)

alloys. A rhenium insert will be fabricated for actual gun performance validation to provide a baseline high coatings will be fabricated and subjected to wear and erosion testing using verified methods for comparison to current stellate and chrome-plated steel barrels and the baseline rhenium and Ta-10W materials.

ULTRAMET 12173 MONTAGUE STREET PACOIMA, CA 91331

Phone: (818) 899-0236

Title: Solid Rocket Booster (SRB)-Based Starter System

Topic#: 92-053

Office: MICOM
Contract #:

PI: Andrew J. Sherman

ID#: 92MIC-065

ID#: 92AVS-111

ID#: 92SW -021

Abstract: In this Phase I program, Ultramet proposes to demonstrate the feasibility of using a modified solid rocket booster (SRB) to provide the hot gas cranking and ignition source for starting a small turbojet sustainer engine, in addition to boost propulsion. This SRB-based starting system would replace the pyrotechnic starter cartridge currently used as a gas generator and ignition source for the sustainer engine, thereby reducing both the cost and weight of the total system without sacrificing performance. The primary difficulties involved are fivefold: reducing the 5000 R, 1500-psia SRB flame to conditions that will not damage the turbine rotor; maintaining sufficient gas velocity, pressure, and mass flow to the impingement nozzles to successfully start the engine, taking into consideration pressure losses due to gas cooling and frictional effects; demonstrating materials of construction capable of surviving the erosive, high temperature propellant gas; modifying the SRB to account for pressure and heat losses due to gas diversion; and possibly filtering carbon, alumina, and other condensible matter from the hot gas stream before its introduction into the turbine section. This program will demonstrate a workable design capable of surmounting these obstacles through theoretical calculations and hardware demonstration of a SRB-based starter system.

UNISTRY ASSOC., INC. 129 N. EAGLE ROAD HAVERTOWN, PA 19083

Phone: (904) 392-7572

Title: Advanced Wave Rotor, Fluid-Fluid Energy Exchanger

Topic#: 92-020 Office: AVSCOM Contract #: PI: Dr. William E. Lear

Abstract: A gas turbine engine concept is proposed that provides the technical innovation needed to increase specific power, thermal efficiency, and overall performance and reliability without need for development in material technologies. This advanced fluid-fluid energy exchange device can serve as the core of high performance gas generators to meet a variety of land/air applications. This unique system is based on unsteady flow phenomena which produces the functional equivalent of a coupled gas turbine and compressor by continuous expansion of one gas stream while extracting energy which is used to compress another gas stream. The wave processes occur within one rotor which features canted blades that are alternately exposed to hot and cold fluids resulting in material temperatures much lower than peak cycle values. The proposed program features the modification of an existing CFD code, that has been developed to investigate the wave processes within a rotor cell, to include blade angel and cell area change effects, and exercise the code to determine optimum rotor and performance characteristics suitable for laboratory test rig. A unique concept will be defined for a cold flow laboratory test rig that features

UNITED SIGNALS & SYSTEMS, INC. P.O. BOX 3435 RANCO PALOS VERDE, CA 90274

Phone: (310) 838-3369

gases.

Title: Noise Reduction Techniques Using Higher-Order Spectra

Topic#: 92-041

Office: CECOM Contract #: PI: Dr. M. Shiva

Abstract: This project will address the development of noise reduction and narrowband/widehand interference cancellation techniques that are needed to support widehand communication systems. Underscoring this effort are advanced signal processing algorithms based on higher-order cumulants or spectra (HOS) techniques, such as the trispectrum. HOS-based techniques have shown great promise in terms of accuracy, robustness and performance improvement over autocorrelation (or power spectrum) -based methods in the face of statistical uncertainties of communication environments. Consequently, the development and

flexibility, modularization, ability to accommodate test diagnostics, and be economical. Moreover, the design will allow for first and second stages of the expansion/compression processes to be investigated without need for high temperature combustor

application of HOS-based algorithms to noise and interference reduction problems that arise in wideband communications has become timely. Four directions are covered during this exploratory development: (1) utilization of HOS-based Time-Frequency Distributions for the identification and cancellation of narrowband/wideband interferences; (2) development of HOS-based methods for the suppression of additive Gaussian noise (generally colored and possibly spatially correlated); (3) evaluation of the performance of the HOS-based methods against varying SNRs, SIRs, as well as different noise/interference characteristics: (4) development of a Reduced Complexity Algorithmic Architecture (RCA2) and assessment of algorithmic complexity.

UTILITY DEVELOPMENT CORP. 112 NAYLON AVENUE LIVINGSTON, NJ 07039

Phone: (201) 994-4334

Title: Latex Coated Fabric for CB Protective Applications

Topic#: 92-132

ID#: 92MTTL-127

ID#: 92TAC-137

ID#: 92ETD-002

Office: MTL Contract #: PI: Harry S. Katz

Abstract: During the Phase I program, we propose to develop latex coated cloth that will have good permeation barrier and decontamination characteristics, with ease of processing and capability of high volume production at low cost. We will coat fabrics with various types of latex materials. We will also study various defoamers and fillers in the latex materials to improve the performance of latex coatings. These coated fabrics will be tested for adhesion between the latex layer and fabric. Tests will also be conducted after long-term exposure to a QUV Weatherometer. Chemical agent testing will help us to determine the best materials for producing masks, hoods, and garments. During Phase II of this program, we will develop and demonstrate a continuous process for production of materials demonstrated in the Phase I program. We will demonstrate large-scale producibility of BCC using the latex process by producing sample rolls of materials meeting MIL-C-51251A and MIL-C-12189H not less than 30 inches in width. We will also produce samples of prototype garments.

VEXCEL CORP. 2477 55TH STREET BOULDER, CO 80301 Phone: (303) 444-0094

Phone: (393) 444-0094
Title: Image-Based Terrain Database Generator for Simulation

Topic#: 92-088 Office: TACOM Contract #:

PI: James Curlander

Abstract: Vexcel Corporation together with Hughes Training, Inc. Advanced Systems Facility proposes a multi-source terrain database generator for the Vetronics Crew Display Demonstrator system. The system would incorporate information from existing VCDD databases, mapping products, and new imagery to produce digital terrain models and environments for combat vehicle simulation. The system would be hosted on a high speed graphics workstation such as the Silicon Graphics Iris family of computers, to take advantage of the state of the art in display and visualization technology. A Unix / C software environment would be used, and the systems interface would be integrated into the VCDD interface development software. Also the VCDD Systat software capabilities would be used. The resulting prototype will prove feasibility of image-based extensions and enhancements to the current VCDD terrain database simulation capabilities.

VHDL TECHNOLOGY GROUP 974 MARCON BLVD., SUITE 260 ALLENTOWN, PA 18103

Phone: (215) 266-9791

Topic#: 92-112

Office: ETDL Contract #:

PI: William D. Billowitch

Title: Very High Speed Integrated Circuit (VHSIC) Hardware Descriptive Language (VHDL) Package Library/Common Packages

Abstract: While there are already a number of packages available either in the public domain or commercially, there are numerous classifications of design techniques and areas in which additional VHDL packages would benefit the industry. These include: (a) Back-Annotation, (b) Math routines, (c) Floating-Point, (d) Digital Signal Processing Functions and (e) Abstract Queuing. In Phase I of the proposed work, a survey of the most needed packages will be conducted and a specification will be written to further develop the packages under Phase II. Therefore the goals are: 1. Develop an industry survey asking users to describe the features in any of the packages mentioned above and gain feedback on requirements for packages other than those identified based upon the industry's needs. 2. Develop a draft specification for each package. In those cases where the functionality can be so well defined as to specify the procedural interfaces, this specification may be as detailed as a VHDL

package declaration, or alternatively the specification may describe the subprograms and types needed in the abstract and leave the detailed design for Phase II. This effort will be accomplished in coordination with the efforts of the IEEE and the industry with the goal of providing VHDL packages not readily available elsewhere.

YANKEE SCIENTIFIC, INC. 93 WEST STREET

MEDFIELD, MA 02052

Phone: (508) 359-7999

Title: Nonpowered Instant Water Heater

Topic#: 92-070

Office: NATICK

Contract #:

PI: Dr. Eric C. Guyer

ID#: 92NAT-095

Abstract: The development of a non-powered, instantaneous, pressurized supply water heater for field use will developed based on the use of established R-tube diesel fuel burner technology and one of several possible two-phase direct steam-water pumping concepts. The direct steam water pumping concepts to be considered are a "chugger" pump which has been recently studied at Massachusetts Institute of Technology, the condensing ejector pump which as been used in a variety of industrial applications, and the pulse pump which is commonly used in food preparation appliances. All concepts for providing the pumping action are based on the use of atmospheric or low pressure steam as the motive force for pumping and involve simple mechanical arrangements with no moving parts, except for possible check valves. The vest direct two-phase pump type for application to the Army requirements will be selected. An overall engineering design will be established and a proof of concept device will be built and tested. The proposed system has a probability of successful development since it is based on the combination of existing burner and two-phase pumping technology.

4 CYCLE TECHNOLOGIES, INC. ADVANCED MATERIALS CORP. AF Topic#: 92-153 ARMY Topic#: 92-035 ADVANCED MECHANICAL TECHNOLOGY, INC. **4D VIDEO** ARMY Topic#: 92-018 ARMY Topic#: 92-070 ADVANCED OPTICAL SYSTEMS, INC. NAVY Topic#: 92-077 ADVANCED PHOTONIX, INC. A & D ASSOC. SDIO Topic#: 92-014 DARPA Topic#: 92-023 ADVANCED PROJECTS RESEARCH, INC. NAVY Topic#: 92-177 SDIO Topic#: 92-002 ABTECH CORP. ADVANCED SCIENTIFIC CONCEPTS, INC. ARMY Topic#: 92-154 ARMY Topic#: 92-022 DARPA Topic#: 92-088 ACCESS DYNAMICS, INC. SDIO Topic#: 92-003 DARPA Topic#: 92-205 SDIO Topic#: 92-003 ACCURATE AUTOMATION CORP. ADVANCED SURFACE TECHNOLOGIES, INC. Topic#: 92-058 DARPA Topic#: 92-065 ΑF Topic#: 92-178 ADVANCED SYSTEM TECHNOLOGIES, INC. NAVY Topic#: 92-153 ACCUWAVE CORP. ARMY Topic#: 92-032 NAVY Topic#: 92-085 DARPA Topic#: 92-041 ADVANCED TECHNOLOGY AND RESEARCH CO ACT RESEARCH CORP. ARMY Topic#: 92-060 SDIO Topic#: 92-010 ADVANCED TECHNOLOGY INCUBATOR, INC. ADAPTIVE SENSORS, INC. NAVY Topic#: 92-117 AF Topic#: 92-031 ADVANCED TECHNOLOGY MATERIALS, INC. ADAPTIVE TECHNOLOGY, INC. ΑF Topic#: 92-130 AF Topic#: 92-102 ARMY Topic#: 92-044 ADCOM SYSTEMS TECHNOLOGY, INC. ARMY Topic#: 92-131 AF Topic#: 92-031 DARPA Topic#: 92-044 NAVY Topic#: 92-049 SDIO Topic#: 92-003 ADIABATICS, INC. SDIO Topic#: 92-014 DARPA Topic#: 92-094 SDIO Topic#: 92-014 ADROIT SYSTEMS, INC. SDIO Topic#: 92-015 AF Topic#: 92-146 SDIO Topic#: 92-015 ARMY Topic#: 92-034 SDIO Topic#: 92-016 ADTECH SYSTEMS RESEARCH, INC. AEGIS RESEARCH CORP. Topic#: 92-016 AF Topic#: 92-163 ADVANCED CERAMICS RESEARCH, INC. **AERO COMPOSITES** DARPA Topic#: 92-033 DARPA Topic#: 92-022 ADVANCED COMMUNICATION SYSTEMS, INC. AEROASTRO CORP. NAVY Topic#: 92-026 ΑF Topic#: 92-088 ADVANCED COMPUTER SUPPORT COMPANY AERODYNE RESEARCH, INC. ARMY Topic#: 92-018 Topic#: 92-086 ADVANCED ENERGY 1 LCHNOLOGY, INC. DARPA Topic#: 92-123 SDIO Topic#: 92-004 NAVY Topic#: 92-074 ADVANCED FUEL RESEARCH, INC. AEROMETRICS, INC AF Topic#: 92-046 AF Topic#: 92-001 AF Topic#: 92-074 NAVY Topic#: 92-178 ΑF Topic#: 92-143 AERONIX, INC. SDIO Topic#: 92-003 ARMY Topic#: 92-172 SDIO Topic#: 92-003 **AEROPRO SYSTEMS** SDIO Topic#: 92-015

ARMY Topic#: 92-051

AEROSPACE COMPUTING, INC. ANALYTIC DESIGNS, INC. Topic#: 92-157 ARMY Topic#: 92-006 AF ARMY Topic#: 92-139 AEROSPACE DESIGN & DEVELOPMENT, INC. AF Topic#: 92-011 ANALYTIC ENGINEERING COMPANY **AEROTECH ENGINEERING & RESEARCH** NAVY Topic#: 92-134 AF Topic#: 92-169 ANALYTICAL DESIGNS, INC. DARPA Topic#: 92-187 ARMY Topic#: 92-007 AETECH, INC. ANALYTICAL SERVICES & MATERIALS, INC. ΑF Topic#: 92-029 AF Topic#: 92-005 AIMS, INC. ARMY Topic#: 92-082 DARPA Topic#: 92-161 NAVY Topic#: 92-156 AKM ASSOC., INC. ANALYTICAL SPECTRAL DEVICES, INC. ARMY Topic#: 92-090 ARMY Topic#: 92-145 ALABAMA CRYOGENIC ENGINEERING, INC. ANAMET LABORATORIES, INC. DARPA Topic#: 92-185 ARMY Topic#: 92-001 NAVY Topic#: 92-145 ALPHATECH, INC. Topic#: 92-031 ANRO ENGINEERING, INC. AF AF Topic#: 92-031 SDIO Topic#: 92-003 Topic#: 92-055 ANTAIRE CORP. AF DARPA Topic#: 92-049 DARPA Topic#: 92-081 DARPA Topic#: 92-161 APA OPTICS, INC. NAVY Topic#: 92-020 AF Topic#: 92-018 NAVY Topic#: 92-047 SDIO Topic#: 92-002 NAVY Topic#: 92-127 SDIO Topic#: 92-014 ALTERNATIVE SYSTEM CONCEPTS, INC. APELDYN CORP. DARPA Topic#: 92-031 DARPA Topic#: 92-098 AMALGAMATED TECHNOLOGIES, INC. APPLIED PHYSICS, INC. NAVY Topic#: 92-144 NAVY Topic#: 92-082 AMERICAN COMPOSITE TECHNOLOGY APPLIED POLYMER SYSTEMS, INC. ARMY Topic#: 92-068 AF Topic#: 92-070 AMERICAN GNC CORP. APPLIED PULSE POWER, INC. AF Topic#: 92-157 SDIO Topic#: 92-006 ARMY Topic#: 92-013 APPLIED RESEARCH ASSOC. DARPA Topic#: 92-103 ARMY Topic#: 92-033 NAVY Topic#: 92-081 APPLIED RESEARCH ASSOC., INC. NAVY Topic#: 92-149 Topic#: 92-157 SDIO Topic#: 92-012 AF Topic#: 92-167 AMERICAN POWER JET COMPANY NAVY Topic#: 92-075 ARMY Topic#: 92-177 APPLIED SCIENCE AND TECHNOLOGY, INC. AMERICAN RESEARCH CORP. OF VIRGINIA DARPA Topic#: 92-044 ARMY Topic#: 92-099 APPLIED SCIENCES, INC. NAVY Topic#: 92-030 Topic#: 92-066 SDIO Topic#: 92-014 AF Topic#: 92-137 AMHERST SYSTEMS, INC. APPLIED TECHNICAL SYSTEMS, INC. Topic#: 92-107 DARPA Topic#: 92-218 DARPA Topic#: 92-206 APPLIED TECHNOLOGY ASSOC., INC. ANADAC, INC. ARMY Topic#: 92-170 NAVY Topic#: 92-038 APPLIED TECHNOLOGY, INC. ANALATOM, INC. AF Topic#: 92-098 ARMY Topic#: 92-064 ARBUS, INC. ANALYTEK LIMITED DARPA Topic#: 92-110 AF Topic#: 92-019 ARCTECH, INC.

NAVY Topic#: 92-095

ASCENSION TECHNOLOGY CORP. BENTHOS, INC. DARPA Topic#: 92-176 ARMY Topic#: 92-023 ASPEN SYSTEMS, INC. NAVY Topic#: 92-060 DARPA Topic#: 92-165 BERKELEY RESEARCH ASSOC., INC. ASTA-BLU ARMY Topic#: 92-127 DARPA Topic#: 92-217 DNA Topic#: 92-014 **ASTRALUX** DNA Topic#: 92-014 SDIO Topic#: 92-014 BESTECH GROUP OF AMERICA, INC. NAVY Topic#: 92-013 SDIO Topic#: 92-014 ASTRON CORP. BIHRLE APPLIED RESEARCH, INC. NAVY Topic#: 92-017 Topic#: 92-122 NAVY Topic#: 92-052 BIO-IMAGING RESEARCH, INC. ASTROPOWER, INC. ARMY Topic#: 92-025 ARMY Topic#: 92-095 AF Topic#: 92-137 SDIO Topic#: 92-003 **BIO-TECHNICAL RESOURCES** SDIO Topic#: 92-005 ARMY Topic#: 92-101 SDIO Topic#: 92-014 BIOELASTICS RESEACH, LTD. SDIO Topic#: 92-014 ARMY Topic#: 92-069 ATLANTIC AEROSPACE ELECTRONICS CORP. **BIOLOGICAL COMPONENTS CORP. (BCC)** ARMY Topic#: 92-059 ARMY Topic#: 92-103 ARMY Topic#: 92-119 NAVY Topic#: 92-006 DARPA Topic#: 92-108 NAVY Topic#: 92-072 ATLANTIC APPLIED RESEARCH CORP. BLACK FOREST ENGINEERING, INC. SDIO Topic#: 92-003 NAVY Topic#: 92-100 ATMOSPHERIC AND ENVIRONMENTAL BLOCK ENGINEERING, INC. NAVY Topic#: 92-187 NAVY Topic#: 92-188 Topic#: 92-085 AF ATSS, INC. Topic#: 92-125 AF BOSTAN RESEARCH, INC. AURORA ASSOC. NAVY Topic#: 92-129 ARMY Topic#: 92-035 BRENNAN & ASSOC., INC. ARMY Topic#: 92-057 NAVY Topic#: 92-146 AURORA FLIGHT SCIENCES CORP. BREWER SCIENCES, INC. NAVY Topic#: 92-109 DARPA Topic#: 92-175 AUTOMATIX, INC. BRIMROSE CORP. OF AMERICA ARMY Topic#: 92-092 ARMY Topic#: 92-049 ARMY Topic#: 92-145 ARMY Topic#: 92-133 SDIO Topic#: 92-003 **AVOCA LABORATORIES** DARPA Topic#: 92-182 BUSEK CO., INC. DARPA Topic#: 92-183 AF Topic#: 92-015 AXIOM CORP. ARMY Topic#: 92-100 AF Topic#: 92-151 SDIO Topic#: 92-005 SDIO Topic#: 92-006 BALDWIN/MCHUGH ASSOC., INC. CAMBRIDGE ACOUSTICAL ASSOC., INC. DARPA Topic#: 92-215 NAVY Topic#: 92-114 BD SYSTEMS, INC. CAMBRIDGE SCIENTIFIC, INC. NAVY Topic#: 92-181 BELTRAN, INC. AF Topic#: 92-132 ARMY Topic#: 92-006 CAPE COD RESEARCH, INC. SDIO Topic#: 92-014 ARMY Topic#: 92-075 SDIO Topic#: 92-011 BEND RESEARCH, INC. ARMY Topic#: 92-067 CARNEGIE GROUP, INC

DARPA Topic#: 92-096

CARPENTER RESEARCH CORP. CIM SYSTEMS, INC. DARPA Topic#: 92-104 DNA Topic#: 92-005 CMTG RESEARCH, INC. CASDE CORP. NAVY Topic#: 92-133 ARMY Topic#: 92-080 CCS ASSOC. CNR, INC. DARPA Topic#: 92-019 AF Topic#: 92-147 CEA. INC. CNS TECHNOLOGY, INC. AF Topic#: 92-033 SDIO Topic#: 92-001 CEMCOM RESEARCH ASSOC., INC. COHERENT TECHNOLOGIES, INC. NAVY Topic#: 92-027 NAVY Topic#: 92-065 CENTER FOR REMOTE SENSING COLEMAN ENGINE CORP. Topic#: 92-181 ARMY Topic#: 92-014 ARMY Topic#: 92-031 COLEMAN RESEARCH CORP. DARPA Topic#: 92-031 SDIO Topic#: 92-002 NAVY Topic#: 92-019 SDIO Topic#: 92-002 SDIO Topic#: 92-010 CERACON, INC. ARMY Topic#: 92-003 COLONIAL CIRCUITS, INC. ARMY Topic#: 92-124 CERAMIC COMPOSITES, INC. SDIO Topic#: 92-007 COMBUSTION SCIENCES, INC. CERCOM, INC. SDIO Topic#: 92-006 ARMY Topic#: 92-021 COMPLERE, INC. CERTEK CORP. NAVY Topic#: 92-110 NAVY Topic#: 92-015 COMPUTER AND INFORMATION SCIENCE, INC. CFD RESEARCH CORP. NAVY Topic#: 92-030 ΑF Topic#: 92-014 COMPUTER SCIENCE AND APPLICATIONS ARMY Topic#: 92-012 Topic#: 92-157 ARMY Topic#: 92-051 COMPUTING SERVICES SUPPORT SOLUTIONS ARMY Topic#: 92-041 CHAMBELL ENGINEERING, INC. ARMY Topic#: 92-053 CONCEPTUAL MINDWORKS, INC. AF Topic#: 92-020 CHANG INDUSTRY, INC. DARPA Topic#: 92-107 CONCEPTUAL SOFTWARE SYSTEMS, INC. CHARGED INJECTION CORP. DARPA Topic#: 92-149 NAVY Topic#: 92-085 DARPA Topic#: 92-164 CHARLES RIVER ANALYTICS, INC. NAVY Topic#: 92-101 AF Topic#: 92-164 SDIO Topic#: 92-003 CONDUCTUS, INC. ARMY Topic#: 92-160 NAVY Topic#: 92-174 NAVY Topic#: 92-010 CHEMAT TECHNOLOGY, INC. SDIO Topic#: 92-015 SDIO Topic#: 92-015 DARPA Topic#: 92-178 CHI SYSTEMS, INC. CONTAMINATION STUDIES LABORATORY NAVY Topic#: 92-161 ARMY Topic#: 92-124 NAVY Topic#: 92-165 CONTINUOUS MOLDING, INC. SDIO Topic#: 92-013 CHIRP CORP. DARPA Topic#: 92-074 CONTINUUM DYNAMICS, INC. CHRONOS RESEARCH LABORATORIES, INC. AF Topic#: 92-009 SDIO Topic#: 92-001 ARMY Topic#: 92-008 CI SYSTEMS, INC. CORDEC CORP. DARPA Topic#: 92-101 ARMY Topic#: 92-017 CIENCIA, INC. COSOFT DESIGNS, INC. NAVY Topic#: 92-121 AF Topic#: 92-180 SDIO Topic#: 92-001 COVALENT ASSOC., INC.

ARMY Topic#: 92-115

SDIO Topic#: 92-012

CREARE, INC.	ARMY Topic#: 92-130
AF Topic#: 92-065	DATA FUSION CORP.
AF Topic#: 92-145	AF Topic#: 92-101
DARPA Topic#: 92-156	SDIO Topic#: 92-003
NAVY Topic#: 92-050	DATAMAT SYSTEMS RESEARCH, INC.
NAVY Topic#: 92-090	NAVY Topic#: 92-157
SDIO Topic#: 92-007	DATASONICS, INC.
SDIO Topic#: 92-015	NAVY Topic#: 92-083
CREE RESEARCH, INC.	DCS CORP.
AF Topic#: 92-114	ARMY Topic#: 92-004
CREW SYSTEMS CONSULTANTS	NAVY Topic#: 92-166
ARMY Topic#: 92-015	DDL OMNI ENGINEERING CORP.
CRYSTAL ASSOC., INC.	NAVY Topic#: 92-061
AF Topic#: 92-130	DEACON RESEARCH
SDIO Topic#: 92-011	AF Topic#: 92-111
CRYSTAL SYSTEMS, INC.	DECISION DYNAMICS, INC.
SDIO Topic#: 92-014	DARPA Topic#: 92-156
CRYSTALIZ, INC.	NAVY Topic#: 92-103
DARPA Topic#: 92-031	NAVY Topic#: 92-106
CRYSTALLUME	DECISION-SCIENCE APPLICATIONS, INC.
AF Topic#: 92-042	ARMY Topic#: 92-139
AF Topic#: 92-066	DEEGAN RESEARCH GROUP, INC.
AF Topic#: 92-138	AF Topic#: 92-001
SDIO Topic#: 92-003	NAVY Topic#: 92-066
CSA ENGINEERING, INC.	DEEPSEA POWER & LIGHT
AF Topic#: 92-071	DARPA Topic#: 92-088
AF Topic#: 92-072	DEFENSE RESEARCH TECHNOLOGIES, INC.
SDIO Topic#: 92-012	ARMY Topic#: 92-128
CUDO TECHNOLOGIES, LTD.	DELFIN SYSTEMS
SDIO Topic#: 92-007	ARMY Topic#: 92-084
CYBERNET SYSTEMS CORP.	DESE RESEARCH, INC.
AF Topic#: 92-058	DNA Topic#: 92-012
ARMY Topic#: 92-147	DEVELOSOFT CORP.
NAVY Topic#: 92-012	AF Topic#: 92-049
CYGNUS IMAGING CORP.	DARPA Topic#: 92-141
SDIO Topic#: 92-003	NAVY Topic#: 92-183
D	DIGITAL OPTICS CORP.
D	DARPA Topic#: 92-057
DAINA	SDIO Topic#: 92-011
ARMY Topic#: 92-032	DIGITAL SYSTEM RESOURCES, INC.
DAMASKOS, INC.	NAVY Topic#: 92-126 DIRECTED TECHNOLOGIES, INC.
SDIO Topic#: 92-005	ARMY Topic#: 92-102
DAMILIC CORP.	DISPLAYTECH, INC.
NAVY Topic#: 92-067	AF Topic#: 92-037
DANIEL H. VALLES & ASSOC.	AF Topic#: 92-087
DNA Topic#: 92-003	DARPA Topic#: 92-057
DANIEL H. WAGNER ASSOC., INC.	NAVY Topic#: 92-117
ARMY Topic#: 92-176	DOVE ELECTRONICS, INC.
NAVY Topic#: 92-023	ARMY Topic#: 92-091
NAVY Topic#: 92-033	DRAGON SYSTEMS, INC.
SDIO Topic#: 92-010	DARPA Topic#: 92-078
DASGROUP	DARPA Topic#: 92-216
ARMY Topic#: 92-050	Distance Express 20 050

DURATECH, INC. ELECTROCHEMICAL SYSTEMS, INC. DARPA Topic#: 92-188 SDIO Topic#: 92-014 DYNA EAST CORP. ELECTROCHEMICAL TECHNOLOGY CORP. AF Topic#: 92-157 NAVY Topic#: 92-139 ARMY Topic#: 92-001 ELECTROKINETICS, INC. DYNACS ENGINEERING COMPANY, INC. ARMY Topic#: 92-151 SDIO Topic#: 92-002 ELECTROMAGNETIC APPLICATIONS, INC. DYNATHERM CORP. ARMY Topic#: 92-110 SDIO Topic#: 92-003 SDIO Topic#: 92-007 DYNETICS, INC. ELECTRONIC DECISIONS, INC. ARMY Topic#: 92-033 Topic#: 92-160 ARMY Topic#: 92-062 EMCOR ELECTRO-MAGNETIX CORP. DARPA Topic#: 92-179 DARPA Topic#: 92-105 EMCORE CORP. DARPA Topic#: 92-072 SDIO Topic#: 92-014 EAI CORP. SDIO Topic#: 92-014 ARMY Topic#: 92-079 **EMF SYSTEMS** EAST, INC. Topic#: 92-093 AF NAVY Topic#: 92-159 ENERGY COMPRESSION RESEARCH CORP. EASTPORT INTERNATIONAL, INC. DARPA Topic#: 92-010 ARMY Topic#: 92-141 ENERGY CONVERSION DEVICES, INC. ECOCAD U.S.A., INC. ARMY Topic#: 92-077 Topic#: 92-063 AF **ENERGY MATERIALS TESTING LABORATORY EDFA CONSULTANTS** Topic#: 92-003 SDIO Topic#: 92-011 ENERGY SCIENCE LABORATORIES, INC. EIC LABORATORIES, INC. Topic#: 92-073 Topic#: 92-007 AF SDIO Topic#: 92-003 AF Topic#: 92-078 SDIO Topic#: 92-007 DARPA Topic#: 92-026 ENGINEERING DEVELOPMENT CORP. SDIO Topic#: 92-011 ARMY Topic#: 92-080 SDIO Topic#: 92-015 ENIG ASSOC., INC. EIDETICS INTERNATIONAL, INC. ARMY Topic#: 92-105 AF Topic#: 92-150 ENSCO, INC. ELASTOMERIC TECHNOLOGIES, INC. ARMY Topic#: 92-005 Topic#: 92-109 DARPA Topic#: 92-121 **ELECTRA MAGNETIC APPLICATIONS** DNA Topic#: 92-004 NAVY Topic#: 92-034 DNA Topic#: 92-005 ELECTRO ENERGY, INC. ENTECH, INC. SDIO Topic#: 92-005 SDIO Topic#: 92-005 ELECTRO-OPTEK CORP. ENTROPIC RESEARCH LABORATORY, INC. Topic#: 92-068 DARPA Topic#: 92-082 Topic#: 92-096 AF EPI CHORUS CORP. ARMY Topic#: 92-035 ΑF Topic#: 92-112 DARPA Topic#: 92-172 EPILOGICS, INC. DNA Topic#: 92-007 ARMY Topic#: 92-009 SDIO Topic#: 92-003 EPION CORP. SDIO Topic#: 92-014 SDIO Topic#: 92-014 SDIO Topic#: 92-014 **ESEA** ELECTRO-RADIATION, INC. ARMY Topic#: 92-146 Topic#: 92-104 ARMY Topic#: 92-148 NAVY Topic#: 92-172 ESSEX CORP. ELECTROCHEM, INC.

SDIO Topic#: 92-005

Topic#: 92-021

EVANS FINDINGS CO, INC.	ARMY Topic#: 92-086
NAVY Topic#: 92-066	ARMY Topic#: 92-093
•	ARMY Topic#: 92-120
F	ARMY Topic#: 92-133
F&H APPLIED SCIENCE ASSOC.	DARPA Topic#: 92-025
NAVY Topic#: 92-035	DARPA Topic#: 92-045
FARACHEM TECHNOLOGY, INC.	DARPA Topic#: 92-061
NAVY Topic#: 92-111	DARPA Topic#: 92-177
FAST MATH. ALGORITHMS & HARDWARE	DARPA Topic#: 92-184
DARPA Topic#: 92-159	DARPA Topic#: 92-221
FASTMAN, INC.	DARPA Topic#: 92-224
ARMY Topic#: 92-062	NAVY Topic#: 92-037
DARPA Topic#: 92-082	NAVY Topic#: 92-070
FEA MICROELECTRONICS CORP.	NAVY Topic#: 92-087
AF Topic#: 92-024	NAVY Topic#: 92-096
FEDERAL ELECTRO-OPTICS	NAVY Topic#: 92-120
SDIO Topic#: 92-003	NAVY Topic#: 92-123
FEDERAL FABRICS	NAVY Topic#: 92-138
ARMY Topic#: 92-073	NAVY Topic#: 92-142
FERMIONICS CORP.	NAVY Topic#: 92-148
ARMY Topic#: 92-043	NAVY Topic#: 92-151
ARMY Topic#: 92-118	NAVY Topic#: 92-186
FIBER AND SENSOR TECHNOLOGIES	SDIO Topic#: 92-007
AF Topic#: 92-120	SDIO Topic#: 92-008
AF Topic#: 92-179	SDIO Topic#: 92-011
DARPA Topic#: 92-045	SDIO Topic#: 92-011
NAVY Topic#: 92-140	FRONT RANGE SCIENTIFIC COMPUTATIONS
SDIO Topic#: 92-012	NAVY Topic#: 92-099
FIBER MATERIALS, INC.	FRONTIER TECHNOLGY, INC.
ARMY Topic#: 92-067	AF Topic#: 92-032
DARPA Topic#: 92-045	FUENTEZ SYSTEMS CONCEPTS, INC.
DARPA Topic#: 92-157	NAVY Topic#: 92-028
SDIO Topic#: 92-013	
SDIO Topic#: 92-013	G
FLAM & RUSSELL, INC.	GAMRY INSTRUMENTS, INC.
NAVY Topic#: 92-049	NAVY Topic#: 92-008
NAVY Topic#: 92-078	GENERAL ATRONICS CORP.
FM TECHNOLOGIES, INC.	ARMY Topic#: 92-026
DARPA Topic#: 92-032	GENERAL SCIENCES, INC.
FOSTER-MILLER, INC.	AF Topic#: 92-125
AF Topic#: 92-040	DNA Topic#: 92-006
AF Topic#: 92-075	SDIO Topic#: 92-001
AF Topic#: 92-077	GEO-CENTERS, INC.
AF Topic#: 92-098	ARMY Topic#: 92-002
AF Topic#: 92-121	DNA Topic#: 92-005
AF Topic#: 92-156	DNA Topic#: 92-005
ARMY Topic#: 92-003	GINER, INC.
ARMY Topic#: 92-004	DARPA Topic#: 92-165
ARMY Topic#: 92-027	SDIO Topic#: 92-005
ARMY Topic#: 92-059	GLOBAL INFORMATION SYSTEMS TECHNOLOGY
ARMY Topic#: 92-070	AF Topic#: 92-029
ARMY Topic#: 92-071	DARPA Topic#: 92-092
ARMI IODICH, JE O/I	EDITATION TO DECEMBER 1 TO DECEMBER 1

GOLDEN TRIANGLE TECHNOLOGY, INC. DARPA Topic#: 92-134 I-KINETICS, INC. GORCA SYSTEMS, INC. NAVY Topic#: 92-112 NAVY Topic#: 92-031 I-MATH ASSOC., INC. SDIO Topic#: 92-010 ARMY Topic#: 92-042 GRAPHIC RESEARCH, INC. IAP RESEARCH, INC. ARMY Topic#: 92-124 NAVY Topic#: 92-098 GREEN MOUNTAIN RADIO RESEARCH CO. SDIO Topic#: 92-013 ARMY Topic#: 92-150 IBIS TECHNOLOGY CORP. GREENLEAF CORP. AF Topic#: 92-128 DARPA Topic#: 92-158 DNA Topic#: 92-007 GREYSTONE DEFENSE SYSTEMS DIVISION SDIO Topic#: 92-014 DARPA Topic#: 92-012 IGC ADVANCED SUPERCONDUCTORS, INC. **GUIDED SYSTEMS TECHNOLOGIES** SDIO Topic#: 92-015 ARMY Topic#: 92-007 II-VI. INC. GUMBS ASSOC., INC. DARPA Topic#: 92-071 ARMY Topic#: 92-068 **IMAGING SCIENCE TECHNOLOGIES** ARMY Topic#: 92-106 SDIO Topic#: 92-003 NAVY Topic#: 92-141 IMPLANT SCIENCES CORP. SDIO Topic#: 92-008 SDIO Topic#: 92-014 INDUSTRIAL EVOLUTION ARMY Topic#: 92-065 INDUSTRIAL HONEYCOMB STRUCTURES, INC. HARRIS. TEDRIC A., CONSULTING ENGINEER ARMY Topic#: 92-027 NAVY Topic#: 92-124 ARMY Topic#: 92-027 HARRIS TECHNOLOGIES, INC. INDUSTRIAL QUALITY, INC. ARMY Topic#: 92-096 ARMY Topic#: 92-095 HERSH ACOUSTICAL ENGINEERING, INC. NAVY Topic#: 92-185 Topic#: 92-079 INDUSTRIAL SENSORS AND ACTUATORS HITTITE MICROWAVE CORP. **DARPA** Topic#: 92-090 ARMY Topic#: 92-126 INEPMAGNETICS GENERAL CORP. HITTMAN MATERIALS & MEDICAL COMPONENTS NAVY Topic#: 92-050 Αr Topic#: 92-069 **INFOMETRICS** SDIO Topic#: 92-013 NAVY Topic#: 92-011 HNC, INC. INFRARED FIBER SYSTEMS, INC. AF Topic#: 92-044 NAVY Topic#: 92-182 AF Topic#: 92-152 INNOVA LABORATORIES, INC. ARMY Topic#: 92-054 SDIO Topic#: 92-016 SDIO Topic#: 92-003 INNOVATION ASSOC., INC. HOLOGRAPHICS, INC. NAVY Topic#: 92-002 DARPA Topic#: 92-132 INNOVATIVE CHEMICAL TECHNOLOGIES CORP. HOLZ INDUSTRIES, INC. SDIO Topic#: 92-014 SDIO Topic#: 92-014 INNOVATIVE DYNAMICS, INC. HORIZONS TECHNOLOGY, INC. ARMY Topic#: 92-143 Topic#: 92-010 AF INNOVATIVE MANAGEMENT DECISIONS ARMY Topic#: 92-087 NAVY Topic#: 92-102 **HUNTINGTON RESEARCH AND ENGINEERING** INNOVATIVE TEST SYSTEMS ARMY Topic#: 92-172 HY-TECH RESEARCH CORP. AF Topic#: 92-094 INRAD, INC. DNA Topic#: 92-019 HYGEIA PHARMACEUTICALS, INC. Topic#: 92-007 AF ARMY Topic#: 92-100 ARMY Topic#: 92-162 NAVY Topic#: 92-007 HYPRES, INC.

Topic#: 92-048

AF

INTEGRATED APPLIED PHYSICS, INC. KARTA TECHNOLOGY, INC. SDIO Topic#: 92-005 ARMY Topic#: 92-133 INTEGRATED SYSTEMS, INC. KDC TECHNOLOGY CORP. DARPA Topic#: 92-038 AF Topic#: 92-128 INTELLIGENT AUTOMATION, INC. KNOWLEDGE BASED SYSTEMS, INC. AF Topic#: 92-012 DARPA Topic#: 92-209 ARMY Topic#: 92-026 **KNOWLEDGE INDUSTRIES** INTELLIGENT REASONING SYSTEMS AF Topic#: 92-101 ARMY Topic#: 92-022 ARMY Topic#: 92-172 NAVY Topic#: 92-113 KNOWLEDGE SCIENCES, INC. INTELLISENSE CORP. ARMY Topic#: 92-022 AF Topic#: 92-090 KOPIN CORP. **INTERFACE TECHNOLOGIES** AF Topic#: 92-129 ARMY Topic#: 92-098 DARPA Topic#: 92-072 INTERNATIONAL BUSINESS ASSOC., INC. KTAADN, INC. NAVY Topic#: 92-154 AF Topic#: 92-031 INTERPHASES RESEARCH KTECH CORP. SDIO Topic#: 92-005 ARMY Topic#: 92-173 INTERSCIENCE, INC. DNA Topic#: 92-013 ARMY Topic#: 92-129 KULITE SEMICONDUCTOR PRODUCTS, INC. INVOCON SDIO Topic#: 92-014 NAVY Topic#: 92-181 KVH INDUSTRIES, INC. **IONWERKS** ARMY Topic#: 92-152 SDIO Topic#: 92-014 EXVINE SENSORS CORP. SDIO Topic#: 92-003 LASER PHOTONIES TECHNOLOGY, INC. ISORCA, INC. DARPA Topic#: 92-041 NAVY Topic#: 92-067 LASERGENICS CORP. ISX CORP. SDIO Topic#: 92-011 Topic#: 92-149 AF SDIO Topic#: 92-014 ITERATED SYSTEMS, INC. LASKER TECHNOLOGY COMPANY ARMY Topic#: 92-054 SDIO Topic#: 92-002 LB&M ASSOC., INC. ARMY Topic#: 92-177 J P LABORATORIES, INC. LEEP SYSTEMS, INC. ARMY Topic#: 92-011 NAVY Topic#: 92-039 J.B.S. TECHNOLOGIES, INC. LIGHTWAVE ELECTRONICS CORP. DARPA Topic#: 92-004 AF Topic#: 92-103 SDIO Topic#: 92-003 DARPA Topic#: 92-162 J.K. RESEARCH LINARES MANAGEMENT ASSOC., INC. ARMY Topic#: 92-046 SDIO Topic#: 92-014 JARDON & HOWARD TECHNOLOGIES, INC. LIVERMORE SOFTWARE TECHNOLOGY CORP. NAVY Topic#: 92-045 NAVY Topic#: 92-069 JET PROCESS CORP. LNK CORP. DARPA Topic#: 92-040 AF Topic#: 92-152 SDIO Topic#: 92-011 NAVY Topic#: 92-001 SDIO Topic#: 92-013 LONE PEAK ENGINEERING, INC. JOHN BROWN ASSOC., INC. **DARPA** Topic#: 92-033 DARPA Topic#: 92-175 LTA INTERNATIONAL, INC. NAVY Topic#: 92-055 LYNNTECH, INC. ARMY Topic#: 92-151 KARS' ADVANCED MATERIALS, INC.

ARMY Topic#: 92-106

DARPA Topic#: 92-025

NAVY Topic#: 92-111	MATERIALS SCIENCES CORP.
	DARPA Topic#: 92-191
M	NAVY Topic#: 92-078
M-DOT, INC.	NAVY Topic#: 92-171
AF Topic#: 92-141	MATHTECH, INC.
ARMY Topic#: 92-052	NAVY Topic#: 92-038
DARPA Topic#: 92-186	NAVY Topic#: 92-167
M.L. ENERGIA, INC.	MAY
AF Topic#: 92-005	ARMY Topic#: 92-085
ARMY Topic#: 92-061	MAYER APPLIED RESEARCH, INC.
NAVY Topic#: 92-175	SDIO Topic#: 92-004
M.S. SAPUPPO & ASSOC.	MAYFLOWER COMMUNICATIONS CO., INC.
SDIO Topic#: 92-002	ARMY Topic#: 92-175
MAINSTREAM ENGINEERING CORP.	MDA ENGINEERING, INC.
ARMY Topic#: 92-074	AF Topic#: 92-157
SDIO Topic#: 92-007	MDL, INC.
MAK TECHNOLOGIES, INC.	NAVY Topic#: 92-039
	MDS COMPANY
ARMY Topic#: 92-098 MALIBU RESEARCH ASSOC., INC.	SDIO Topic#: 92-001
•	MELLER OPTICS, INC.
DARPA Topic#: 92-109	NAVY Topic#: 92-118
MANAGEMENT CONSULTING & RESEARCH	MEMRY TECHNOLOGIES, INC.
AF Topic#: 92-151	AF Topic#: 92-156
MANAGEMENT RESEARCH INSTITUTE	MERIX CORP.
ARMY Topic#: 92-154	
MANAGEMENT SUPPORT SERVICES, INC.	ARMY Topic#: 92-073
NAVY Topic#: 92-066	DARPA Topic#: 92-061
MANDEX, INC.	METEOR COMMUNICATIONS CORP.
DARPA Topic#: 92-095	DARPA Topic#: 92-130
MARBLE ASSOC., INC.	METROLASER
DARPA Topic#: 92-139	SDIO Topic#: 92-003
MARCHEM	METSAT, INC.
AF Topic#: 92-124	AF Topic#: 92-088
MARK RESOURCES, INC.	MHM CBNSULTANTS
DARPA Topic#: 92-102	NAVY Topic#: 92-086
MARTIN GOFFMAN ASSOC.	MICHAEL HUNG, INC.
SDIO Topic#: 92-014	NAVY Topic#: 92-058
MARTIN SYSTEMS, INC.	MICRO COMPOSITE MATERIALS CORP.
AF Topic#: 92-035	ARMY Topic#: 92-012
MASSA PRODUCTS CORP.	MICROSYSTEMS ENGINEERING, INC.
NAVY Topic#: 92-088	ARMY Topic#: 92-113
MATERIALS & ELECTROCHEMICAL RESEARCH	MICROTRONICS ASSOC., INC.
AF Topic#: 92-073	AF Topic#: 92-017
ARMY Topic#: 92-102	MICROWAVE MONOLITHICS, INC.
ARMY Topic#: 92-131	DARPA Topic#: 92-055
ARMY Topic#: 92-171	MIDWEST RESEARCH TECHNOLOGIES, INC.
DARPA Topic#: 92-030	SDIO Topic#: 92-013
SDIO Topic#: 92-015	MIKROS SYSTEMS CORP.
MATERIALS ANALYSIS, INC.	NAVY Topic#: 92-083
AF Topic#: 92-156	MILLIMETER WAVE TECHNOLOGY, INC.
MATERIALS AND SYSTEMS RESEARCH, INC.	DARPA Topic#: 92-067
DARPA Topic#: 92-030	NAVY Topic#: 92-051
MATERIALS MODIFICATION, INC.	MILLITECH CORP.
ARMY Topic#: 92-137	ARMY Topic#: 92-056
AND 1 10pium. 72-137	TARREST TO PROPERTY OF THE PRO

MINARET SYSTEMS ARMY Topic#: 92-039 N.S. GOWADIA, INC. MISSION RESEARCH CORP. DARPA Topic#: 92-123 AF Topic#: 92-060 N.TEXAS RESEARCH & DEVELOPMENT CORP AF Topic#: 92-064 NAVY Topic#: 92-107 ARMY Topic#: 92-071 NAMBETECH, INC. DARPA Topic#: 92-029 ARMY Topic#: 92-025 DARPA Topic#: 92-202 NAVMAR APPLIED SCIENCES CORP. DNA Topic#: 92-001 NAVY Topic#: 92-170 DNA Topic#: 92-005 NAVY Topic#: 92-088 NAVTROL COMPANY, INC. AF Topic#: 92-119 MO-SCI CORP. NEOMECS, INC. DARPA Topic#: 92-028 Topic#: 92-027 MOLECULAR PROBES, INC. NEOTERIC TECHNOLOGIES, INC. DARPA Topic#: 92-129 NAVY Topic#: 92-104 MOLTECH CORP. NETROLOGIC, INC. DARPA Topic#: 92-060 Topic#: 92-144 NAVY Topic#: 92-013 DARPA Topic#: 92-120 MOLTEN SALT TECHNOLOGY, INC. NEURODYNE, INC. Topic#: 92-139 DARPA Topic#: 92-089 MORGAN RESEARCH CORP. DARPA Topic#: 92-197 DARPA Topic#: 92-099 NAVY Topic#: 92-128 MOSET CORP. NEW LIGHT INDUSTRIES, LTD. ARMY Topic#: 92-043 SDIO Topic#: 92-005 MOUNTAIN OPTECH, INC. NIELSEN ENGINEERING & RESEARCH, INC. NAVY Topic#: 92-137 DARPA Topic#: 92-001 MRJ, INC. SDIO Topic#: 92-002 ΑF Topic#: 92-044 NIMBLE COMPUTER CORP. MSNW, INC. SDIO Topic#: 92-010 AF Topic#: 92-045 NKF ENGINEERING, INC. AF Topic#: 92-123 NAVY Topic#: 92-079 AF Topic#: 92-126 **NOISE REMOVAL SYSTEMS** ARMY Topic#: 92-135 ARMY Topic#: 92-160 NAVY Topic#: 92-120 NONLINEAR PREDICTION SYSTEMS SDIO Topic#: 92-007 DARPA Topic#: 92-073 MSP CORP. NONVOLATILE ELECTRONICS, INC. ARMY Topic#: 92-048 SDIO Topic#: 92-014 MTL SYSTEMS, INC. SDIO Topic#: 92-014 Topic#: 92-105 ΑF NORTH STAR RESEARCH CORP. AF Topic#: 92-110 DNA Topic#: 92-019 Topic#: 92-148 NORTHWEST TECHNICAL INDUSTRIES, INC. DARPA Topic#: 92-144 NAVY Topic#: 92-097 DARPA Topic#: 92-145 NOVA MANAGEMENT, INC. MUDAWAR THERMAL SYSTEM, INC. ARMY Topic#: 92-087 ARMY Topic#: 92-089 NAVY Topic#: 92-136 MUITISPEC CORP. NOVEX CORP. NAVY Topic#: 92-009 **DARPA** Topic#: 92-067 MULTILAYER OPTICS AND X-RAY TECHNOLOGY SDIO Topic#: 92-001 MXR, INC. OC SYSTEMS, INC. SDIO Topic#: 92-003 DARPA Topic#: 92-137 OCA APPLIED OPTICS

ARMY Topic#: 92-060

DARPA Topic#: 92-189 NAVY Topic#: 92-160 OCEANEERING TECHNOLOGY, INC. PAGE AUTOMATED TELECOM. SYSTEMS, INC. NAVY Topic#: 92-015 SDIO Topic#: 92-012 OLYMPIC LOAD & TEST, INC. PAI CORP. NAVY Topic#: 92-010 ARMY Topic#: 92-141 OMNITECH ROBOTICS, INC. PALRESEARCH, LTD. NAVY Topic#: 92-012 AF Topic#: 92-166 ONTAR CORP. PAQ COMMUNICATIONS ARMY Topic#: 92-092 AF Topic#: 92-031 OPERATIONAL TECHNOLOGIES CORP. PARADIGM, INC. ARMY Topic#: 92-153 AF Topic#: 92-161 PARASOFT CORP. OPHIR CORP. Topic#: 92-118 SDIO Topic#: 92-010 AF OPTICAL CONCEPTS, INC. PARKE MATHEMATICAL LABORATORIES DARPA Topic#: 92-196 AF Topic#: 92-045 OPTICOMP CORP. PECHT ASSOC., INC AF Topic#: 92-052 Topic#: 92-099 OPTIVISION, INC. PERFORMANCE SIGNAL INTEGRITY, INC. DARPA Topic#: 92-125 DARPA Topic#: 92-148 DARPA Topic#: 92-196 PHASEX CORP. SDIO Topic#: 92-011 Topic#: 92-016 AF SDIO Topic#: 92-013 OPTOELECTRONIC DATA SYSTEMS ARMY Topic#: 92-063 PHOTONIC SYSTEMS, INC. OPTRA. INC. NAVY Topic#: 92-046 Topic#: 92-022 PHOTONICS RESEARCH, INC. AF DARPA Topic#: 92-195 ARMY Topic#: 92-120 OPTRON SYSTEMS, INC. PHOTONICS, INC. DARPA Topic#: 92-163 AF Topic#: 92-179 DNA Topic#: 92-022 PHYSICAL OPTICS CORP. SDIO Topic#: 92-011 \mathbf{AF} Topic#: 92-001 ORBITAL RESEARCH, INC. Topic#: 92-020 DARPA Topic#: 92-058 Topic#: 92-031 AF ORBITAL TECHNOLOGIES CORP. AF Topic#: 92-170 AF Topic#: 92-074 AF Topic#: 92-174 ARMY Topic#: 92-036 ORINCON CORP. ARMY Topic#: 92-047 AF Topic#: 92-031 ARMY Topic#: 92-049 ARMY Topic#: 92-026 ARMY Topic#: 92-026 ARMY Topic#: 92-121 NAVY Topic#: 92-086 NAVY Topic#: 92-127 NAVY Topic#: 92-150 ARMY Topic#: 92-065 ARMY Topic#: 92-149 DARPA Topic#: 92-132 NAVY Topic#: 92-005 **ORION INTERNATIONAL TECHNOLOGIES** NAVY Topic#: 92-077 NAVY Topic#: 92-089 DNA Topic#: 92-006 NAVY Topic#: 92-108 ORTEL CORP. NAVY Topic#: 92-169 SDIO Topic#: 92-014 SDIO Topic#: 92-001 SDIO Topic#: 92-003 SDIO Topic#: 92-011 P C DYNAMICS SDIO Topic#: 92-011 ARMY Topic#: 92-124 SDIO Topic#: 92-011 PACIFIC ADVANCED TECHNOLOGY SDIO Topic#: 92-011 ARMY Topic#: 92-036 SDIO Topic#: 92-011 PACIFIC-SIERRA RESEARCH CORP. SDIO Topic#: 92-014

DARPA Topic#: 92-100

PHYSICAL SCIENCES, INC. PSR SERVICES, INC. AF Topic#: 92-019 ARMY Topic#: 92-094 AF Topic#: 92-062 AF Topic#: 92-091 ARMY Topic#: 92-169 O-DOT, INC. DARPA Topic#: 92-166 AF Topic#: 92-048 SDIO Topic#: 92-003 Topic#: 92-059 PHYSICS MATHEMATICS & COMPUTERS, INC. DARPA Topic#: 92-070 NAVY Topic#: 92-076 DARPA Topic#: 92-172 PHYSITRON, INC. QUADRANT ENGINEERING, INC. SDIO Topic#: 92-001 AF Topic#: 92-082 PIASECKI AIRCRAFT CORP. NAVY Topic#: 92-110 NAVY Topic#: 92-129 QUANTIC INDUSTRIES, INC. PICOTRONIX, INC. Topic#: 92-171 SDIO Topic#: 92-011 **OUANTITATIVE TECHNOLOGY CORP** PLANNING SYSTEMS, INC. Topic#: 92-117 NAVY Topic#: 92-018 OUANTUM ADVANCE TECHNOLOGY, INC. PLASMATRON COATINGS & SYSTEMS, INC. DARPA Topic#: 92-042 ARMY Topic#: 92-028 **OUANTUM EPITAXIAL DESIGNS, INC.** PLEX CORP. Topic#: 92-038 DARPA Topic#: 92-194 QUEST INTEGRATED, INC. POLHEMUS LABORATORIES, INC. AF Topic#: 92-116 ARMY Topic#: 92-011 ARMY Topic#: 92-095 POWDER TECHNOLOGY, INC. ARMY Topic#: 92-104 SDIO Topic#: 92-013 NAVY Topic#: 92-109 POWER SPECTRA, INC. Topic#: 92-172 R= PRECISION COMBUSTION, INC. RADAR GUIDANCE, INC. Topic#: 92-140 ARMY Topic#: 92-057 PRINCETON ELECTRONIC SYSTEMS, INC. RADEX, INC. DARPA Topic#: 92-198 AF Topic#: 92-089 NAVY Topic#: 92-162 RADIATION SCIENCE, INC. PRINCETON MICROWAVE TECHNOLOGY, INC. SDIO Topic#: 92-003 ARMY Topic#: 92-110 RADIX TECHNOLOGIES, INC. PRINCETON SCIENTIFIC INSTRUMENTS, INC. ARMY Topic#: 92-040 ARMY Topic#: 92-174 RADKOWSKI ASSOC. PRO-TECH ARMY Topic#: 92-173 AF Topic#: 92-061 RASOR ASSOC., INC. PRODUCT DEVELOPMENT ASSISTANCE, INC. SDIO Topic#: 92-004 ARMY Topic#: 92-045 REDWOOD MICROSYSTEMS, INC. PRODUCT PLANNING, INC. DARPA Topic#: 92-058 NAVY Topic#: 92-064 REDZONE ROBOTICS, INC. **PRODUCTIVITY SOLUTIONS** ARMY Topic#: 92-143 SDIO Topic#: 92-010 **REID LABORATORIES** PROMETHEUS, INC. ARMY Topic#: 92-158 Topic#: 92-035 AF REJEN COMPANY, THE PROMETRIX CORP. AF Topic#: 92-009 DARPA Topic#: 92-193 RELMAN, INC. PROPULSION RESEARCH, INC. DARPA Topic#: 92-160 SDIO Topic#: 92-002 RESEARCH & DEVELOPMENT LABORATORIES PSI TECHNOLOGY COMPANY ARMY Topic#: 92-108 AF Topic#: 92-177 RESEARCH ASSOC. OF SYRACUSE, INC. ARMY Topic#: 92-175

RESEARCH DEVELOPMENT CORP. SAUNDERS PRODUCT DEVELOPMENT NAVY Topic#: 92-158 ARMY Topic#: 92-141 RESEARCH OPPORTUNITIES, INC. SBS ENGINEERING, INC NAVY Topic#: 92-082 ARMY Topic#: 92-037 SCHMIDT INSTRUMENTS, INC. NAVY Topic#: 92-096 NAVY Topic#: 92-135 SDIO Topic#: 92-014 SDIO Topic#: 92-007 SDIO Topic#: 92-014 SDIO Topic#: 92-014 REVEO, INC. SCHWARTZ ELECTRO-OPTICS, INC. DARPA Topic#: 92-041 SDIO Topic#: 92-011 ARMY Topic#: 92-035 RGS ASSOC., INC. DARPA Topic#: 92-010 NAVY Topic#: 92-107 NAVY Topic#: 92-062 SCIENCE & ENGINEERING ASSOC., INC. RICE LASER DARPA Topic#: 92-132 DNA Topic#: 92-008 RISON RESEARCH CORP. SCIENCE & ENGINEERING SERVICES, INC. AF Topic#: 92-019 SDIO Topic#: 92-003 ROBERT LEVI ASSOC. SCIENCE & TECHNOLOGY CORP. ARMY Topic#: 92-147 ARMY Topic#: 92-092 ROCHESTER PHOTONICS CORP. SCIENCE RESEARCH LABORATORY, INC DARPA Topic#: 92-032 ARMY Topic#: 92-122 **ROCKY RESEARCH** DARPA Topic#: 92-158 SDIO Topic#: 92-007 DNA Topic#: 92-005 SDIO Topic#: 92-001 RTWARE, INC. SDIO Topic#: 92-006 NAVY Topic#: 92-112 **SCIENTIFIC & ENGINEERING** AF Topic#: 92-050 SCIENTIFIC AERO MONITORING, INC. S.R. TAYLOR AND ASSOC. ARMY Topic#: 92-010 ARMY Topic#: 92-066 SCIENTIFIC APPLICATIONS & RESEARCH ASSOC SABBAGH ASSOC., INC. DARPA Topic#: 92-066 DARPA Topic#: 92-106 SCIENTIFIC COMPUTING ASSOC., INC. SACH SINHA AND ASSOC., INC. DARPA Topic#: 92-219 AF Topic#: 92-171 SACHSE ENGINEERING ASSOC., INC. SCIENTIFIC RESEARCH ASSOC., INC. ARMY Topic#: 92-055 NAVY Topic#: 92-105 SCIENTIFIC STUDIES CORP. SAG CORP. AF Topic#: 92-031 ARMY Topic#: 92-153 SCIENTIFIC SYSTEMS COMPANY, INC. SAN'DOIL COMPANY DARPA Topic#: 92-031 ARMY Topic#: 92-163 SCS TELECOM, INC. SANDIA SYSTEMS, INC. DARPA Topic#: 92-016 DARPA Topic#: 92-193 DARPA Topic#: 92-130 SDIO Topic#: 92-001 SECURE COMPUTING TECHNOLOGY CORP. SARCOS RESEARCH CORP. AF Topic#: 92-031 SDIO Topic#: 92-003 SDIO Topic#: 92-010 SATCON TECHNOLOGY CORP. SEGUE CORP. ARMY Topic#: 92-008 DARPA Topic#: 92-031 ARMY Topic#: 92-019 SENSOR SYSTEMS GROUP, INC. ARMY Topic#: 92-023 SDIO Topic#: 92-003 ARMY Topic#: 92-024 SENSORS UNLIMITED, INC. ARMY Topic#: 92-080 AF Topic#: 92-056 DARPA Topic#: 92-124 ARMY Topic#: 92-107 NAVY Topic#: 92-094 DARPA Topic#: 92-091 SDIO Topic#: 92-012

SDIO Topic#: 92-003

DARPA Topic#: 92-088 SDIO Topic#: 92-014 SDIO Topic#: 92-014 SDIO Topic#: 92-011 SEPARATION SYSTEMS TECHNOLOGY, INC. SPAUCHUS ASSOC., INC. NAVY Topic#: 92-092 AF Topic#: 92-098 SPEARS ASSOC., INC. **SESCO** NAVY Topic#: 92-017 DARPA Topic#: 92-119 SHERMAN M. SELTZER SPECTRA RESEARCH, INC. SDIO Topic#: 92-012 ARMY Topic#: 92-065 SHERWIN, INC. ARMY Topic#: 92-097 NAVY Topic#: 92-122 DARPA Topic#: 92-119 SIERRA MONOLITHICS, INC. NAVY Topic#: 92-180 SPECTRAL SCIENCES, INC. ARMY Topic#: 92-116 SIGMA LABS, INC. ARMY Topic#: 92-159 NAVY Topic#: 92-039 ARMY Topic#: 92-109 SDIO Topic#: 92-003 SIGNATRON ACQUISITION CORP. SPIRE CORP. NAVY Topic#: 92-048 Topic#: 92-005 SILHOUETTE TECHNOLOGY, INC. AF ARMY Topic#: 92-122 ARMY Topic#: 92-044 DARPA Topic#: 92-174 SIMPEX TECHNOLOGIES, INC. DARPA Topic#: 92-174 ARMY Topic#: 92-123 SDIO Topic#: 92-003 ARMY Topic#: 92-124 NAVY Topic#: 92-119 SDIO Topic#: 92-003 SIOUX MANUFACTURING CORP. SDIO Topic#: 92-003 SDIO Topic#: 92-013 SDIO Topic#: 92-004 SIPPICAN, INC. SDIO Topic#: 92-005 SDIO Topic#: 92-007 NAVY Topic#: 92-080 SKW CORP. SDIO Topic#: 92-011 SDIO Topic#: 92-011 AF Topic#: 92-002 SDIO Topic#: 92-014 SOHAR, INC. SDIO Topic#: 92-014 AF Topic#: 92-051 SDIO Topic#: 92-014 SONEX ENTERPRISES, INC. ARMY Topic#: 92-038 SRS TECHNOLOGIES SOUTHWALL TECHNOLOGIES, INC. AF Topic#: 92-080 ARMY Topic#: 92-068 SSG, INC. SPACE APPLICATIONS CORP. DARPA Topic#: 92-004 STANNOUS TECHNOLOGIES CORP. NAVY Topic#: 92-150 SPACE COMPUTER CORP. ARMY Topic#: 92-124 STARFIRE SYSTEMS, INC. Topic#: 92-067 DARPA Topic#: 92-173 ARMY Topic#: 92-134 STD RESEARCH CORP. DARPA Topic#: 92-196 SPACE EXPLORATION ASSOC. NAVY Topic#: 92-044 STEROIDS, LTD. ARMY Topic#: 92-111 DARPA Topic#: 92-164 ARMY Topic#: 92-162 SDIO Topic#: 92-006 SDIO Topic#: 92-004 STOTTLER HENKE ASSOC., INC. SDIO Topic#: 92-006 NAVY Topic#: 92-068 SPACE INDUSTRIES, INC. STR CORP. AF Topic#: 92-011 SPACE POWER, INC. ΑF Topic#: 92-153 STRATTON PARK ENGRG CO, INC SDIO Topic#: 92-006 SDIO Topic#: 92-014 ARMY Topic#: 92-144 STRUCTURAL COMPOSITES, INC. SPARTA, INC.

AF

AF

Topic#: 92-138

Topic#: 92-157

NAVY Topic#: 92-087

STRUCTURED MATERIALS INDUSTRIES, INC.	SYSTEMS EXPLORATION, INC.
NAVY Topic#: 92-071	AF Topic#: 92-115
SDIO Topic#: 92-014	AF Topic#: 92-154
SUBMICRON TECHNOLOGY CORP.	SYSTEMS TECHNOLOGY, INC.
DARPA Topic#: 92-076	ARMY Topic#: 92-013
SUMMATION, LTD	DARPA Topic#: 92-073
AF Topic#: 92-151	NAVY Topic#: 92-155
SUNPOWER, INC.	NAVY Topic#: 92-164
AF Topic#: 92-066	NAVY Topic#: 92-173
SUPERCONDUCTIVITY, INC.	SYUKHTUN RESEAPCH
AF Topic#: 92-013	ARMY Topic#: 92-155
SUPERCONDUCTOR TECHNOLOGIES, INC.	Market Topica. 72 133
AF Topic#: 92-106	Т
ARMY Topic#: 92-117	•
	TACAN CORP.
SDIO Topic#: 92-015	AF Topic#: 92-031
SDIO Topic#: 92-015	AF Topic#: 92-066
SUPERIOR VACUUM TECHNOLOGY, INC.	AF Topic#: 92-142
AF Topic#: 92-112	SDIO Topic#: 92-003
AF Topic#: 92-135	TAKOM COMPANY
SURFACE SOLUTIONS, INC.	SDIO Topic#: 92-008
ARMY Topic#: 92-003	TANNER RESEARCH, INC.
SURFACTANT ASSOC., INC.	DARPA Topic#: 92-156
AF Topic#: 92-006	NAVY Topic#: 92-003
SYMBIOTECH, INC.	NAVY Topic#: 92-108
ARMY Topic#: 92-166	TAU CORP.
SYNAPTICS, INC.	AF Topic#: 92-101
NAVY Topic#: 92-113	TDA RESEARCH, INC.
SYNECTICS CORP.	AF Topic#: 92-147
AF Topic#: 92-031	TE TECHNOLOGY, INC.
SYNETICS CORP.	ARMY Topic#: 92-077
AF Topic#: 92-100	TECHNICAL RESEARCH ASSOC., INC.
NAVY Topic#: 92-041	AF Topic#: 92-020
NAVY Topic#: 92-042	AF Topic#: 92-023
SYSTEM DYNAMICS INTERNATIONAL, INC.	AF Topic#: 92-028
NAVY Topic#: 92-132	•
SYSTEM ENGINEERING TECHNOLOGY SERV.	· •
ARMY Topic#: 92-034	NAVY Topic#: 92-040
SYSTEM PLANNING CORP.	NAVY Topic#: 92-096
	TECHNICAL SOLUTIONS, INC.
AF Topic#: 92-084	ARMY Topic#: 92-088
SYSTEM/TECHNOLOGY DEVELOPMENT CORP.	ARMY Topic#: 92-089
DARPA Topic#: 92-140	TECHNO-SCIENCES, INC.
SYSTEMS & PROCESSES ENGINEERING CORP.	ARMY Topic#: 92-082
ARMY Topic#: 92-047	SDIO Topic#: 92-010
SYSTEMS CONTROL TECHNOLOGY, INC.	SDIO Topic#: 92-012
DNA Topic#: 92-010	TECHNOLOGY ASSESSMENT & TRANSFER, INC.
NAVY Topic#: 92-154	AF Topic#: 92-135
SYSTEMS ENGINEERING & ANALYTICS, INC.	DARPA Topic#: 92-158
NAVY Topic#: 92-053	TECHNOLOGY DEVELOPMENT, INC.
SYSTEMS ENGINEERING ASSOC. (SEA CORP)	NAVY Topic#: 92-095
ARMY Topic#: 92-149	TECHNOLOGY INTEGRATION, INC.
SYSTEMS ENGINEERING GROUP, INC.	NAVY Topic#: 92-121
ARMY Topic#: 92-176	TECHNOLOGY INTERNATIONAL, INC.
	AF Topic#: 92-013
	· · · · · · · · · · · · · · · · · · ·

TRANS-SCIENCE CORP ARMY Topic#: 92-066 DARPA Topic#: 92-027 TECHNOLOGY SYSTEMS, INC. TRANSMET CORP. AF Tople#: 92-020 AF Topic#: 92-127 DARPA Topic#: 92-015 TRAVERSE GROUP, INC. TECHNOLOGY/ENGINEERINGMANAGEMENT, INC. Topic#: 92-008 AF NAVY Topic#: 92-081 TRF TECHNOLOGIES, INC. TECOLOTE RESEARCH, INC. ARMY Topic#: 92-125 DARPA Topic#: 92-007 TRIANGLE RESEARCH AND DEVELOPMENT CORP. TERA RESEARCH, INC. NAVY Topic#: 92-152 Topic#: 92-034 AF TRISTAN TECHNOLOGIES, INC. TETRA CORP. SDIO Topic#: 92-015 DARPA Topic#: 92-225 TRITON SYSTEMS, INC. NAVY Topic#: 92-088 ARMY Topic#: 92-134 SDIO Topic#: 92-005 TRS CERAMICS, INC. TEXAS RESEARCH INSTITUTE AUSTIN, INC. SDIO Topic#: 92-012 NAVY Topic#: 92-057 NAVY Topic#: 92-065 SDIO Topic#: 92-014 THERMACORE, INC. SDIO Topic#: 92-007 U.S. COMPOSITES CORP. THIN FILM CONCEPTS, INC. NAVY Topic#: 92-004 DARPA Topic#: 92-093 THOMAS L. CLARKE UBC, INC. DARPA Topic#: 92-017 AF Topic#: 92-157 ARMY Topic#: 92-058 TIBURON SYSTEMS, INC. UDELL TECHNOLOGIES, INC. NAVY Topic#: 92-056 AF Topic#: 92-006 TIGTEK, INC. SDIO Topic#: 92-001 UES, INC. TIMEPLUS, INC. DARPA Topic#: 92-157 SDIO Topic#: 92-013 NAVY Topic#: 92-163 NAVY Topic#: 92-179 ULTRALIFE BATTERIES, INC. TINI ALLOY COMPANY ARMY Topic#: 92-114 DARPA Topic#: 92-058 ULTRAMET ARMY Topic#: 92-003 TORANAGA TECHNOLOGIES, INC. SDIO Topic#: 92-014 ARMY Topic#: 92-053 TORREY SCIENCE & TECHNOLOGY CORP. NAVY Topic#: 92-097 NAVY Topic#: 92-125 ARMY Topic#: 92-030 NAVY Topic#: 92-024 SDIO Topic#: 92-004 TOYON RESEARCH CORP. UNIAX CORP. ARMY Topic#: 92-176 DARPA Topic#: 92-060 DARPA Topic#: 92-023 UNIQUE MOBILITY, INC. NAVY Topic#: 92-016 TPL, INC. Topic#: 92-173 UNISTRY ASSOC., INC. AF ARMY Topic#: 92-020 ARMY Topic#: 92-002 ARMY Topic#: 92-004 DARPA Topic#: 92-027 ARMY Topic#: 92-109 UNITED SIGNALS & SYSTEMS, INC. ARMY Topic#: 92-140 ARMY Topic#: 92-041 DARPA Topic#: 92-181 UNIXPROS. INC. Topic#: 92-033 NAVY Topic#: 92-095 UTILITY DEVELOPMENT CORP. NAVY Topic#: 92-131 ARMY Topic#: 92-132 NAVY Topic#: 92-176 SDIO Topic#: 92-005 SDIO Topic#: 92-012

SDIO Topic#: 92-013

DARPA Topic#: 92-128 VATELL CORP. AF Topic#: 92-004 VECTOR MICROWAVE RESEARCH CORP. NAVY Topic#: 92-168 VERITAY TECHNOLOGY, INC. NAVY Topic#: 92-040 VERSATRON CORP. NAVY Topic#: 92-015 VEXCEL CORP. ARMY Topic#: 92-088 VHDL TECHNOLOGY GROUP ARMY Topic#: 92-112 VIASAT, INC. NAVY Topic#: 92-021 NAVY Topic#: 92-022 NAVY Topic#: 92-026 VIGYAN, INC. AF Topic#: 92-122 VISIDYNE, INC. AF Topic#: 92-081 AF Topic#: 92-083 VISUAL COMPUTING SYSTEMS DARPA Topic#: 92-222 VOSS SCIENTIFIC AF Topic#: 92-061 WAMAX, INC. AF Topic#: 92-133 WARE TECHNICAL SERVICES, INC. SDIO Topic#: 92-014 WAVE III, INC. DARPA Topic#: 92-197 WEIDLINGER ASSOCIATES NAVY Topic#: 92-114 DR. WEIGHT AND ASSOC. ARMY Topic#: 92-172 WILLIAMSON CONSULTING AF Topic#: 92-153 WINDROCK, INC. AF Topic#: 92-002 WIZDOM SYSTEMS, INC. AF Topic#: 92-030 NAVY Topic#: 92-084 XYZ=== XAR INDUSTRIES, INC. AF Topic#: 92-155 XEMET, INC.

DARPA Topic#: 92-097

VAN EVERY & ASSOC.

SDIO Topic#: 92-001 SDIO Topic#: 92-007 SDIO Topic#: 92-007 XMCO, INC. AF Topic#: 92-036 XONTECH, INC. AF Topic#: 92-092 XSIRIUS SUPERCONDUCTIVITY, INC. SDIO Topic#: 92-015 YANKEE SCIENTIFIC, INC. ARMY Topic#: 92-070 ZEGER-ABRAMS, INC. AF Topic#: 92-047

ARMY Topic#: 92-001

ANAMET LABORATORIES, INC.

DYNA EAST CORP

ARMY Topic#: 92-002 GEO-CENTERS, INC. TPL, INC.

ARMY Topic#: 92-003
CERACON, INC.
FOSTER-MILLER, INC.
SURFACE SOLUTIONS, INC.
ULTRAMET

ARMY Topic#: 92-004 DCS CORP. FOSTER-MILLER, INC. TPL, INC.

ARMY Topic#: 92-005 ENSCO, INC.

ARMY Topic#: 92-006
ANALYTIC DESIGNS, INC.
BELTRAN, INC.

ARMY Topic#: 92-007
ANALYTICAL DESIGNS, INC.
GUIDED SYSTEMS TECHNOLOGIES

ARMY Topic#: 92-008

CONTINUUM DYNAMICS, INC.
SATCON TECHNOLOGY CORP.

ARMY Topic#: 92-009 EPILOGICS, INC.

ARMY Topic#: 92-010 SCIENTIFIC AERO MONITORING, INC.

ARMY Topic#: 92-011 LEEP SYSTEMS, INC. POLHEMUS LABORATORIES, INC.

ARMY Topic#: 92-012 CFD RESEARCH CORP. MICRO COMPOSITE MATERIALS CORP.

ARMY Topic#: 92-013
AMERICAN GNC CORP.
SYSTEMS TECHNOLOGY, INC.

ARMY Topic#: 92-014
COLEMAN ENGINE CORP.

ARMY Topic#: 92-015
CREW SYSTEMS CONSULTANTS

ARMY Topic#: 92-017 CORDEC CORP.

ARMY Topic#: 92-018 4D VIDEO

ARMY Topic#: 92-019 SATCON TECHNOLOGY CORP.

ARMY Topic#: 92-020 UNISTRY ASSOC., INC.

ARMY Topic#: 92-021 CERCOM, INC.

ARMY Topic#: 92-022
ABTECH CORP.
KNOWLEDGE INDUSTRIES
KNOWLEDGE SCIENCES, INC.

ARMY Topic#: 92-023
BENTHOS, INC.
SATCON TECHNOLOGY CORP.

ARMY Topic#: 92-024 SATCON TECHNOLOGY CORP.

ARMY Topic#: 92-025
BIO-IMAGING RESEARCH, INC.
NAMBETECH, INC.

ARMY Topic#: 92-026

GENERAL ATRONICS CORP.

INTL_LIGENT AUTOMATION, INC.

ORINCON CORP.

ARMY Topic#: 92-027
FOSTER-MILLER, INC.
INDUSTRIAL HONEYCOMB STRUCTURES, INC.
INDUSTRIAL HONEYCOMB STRUCTURES, INC.

ARMY Topic#: 92-028
PLASMATRON COATINGS & SYSTEMS. INC.

ARMY Topic#: 92-030
TORREY SCIENCE & TECHNOLOGY CORP.

ARMY Topic#: 92-031 CENTER FOR REMOTE SENSING

ARMY Topic#: 92-032
ADVANCED SYSTEM TECHNOLOGIES, INC.
DAINA

ARMY Topic#: 92-033
APPLIED RESEARCH ASSOC.
DYNETICS, INC.

ARMY Topic#: 92-034
ADROIT SYSTEMS, INC.
SYSTEM ENGINEERING TECHNOLOGY SERV.

ARMY Topic#: 92-035
ADVANCED MATERIALS CORP.
AURORA ASSOC.
ELECTRO-OPTEK CORP.
SCHWARTZ ELECTRO-OPTICS, INC.

ARMY Topic#: 92-036
PACIFIC ADVANCED TECHNOLOGY
PHYSICAL OPTICS CORP.

ARMY Topic#: 92-037 SBS ENGINEERING, INC.

ARMY Topic#: 92-038
ADVANCED COMPUTER SUPPORT COMPANY SONEX ENTERPRISES, INC.

ARMY Topic#: 92-039 MINARET SYSTEMS

ARMY Topic#: 92-040

RADIX TECHNOLOGIES, INC.

ARMY Topic#: 92-041
COMPUTING SERVICES SUPPORT SOLUTIONS
UNITED SIGNALS & SYSTEMS, INC.

ARMY Topic#: 92-042 I-MATH ASSOC., INC.

ARMY Topic#: 92-043 FERMIONICS CORP. MOSET CORP.

ARMY Topic#: 92-044
ADVANCED TECHNOLOGY MATERIALS, INC.
SPIRE CORP.

ARMY Topic#: 92-045
PRODUCT DEVELOPME. T ASSISTANCE, INC

ARMY Topic#: 92-046 J.K. RESEARCH

ARMY Topic#: 92-047
PHYSICAL OPTICS CORP.
SYSTEMS & PROCESSES ENGINEERING CORP.

ARMY Topic#: 92-048 MSP CORP.

ARMY Topic#: 92-049
BRIMROSE CORP. OF AMERICA
PHYSICAL OPTICS CORP.

ARMY Topic#: 92-050 DASGROUP

ARMY Topic#: 92-051 AEROPRO SYSTEMS CFD RESEARCH CORP.

ARMY Topic#: 92-052 M-DOT, INC.

ARMY Topic#: 92-053
CHAMBELL ENGINEERING, iNC.
ULTRAMET

ARMY Topic#: 92-054 HNC, INC. ITERATED SYSTEMS, INC.

ARMY Topic#: 92-055
SCIENTIFIC RESEARCH ASSOC., INC.

ARMY Topic#: 92-056 MILLITECH CORP.

ARMY Topic#: 92-057
AURORA ASSOC.
RADAR GUIDANCE, INC.

ARMY Topic#: 92-058 UBC, INC.

ARMY Topic#: 92-059
ATLANTIC AEROSPACE ELECTRONICS CORP.
FOSTER-MILLER, INC.

ARMY Topic#: 92-060
ADVANCED TECHNOLOGY AND RESEARCH CO
OCA APPLIED OPTICS

ARMY Topic#: 92-061 M.L. ENERGIA, INC.

ARMY Topic#: 92-062 DYNETICS, INC. FASTMAN, INC.

ARMY Topic#: 92-063
OPTOELECTRONIC DATA SYSTEMS

ARMY Topic#: 92-064 ANALATOM, INC.

ARMY Topic#: 92-065
INDUSTRIAL EVOLUTION
PHYSICAL OPTICS CORP.
SPECTRA RESEARCH, INC.

ARMY Topic#: 92-066 S.R. TAYLOR AND ASSOC. TECHNOLOGY INTERNATIONAL, INC.

ARMY Topic#: 92-067 BEND RESEARCH, INC. FIBER MATERIALS, INC.

ARMY Topic#: 92-068

APPLIED POLYMER SYSTEMS, INC.
GUMBS ASSOC., INC.
SOUTHWALL TECHNOLOGIES, INC.

ARMY Topic#: 92-069
BIOELASTICS RESEACH, LTD.

ARMY Topic#: 92-070

ADVANCED MECHANICAL TECHNOLOGY, INC.
FOSTER-MILLER, INC.
YANKEE SCIENTIFIC, INC.

ARMY Topic#: 92-071 FOSTER-MILLER, INC. MISSION RESEARCH CORP.

ARMY Topic#: 92-073

¿EDERAL FABRICS

MERIX CORP.

ARMY Topic#: 92-074
MAINSTREAM ENGINEERING CORP.

ARMY Topic#: 92-075 CAPE COD RESEARCH, INC.

ARMY Topic#: 92-077

ENERGY CONVERSION DEVICES, INC.
TE TECHNOLOGY, INC.

ARMY Topic#: 92-078 FOSTER-MILLER, INC

ARMY Topic#: 92-079 EAI CORP

ARMY Topic#: 92-080
CMTG RESEARCH, INC.
ENGINEERING DEVELOPMENT CORP.
SATCON TECHNOLOGY CORP.

ARMY Fopic#:-92-082
ANALYTICAL SERVICES & MATERIALS, INC.
TECHNO-SCIENCES, INC.

ARMY Topic#: 92-084 DELFIN SYSTEMS

ARMY Topic#: 92-085 MAY

ARMY Topic#: 92-086 FOSTER-MILLER, INC.

ARMY Topic#: 92-087
HORIZONS TECHNOLOGY, INC.
NOVA MANAGEMENT, INC.

ARMY Topic#: 92-088 TECHNICAL SOLUTIONS, INC. VEXCEL CORP.

ARMY Topic#: 92-089 NOVA MANAGEMENT, INC. TECHNICAL SOLUTIONS, INC

ARMY Topic#: 92-090 AKM ASSOC., INC.

ARMY Topic#: 92-091 DOVE ELECTRONICS, INC.

ARMY Topic#: 92-092
AUTOMATIX, INC.
ONTAR CORP.
SCIENCE & TECHNOLOGY CORP.

ARMY Topic#: 92-093 FOSTER-MILLER, INC.

ARMY Topic#: 92-094 PSR SERVICES, INC.

ARMY Topic#: 92-095
BIO-IMAGING RESEARCH, INC.
INDUSTRIAL QUALITY, INC.
QUEST INTEGRATED, INC.

ARMY Topic#: 92-096
HARRIS TECHNOLOGIES, INC.

ARMY Topic#: 92-097 SPECTRA RESEARCH, INC.

ARMY Topic#: 92-098
INTERFACE TECHNOLOGIES
MAK TECHNOLOGIES, INC.

ARMY Topic#: 92-099

AMERICAN RESEARCH CORP. OF VIRGINIA

ARMY Topic#: 92-100 BUSEK CO., INC. INRAD, INC.

ARMY Topic#: 92-101
BIO-TECHNICAL RESOURCES

ARMY Topic#: 92-102
DIRECTED TECHNOLOGIES, INC.
MATERIALS & ELECTROCHEMICAL RESEARCH

ARMY Topic#: 92-103
BIOLOGICAL COMPONENTS CORP. (BCC)

ARMY Topic#: 92-104
QUEST INTEGRATED, INC.

ARMY Topic#: 92-105 ENIG ASSOC., INC.

ARMY Topic#: 92-106
GUMBS ASSOC., INC.
KARS' ADVANCED MATERIALS, INC.

ARMY Topic#: 92-107
SENSORS UNLIMITED, INC.

ARMY Topic#: 92-108
RESEARCH & DEVELOPMENT LABORATORIES

ARMY Topic#: 92-109 SIGMA LABS, INC. TPL, INC.

ARMY Topic#: 92-110

ELECTROMAGNETIC APPLICATIONS, INC.
PRINCETON MICROWAVE TECHNOLOGY, INC.

ARMY Topic#: 92-111
SPACE EXPLORATION ASSOC

ARMY Topic#: 92-112 VHDL TECHNOLOGY GROUP

ARMY Topic#: 92-113
MICROSYSTEMS ENGINEERING, INC.

ARMY Topic#: 92-114
ULTRALIFE BATTERIES, INC.

ARMY Topic#: 92-115 COVALENT ASSOC., INC.

ARMY Topic#: 92-116
SIERRA MONOLITHICS, INC.

ARMY Topic#: 92-117
SUPERCONDUCTOR TECHNOLOGIES, INC.

ARMY Topic#: 92-118 FERMIONICS CORP.

ARMY Topic#: 92-119
ATLANTIC AEROSPACE ELECTRONICS CORP.

ARMY Topic#: 92-120 FOSTER-MILLER, INC. PHOTONICS RESEARCH, INC.

ARMY Topic#: 92-121 ORINCON CORP.

ARMY Topic#: 92-122 ROCHESTER PHOTONICS CORP. SILHOUETTE TECHNOLOGY, INC.

ARMY Topic#: 92-123
SIMPEX TECHNOLOGIES, INC.

ARMY Topic#: 92-124
COLONIAL CIRCUITS, INC.
CONTAMINATION STUDIES LABORATORY
GRAPHIC RESEARCH, INC.
P C DYNAMICS
SIMPEX TECHNOLOGIES, INC.
STANNOUS TECHNOLOGIES CORP.

ARMY Topic#: 92-125 TRF TECHNOLOGIES, INC.

ARMY Topic#: 92-126
HITTITE MICROWAVE CORP.

ARMY Topic#: 92-127
BERKELEY RESEARCH ASSOC., INC.

ARMY Topic#: 92-128
DEFENSE RESEARCH TECHNOLOGIES, INC.

ARMY Topic#: 92-129 INTERSCIENCE, INC.

ARMY Topic#: 92-130 DASGROUP

ARMY Topic#: 92-131
ADVANCED TECHNOLOGY MATERIALS, INC.
MATERIALS & ELECTROCHEMICAL RESEARCH

ARMY Topic#: 92-132 UTILITY DEVELOPMENT CORP.

ARMY Topic#: 92-133
AUTOMATIX, INC.
FOSTER-MILLER, INC.
KARTA TECHNOLOGY, INC.

AKMY Topic#: 92-134 STARFIRE SYSTEMS, INC TRITON SYSTEMS, INC.

ARMY Topic#: 92-135 MSNW, INC.

ARMY Topic#: 92-137
MATERIALS MODIFICATION, INC.

ARMY Topic#: 92-139
ANALYTIC DESIGNS, INC.
DECISION-SCIENCE APPLICATIONS, INC.

ARMY Topic#: 92-140 TPL, INC.

ARMY Topic#: 92-141

EASTPORT INTERNATIONAL, INC.
PAI CORP.
SAUNDERS PRODUCT DEVELOPMENT

ARMY Topic#: 92-143
INNOVATIVE DYNAMICS, INC.
REDZONE ROBOTICS, INC.

ARMY Topic#: 92-144 STRATTON PARK ENGRG CO, INC.

ARMY Topic#: 92-145
ANALYTICAL SPECTRAL DEVICES, INC.
BRIMROSE CORP. OF AMERICA

ARMY Topic#: 92-146 ESEA

ARMY Topic#: 92-147

CYBERNET SYSTEMS CORP.

ROBERT LEVI ASSOC.

ARMY Topic#: 92-148 ESEA

ARMY Topic#: 92-149
PHYSICAL OPTICS CORP.
SYSTEMS ENGINEERING ASSOC. (SEA CORP)

ARMY Topic#: 92-150
GREEN MOUNTAIN RADIO RESEARCH CO.

ARMY Topic#: 92-151

ELECTROKINETICS, INC.
LYNNTECH, INC.

ARMY Topic#: 92-152 KVH INDUSTRIES, INC.

ARMY Topic#: 92-153

OPERATIONAL TECHNOLOGIES CORP.
SAG CORP.

ARMY Topic#: 92-154
ADVANCED SCIENTIFIC CONCEPTS, INC.
MANAGEMENT RESEARCH INSTITUTE

ARMY Topic#: 92-155 SYUKHTUN RESEARCH

ARMY Topic#: 92-158
REID LABORATORIES

ARMY Topic#: 92-177
AMERICAN POWER JET COMPANY
LB&M ASSOC., INC.

ARMY Topic#: 92-159 SPECTRAL SCIENCES, INC.

ARMY Topic#: 92-160
CHARLES RIVER ANALYTICS, INC.
NOISE REMOVAL SYSTEMS

ARMY Topic#: 92-162
HYGEIA PHARMACEUTICALS, INC.
STEROIDS, LTD.

ARMY Topic#: 92-163 SAN'DOIL COMPANY

ARMY Topic#: 92-166 SYMBIOTECH, INC.

ARMY Topic#: 92-169
PHYSICAL SCIENCES, INC.

ARMY Topic#: 92-170
APPLIED TECHNOLOGY ASSOC., INC.

ARMY Topic#: 92-171
MATERIALS & ELECTROCHEMICAL RESEARCH

ARMY Topic#: 92-172
AERONIX, INC.
DR. WEIGHT AND ASSOC.
HUNTINGTON RESEARCH AND ENGINEERING
INTELLIGENT REASONING SYSTEMS

ARMY Topic#: 92-173 KTECH CORP. RADKOWSKI ASSOC.

ARMY Topic#: 92-174
PRINCETON SCIENTIFIC INSTRUMENTS, INC.

ARMY Topic#: 92-175
MAYFLOWER COMMUNICATIONS CO., INC. RESEARCH ASSOC. OF SYRACUSE, INC.

ARMY Topic#: 92-176
DANIEL H. WAGNER ASSOC., INC.
SYSTEMS ENGINEERING GROUP, INC.
TOYON RESEARCH CORP.

DEPARTMENT OF DEFENSE SMALL AND DISADVANTAGED BUSINESS UTILIZATION 3061 DEFENSE PENTAGON WASHINGTON, DC 20301-3061

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

DO NOT FORWARD, DO NOT RETURN

Third Class